

PolynomialLR#

https://pytorch.org/docs/stable/generated/torch.optim.lr_scheduler.PolynomialLR.html

Description:

Decays the learning rate of each parameter group using a polynomial function in the given total_iters. When last_epoch=-1, sets initial lr as lr.

optimizer (Optimizer) – Wrapped optimizer. total_iters (int) – The number of steps that the scheduler decays the learning rate. Default: 5. power (float) – The power of the polynomial. Default: 1.0.

Function Signature

```
class torch.optim.lr_scheduler.PolynomialLR(optimizer,  
total_iters=5, power=1.0, last_epoch=-1)[source]#
```

Parameters

```
get_last_lr()[source]#
```

Return type

```
get_lr()[source]#
```

Returns:

dict[str, Any]

Code Examples

```
>>> # Assuming optimizer uses lr = 0.05 for all groups
>>> # lr = 0.0490    if epoch == 0
>>> # lr = 0.0481    if epoch == 1
>>> # lr = 0.0472    if epoch == 2
>>> # ...
>>> # lr = 0.0       if epoch >= 50
>>> scheduler = PolynomialLR(optimizer, total_iters=50,
power=0.9)
>>> for epoch in range(100):
>>>     train(...)
>>>     validate(...)
>>>     scheduler.step()
```

Detailed Documentation

Documentation

Decays the learning rate of each parameter group using a polynomial function in the given `total_iters`.

When `last_epoch=-1`, sets initial lr as lr.

`optimizer (Optimizer)` – Wrapped optimizer.

`total_iters (int)` – The number of steps that the scheduler decays the learning rate. Default: 5.

`power (float)` – The power of the polynomial. Default: 1.0.

Return last computed learning rate by current scheduler.

Compute the learning rate.

Load the scheduler's state.

`state_dict (dict)` – scheduler state. Should be an object returned from a call to `state_dict()`.

Return the state of the scheduler as a dict.

It contains an entry for every variable in `self.__dict__` which is not the optimizer.

