

SequentialLR#

https://pytorch.org/docs/stable/generated/torch.optim.lr_scheduler.SequentialLR.html

Description:

Contains a list of schedulers expected to be called sequentially during the optimization process. Specifically, the schedulers will be called according to the milestone points, which should provide exact intervals by which each scheduler should be called at a given epoch. optimizer (Optimizer) – Wrapped optimizer. schedulers (list) – List of chained schedulers. milestones (list) – List of integers that reflects milestone points.

Function Signature

```
class torch.optim.lr_scheduler.SequentialLR(optimizer,  
schedulers, milestones, last_epoch=-1)[source]#
```

Parameters

```
get_last_lr()[source]#
```

Return type

```
get_lr()[source]#
```

Returns:

dict[str, Any]

Code Examples

```
>>> # Assuming optimizer uses lr = 0.05 for all groups
>>> # lr = 0.005      if epoch == 0
>>> # lr = 0.005      if epoch == 1
>>> # lr = 0.005      if epoch == 2
>>> # ...
>>> # lr = 0.05       if epoch == 20
>>> # lr = 0.045      if epoch == 21
>>> # lr = 0.0405     if epoch == 22
>>> scheduler1 = ConstantLR(optimizer, factor=0.1,
total_iters=20)
>>> scheduler2 = ExponentialLR(optimizer, gamma=0.9)
>>> scheduler = SequentialLR(
...     optimizer,
...     schedulers=[scheduler1, scheduler2],
...     milestones=[20],
... )
>>> for epoch in range(100):
>>>     train(...)
>>>     validate(...)
>>>     scheduler.step()
```

Detailed Documentation

Documentation

Contains a list of schedulers expected to be called sequentially during the optimization process.

Specifically, the schedulers will be called according to the milestone points, which should provide exact intervals by which each scheduler should be called at a given epoch.

optimizer (Optimizer) – Wrapped optimizer.

schedulers (list) – List of chained schedulers.

milestones (list) – List of integers that reflects milestone points.

last_epoch (int) – The index of last epoch. Default: -1.

Return last computed learning rate by current scheduler.

Compute learning rate using chainable form of the scheduler.

Load the scheduler's state.

state_dict (dict) – scheduler state. Should be an object returned from a call to state_dict().

Recursively undo any step performed by the initialisation of schedulers.

Return the state of the scheduler as a dict.

It contains an entry for every variable in self.__dict__ which is not the optimizer. The wrapped scheduler states will also be saved.

