

torch.accelerator.current_accelerator#

https://pytorch.org/docs/stable/generated/torch.accelerator.current_accelerator.html

Description:

Return the device of the accelerator available at compilation time. If no accelerator were available at compilation time, returns None. See `accelerator` for details. `check_available` (bool, optional) – if True, will also do a runtime check to see if the device `torch.accelerator.is_available()` on top of the compile-time check. Default: False return the current accelerator as `torch.device`.

Function Signature

```
torch.accelerator.current_accelerator(check_available=False)  
[source]#
```

Parameters

Returns

Return type

Returns:

`torch.device`

Code Examples

```
>>> # If an accelerator is available, sent the model to it
>>> model = torch.nn.Linear(2, 2)
>>> if (current_device :=
current_accelerator(check_available=True)) is not None:
>>>     model.to(current_device)
```

Notes & Warnings

NOTE Note The index of the returned `torch.device` will be `None`, please use `torch.accelerator.current_device_index()` to know the current index being used. This API does NOT poison fork. For more details, see [Poison fork in multiprocessing](#).

Detailed Documentation

Documentation

Return the device of the accelerator available at compilation time. If no accelerator were available at compilation time, returns None. See accelerator for details.

`check_available` (bool, optional) – if True, will also do a runtime check to see if the device `torch.accelerator.is_available()` on top of the compile-time check. Default: False

return the current accelerator as `torch.device`.

The index of the returned `torch.device` will be None, please use `torch.accelerator.current_device_index()` to know the current index being used. This API does NOT poison fork. For more details, see Poison fork in multiprocessing.