

# torch.accelerator.is\_available#

[https://pytorch.org/docs/stable/generated/torch.accelerator.is\\_available.html](https://pytorch.org/docs/stable/generated/torch.accelerator.is_available.html)

## Description:

Check if the current accelerator is available at runtime: it was build, all the required drivers are available and at least one device is visible. See `accelerator` for details. A boolean indicating if there is an available accelerator. This API delegates to the device-specific version of `is_available`. On CUDA, when the environment variable `PYTORCH_NVML_BASED_CUDA_CHECK=1` is set, this function will NOT poison fork. Otherwise, it will. For more details, see Poison fork in multiprocessing.

## Function Signature

---

```
torch.accelerator.is_available()[source]#
```

Returns

Return type

### Returns:

bool

## Code Examples

---

```
>>> assert torch.accelerator.is_available() "No available  
accelerators detected."
```

## Notes & Warnings

---

### NOTE

This API delegates to the device-specific version of `is_available`. On CUDA, when the environment variable `PYTORCH_NVML_BASED_CUDA_CHECK=1` is set, this function will NOT poison fork. Otherwise, it will. For more details, see [Poison fork in multiprocessing](#).

# Detailed Documentation

---

## Documentation

Check if the current accelerator is available at runtime: it was build, all the required drivers are available and at least one device is visible. See [accelerator](#) for details.

A boolean indicating if there is an available accelerator.

This API delegates to the device-specific version of `is_available`. On CUDA, when the environment variable `PYTORCH_NVML_BASED_CUDA_CHECK=1` is set, this function will NOT poison fork. Otherwise, it will. For more details, see [Poison fork](#) in [multiprocessing](#).