

torch.accelerator.is_available#

https://pytorch.org/docs/stable/generated/torch.accelerator.is_available.html

Description:

Check if the current accelerator is available at runtime: it was build, all the required drivers are available and at least one device is visible. See `accelerator` for details. A boolean indicating if there is an available accelerator. This API delegates to the device-specific version of `is_available`. On CUDA, when the environment variable `PYTORCH_NVML_BASED_CUDA_CHECK=1` is set, this function will NOT poison fork. Otherwise, it will. For more details, see Poison fork in multiprocessing.

Function Signature

```
torch.accelerator.is_available()[source]#
```

Returns

Return type

Returns:

bool

Code Examples

```
>>> assert torch.accelerator.is_available() "No available  
accelerators detected."
```

Notes & Warnings

NOTE This API delegates to the device-specific version of `is_available`. On CUDA, when the environment variable `PYTORCH_NVML_BASED_CUDA_CHECK=1` is set, this function will NOT poison fork. Otherwise, it will. For more details, see [Poison fork in multiprocessing](#).

Detailed Documentation

Documentation

Check if the current accelerator is available at runtime: it was build, all the required drivers are available and at least one device is visible. See [accelerator](#) for details.

A boolean indicating if there is an available accelerator.

This API delegates to the device-specific version of `is_available`. On CUDA, when the environment variable `PYTORCH_NVML_BASED_CUDA_CHECK=1` is set, this function will NOT poison fork. Otherwise, it will. For more details, see [Poison fork](#) in [multiprocessing](#).