

# torch.accelerator.memory.reset\_peak\_m

[https://pytorch.org/docs/stable/generated/torch.accelerator.memory.reset\\_peak](https://pytorch.org/docs/stable/generated/torch.accelerator.memory.reset_peak_memory_stats.html)

## Description:

Reset the “peak” stats tracked by the current accelerator memory allocator for a given device index. `device_index` (`torch.device`, `str`, `int`, optional) – the index of the device to target. If not given, use `torch.accelerator.current_device_index()` by default. If a `torch.device` or `str` is provided, its type must match the current accelerator device type. This function is a no-op if the memory allocator for the current accelerator has not been initialized.

## Function Signature

---

```
torch.accelerator.memory.reset_peak_memory_stats(device_index=None, /)[source]#
```

Parameters

## Notes & Warnings

---

### NOTE

Note This function is a no-op if the memory allocator for the current accelerator has not been initialized.

# Detailed Documentation

---

## Documentation

Reset the “peak” stats tracked by the current accelerator memory allocator for a given device index.

`device_index` (`torch.device`, `str`, `int`, optional) – the index of the device to target. If not given, use `torch.accelerator.current_device_index()` by default. If a `torch.device` or `str` is provided, its type must match the current accelerator device type.

This function is a no-op if the memory allocator for the current accelerator has not been initialized.

Reset the “peak” stats tracked by the current accelerator memory allocator for a given device index.

`device_index` (`torch.device`, `str`, `int`, optional) – the index of the device to target. If not given, use `torch.accelerator.current_device_index()` by default. If a `torch.device` or `str` is provided, its type must match the current accelerator device type.

This function is a no-op if the memory allocator for the current accelerator has not been initialized.