

torch.accelerator.synchronize#

<https://pytorch.org/docs/stable/generated/torch.accelerator.synchronize.html>

Description:

Wait for all kernels in all streams on the given device to complete. device (torch.device, str, int, optional) – device for which to synchronize. It must match the current accelerator device type. If not given, use torch.accelerator.current_device_index() by default. This function is a no-op if the current accelerator is not initialized.

Function Signature

```
torch.accelerator.synchronize(device=None, /)[source]#
```

Parameters

Code Examples

```
>>> assert torch.accelerator.is_available() "No available
accelerators detected."
>>> start_event = torch.Event(enable_timing=True)
>>> end_event = torch.Event(enable_timing=True)
>>> start_event.record()
>>> tensor = torch.randn(100,
device=torch.accelerator.current_accelerator())
>>> sum = torch.sum(tensor)
>>> end_event.record()
>>> torch.accelerator.synchronize()
>>> elapsed_time_ms = start_event.elapsed_time(end_event)
```

Notes & Warnings

NOTE This function is a no-op if the current accelerator is not initialized.

Detailed Documentation

Documentation

Wait for all kernels in all streams on the given device to complete.

device (torch.device, str, int, optional) – device for which to synchronize. It must match the current accelerator device type. If not given, use `torch.accelerator.current_device_index()` by default.

This function is a no-op if the current accelerator is not initialized.

Wait for all kernels in all streams on the given device to complete.

device (torch.device, str, int, optional) – device for which to synchronize. It must match the current accelerator device type. If not given, use `torch.accelerator.current_device_index()` by default.

This function is a no-op if the current accelerator is not initialized.