

LSTM#

<https://pytorch.org/docs/stable/generated/torch.nn.quantizable.LSTM.html>

Description:

A quantizable long short-term memory (LSTM). For the description and the argument types, please, refer to LSTM layers – instances of the `_LSTMLayer`. To access the weights and biases, you need to access them per layer. See examples below.

Function Signature

```
class torch.nn.quantizable.LSTM(input_size, hidden_size,  
                                num_layers=1, bias=True, batch_first=False, dropout=0.0,  
                                bidirectional=False, device=None, dtype=None, *,  
                                split_gates=False)[source]#
```

Variables

Code Examples

```
>>> import torch.nn.quantizable as nnqa
>>> rnn = nnqa.LSTM(10, 20, 2)
>>> input = torch.randn(5, 3, 10)
>>> h0 = torch.randn(2, 3, 20)
>>> c0 = torch.randn(2, 3, 20)
>>> output, (hn, cn) = rnn(input, (h0, c0))
>>> # To get the weights:
>>> print(rnn.layers[0].weight_ih)
tensor([[...]])
>>> print(rnn.layers[0].weight_hh)
AssertionError: There is no reverse path in the non-
bidirectional layer
```

Notes & Warnings

NOTE

Note To access the weights and biases, you need to access them per layer. See examples below.

Detailed Documentation

Documentation

A quantizable long short-term memory (LSTM).

For the description and the argument types, please, refer to LSTM

layers – instances of the `_LSTMLayer`

To access the weights and biases, you need to access them per layer. See examples below.

A quantizable long short-term memory (LSTM).

For the description and the argument types, please, refer to LSTM

layers – instances of the `_LSTMLayer`

To access the weights and biases, you need to access them per layer. See examples below.