

ReLU6#

<https://pytorch.org/docs/stable/generated/torch.nn.quantized.ReLU6.html>

Description:

Applies the element-wise function:

$$\text{ReLU6}(x) = \min(\max(x - x_0, 0), q(6))$$
$$\text{ReLU6}(x) = \min(\max(x_0, x), q(6))$$
, where x_0 is the zero_point, and $q(6)$ is the quantized representation of number 6. inplace (bool) – can optionally do the operation in-place. Default: False Input: (N,*) (N, *) where * means, any number of additional dimensions Output: (N,*) (N, *) (N,*) same shape as the input

Function Signature

```
class torch.nn.quantized.ReLU6(inplace=False)[source]#
```

Parameters

Shape:

Code Examples

```
>>> m = nn.quantized.ReLU6()
>>> input = torch.randn(2)
>>> input = torch.quantize_per_tensor(input, 1.0, 0,
dtype=torch.qint32)
>>> output = m(input)
```

Detailed Documentation

Documentation

Applies the element-wise function:

$\text{ReLU6}(x) = \min(\max(x - x_0, 0), q(6))$
 $\text{ReLU6}(x) = \min(\max(x - x_0, 0), q(6))$, where x_0 is the zero_point, and $q(6)$ is the quantized representation of number 6.

`inplace (bool)` – can optionally do the operation in-place. Default: False

Input: $(N, *) (N, *) (N, *)$ where * means, any number of additional dimensions

Output: $(N, *) (N, *) (N, *)$, same shape as the input

Applies the element-wise function:

$\text{ReLU6}(x) = \min(\max(x - x_0, 0), q(6))$
 $\text{ReLU6}(x) = \min(\max(x - x_0, 0), q(6))$, where x_0 is the zero_point, and $q(6)$ is the quantized representation of number 6.

`inplace (bool)` – can optionally do the operation in-place. Default: False

Input: $(N, *) (N, *) (N, *)$ where * means, any number of additional dimensions

Input: $(N, *) (N, *) (N, *)$ where * means, any number of additional dimensions

Output: $(N, *) (N, *) (N, *)$, same shape as the input

Output: $(N, *) (N, *) (N, *)$, same shape as the input

