

ObservationType#

https://pytorch.org/docs/stable/generated/torch.ao.quantization.backend_conf

Description:

An enum that represents different ways of how an operator/operator pattern should be observed this means the input and output are never observed example: x.shape, x.size this means the output will use the same observer instance as input, based on qconfig.activation example: torch.cat, maxpool this means input and output are observed with different observers, based on qconfig.activation example: conv, linear, softmax

Function Signature

```
class
torch.ao.quantization.backend_config.ObservationType(value)
[source]#

INPUT_OUTPUT_NOT_OBSERVED = 2#

OUTPUT_SHARE_OBSERVER_WITH_INPUT = 1#

OUTPUT_USE_DIFFERENT_OBSERVER_AS_INPUT = 0#
```

Detailed Documentation

Documentation

An enum that represents different ways of how an operator/operator pattern should be observed

this means the input and output are never observed example: `x.shape`, `x.size`

this means the output will use the same observer instance as input, based on `qconfig.activation` example: `torch.cat`, `maxpool`

this means input and output are observed with different observers, based on `qconfig.activation` example: `conv`, `linear`, `softmax`

An enum that represents different ways of how an operator/operator pattern should be observed

this means the input and output are never observed example: `x.shape`, `x.size`

this means the output will use the same observer instance as input, based on `qconfig.activation` example: `torch.cat`, `maxpool`

this means input and output are observed with different observers, based on `qconfig.activation` example: `conv`, `linear`, `softmax`