

convert#

<https://pytorch.org/docs/stable/generated/torch.ao.quantization.convert.html>

Description:

Converts submodules in input module to a different module according to mapping by calling `from_float` method on the target module class. And remove `qconfig` at the end if `remove_qconfig` is set to `True`. `module` – prepared and calibrated module mapping – a dictionary that maps from source module type to target module type, can be overwritten to allow swapping user defined Modules `inplace` – carry out model transformations in-place, the original module is mutated `convert_custom_config_dict` – custom configuration dictionary for `convert` function

Function Signature

```
class torch.ao.quantization.convert(module, mapping=None,
inplace=False, remove_qconfig=True, is_reference=False,
convert_custom_config_dict=None,
use_precomputed_fake_quant=False)[source]#
```

Parameters

Code Examples

```
# Example of convert_custom_config_dict:
convert_custom_config_dict = {
    # user will manually define the corresponding quantized
    # module class which has a from_observed class method that
    # converts
    # observed custom module to quantized custom module
    "observed_to_quantized_custom_module_class": {
        ObservedCustomModule: QuantizedCustomModule
    }
}
```

Detailed Documentation

Documentation

Converts submodules in input module to a different module according to mapping by calling `from_float` method on the target module class. And remove `qconfig` at the end if `remove_qconfig` is set to `True`.

`module` – prepared and calibrated module

`mapping` – a dictionary that maps from source module type to target module type, can be overwritten to allow swapping user defined Modules

`inplace` – carry out model transformations in-place, the original module is mutated

`convert_custom_config_dict` – custom configuration dictionary for convert function

`use_precomputed_fake_quant` – a flag to enable use of precomputed fake quant