

PlaceholderObserver#

<https://pytorch.org/docs/stable/generated/torch.quantization.observer.PlaceholderObserver.html>

Description:

Observer that doesn't do anything and just passes its configuration to the quantized module's `.from_float()`. Can be used for quantization to float16 which doesn't require determining ranges. `dtype` – dtype argument to the `quantize` node needed to implement the reference model spec. `quant_min` – minimum value in quantized domain (TODO: align behavior with other observers) `quant_max` – maximum value in quantized domain

Function Signature

```
class  
torch.quantization.observer.PlaceholderObserver(dtype=torch.  
float32, custom_op_name='', compute_dtype=None,  
quant_min=None, quant_max=None, qscheme=None, eps=None,  
is_dynamic=False)[source]#
```

Parameters

Detailed Documentation

Documentation

Observer that doesn't do anything and just passes its configuration to the quantized module's `.from_float()`.

Can be used for quantization to float16 which doesn't require determining ranges.

`dtype` – dtype argument to the quantize node needed to implement the reference model spec.

`quant_min` – minimum value in quantized domain (TODO: align behavior with other observers)

`quant_max` – maximum value in quantized domain

`custom_op_name` – (temporary) specify this observer for an operator that doesn't require any observation (Can be used in Graph Mode Passes for special case ops).

`compute_dtype` (deprecated) – if set, marks the future quantize function to use dynamic quantization instead of static quantization. This field is deprecated, use `is_dynamic=True` instead.

`is_dynamic` – if True, the quantize function in the reference model representation taking stats from this observer instance will use dynamic quantization.