

fuse_fx#

[https://pytorch.org/docs/stable/generated/torch.ao.quantization.quantize_fx.](https://pytorch.org/docs/stable/generated/torch.ao.quantization.quantize_fx.html)

Description:

Fuse modules like conv+bn, conv+bn+relu etc, model must be in eval mode. Fusion rules are defined in `torch.ao.quantization.fx.fusion_pattern.py` model (*) – a `torch.nn.Module` model `fuse_custom_config` (*) – custom configurations for `fuse_fx`. See `FuseCustomConfig` for more details

Function Signature

```
class torch.ao.quantization.quantize_fx.fuse_fx(model,  
fuse_custom_config=None, backend_config=None)[source]#
```

Parameters

Return type

Returns:

GraphModule

Code Examples

```
from torch.ao.quantization import fuse_fx

m = Model().eval()
m = fuse_fx(m)
```

Detailed Documentation

Documentation

Fuse modules like conv+bn, conv+bn+relu etc, model must be in eval mode. Fusion rules are defined in `torch.ao.quantization.fx.fusion_pattern.py`

`model (*)` – a `torch.nn.Module` model

`fuse_custom_config (*)` – custom configurations for `fuse_fx`. See `FuseCustomConfig` for more details

Fuse modules like conv+bn, conv+bn+relu etc, model must be in eval mode. Fusion rules are defined in `torch.ao.quantization.fx.fusion_pattern.py`

`model (*)` – a `torch.nn.Module` model

`model (*)` – a `torch.nn.Module` model

`fuse_custom_config (*)` – custom configurations for `fuse_fx`. See `FuseCustomConfig` for more details

`fuse_custom_config (*)` – custom configurations for `fuse_fx`. See `FuseCustomConfig` for more details