

torch.broadcast_shapes#

https://pytorch.org/docs/stable/generated/torch.broadcast_shapes.html#torch.broadcast_shapes

Description:

Similar to `broadcast_tensors()` but for shapes. This is equivalent to `torch.broadcast_tensors(*map(torch.empty, shapes))[0].shape` but avoids the need create to intermediate tensors. This is useful for broadcasting tensors of common batch shape but different rightmost shape, e.g. to broadcast mean vectors with covariance matrices. `*shapes` (`torch.Size`) – Shapes of tensors. A shape compatible with all input shapes.

Function Signature

```
torch.broadcast_shapes(*shapes) → Size[source]#
```

Parameters

Returns

Return type

Raises

Returns:

shape (torch.Size)

Code Examples

```
>>> torch.broadcast_shapes((2,), (3, 1), (1, 1, 1))  
torch.Size([1, 3, 2])
```

Detailed Documentation

Documentation

Similar to `broadcast_tensors()` but for shapes.

This is equivalent to `torch.broadcast_tensors(*map(torch.empty, shapes))[0].shape` but avoids the need create to intermediate tensors. This is useful for broadcasting tensors of common batch shape but different rightmost shape, e.g. to broadcast mean vectors with covariance matrices.

*shapes (torch.Size) – Shapes of tensors.

A shape compatible with all input shapes.

RuntimeError – If shapes are incompatible.

Similar to `broadcast_tensors()` but for shapes.

This is equivalent to `torch.broadcast_tensors(*map(torch.empty, shapes))[0].shape` but avoids the need create to intermediate tensors. This is useful for broadcasting tensors of common batch shape but different rightmost shape, e.g. to broadcast mean vectors with covariance matrices.

*shapes (torch.Size) – Shapes of tensors.

A shape compatible with all input shapes.

RuntimeError – If shapes are incompatible.
