

torch.compiler.cudagraph_mark_step_begin

https://pytorch.org/docs/stable/generated/torch.compiler.cudagraph_mark_step_begin.html

Description:

Indicates that a new iteration of inference or training is about to begin. CUDA Graphs will free tensors of a prior iteration. A new iteration is started on each invocation of `torch.compile`, so long as there is not a pending backward that has not been called. If that heuristic is wrong, such as in the following example, manually mark it with this api. For more details, see `torch.compiler_cudagraph_trees`

Function Signature

```
torch.compiler.cudagraph_mark_step_begin()[source]#
```

Code Examples

```
@torch.compile(mode="reduce-overhead")
def rand_foo():
    return torch.rand([4], device="cuda")

for _ in range(5):
    torch.compiler.cudagraph_mark_step_begin()
    rand_foo() + rand_foo()
```

Detailed Documentation

Documentation

Indicates that a new iteration of inference or training is about to begin.

CUDA Graphs will free tensors of a prior iteration. A new iteration is started on each invocation of `torch.compile`, so long as there is not a pending backward that has not been called.

If that heuristic is wrong, such as in the following example, manually mark it with this api.

For more details, see `torch.compiler_cudagraph_trees`

Indicates that a new iteration of inference or training is about to begin.

CUDA Graphs will free tensors of a prior iteration. A new iteration is started on each invocation of `torch.compile`, so long as there is not a pending backward that has not been called.

If that heuristic is wrong, such as in the following example, manually mark it with this api.

For more details, see `torch.compiler_cudagraph_trees`