

torch.dspllit#

<https://pytorch.org/docs/stable/generated/torch.dspllit.html#torch.dspllit>

Description:

Splits input, a tensor with three or more dimensions, into multiple tensors depthwise according to indices_or_sections. Each split is a view of input. This is equivalent to calling `torch.tensor_split(input, indices_or_sections, dim=2)` (the split dimension is 2), except that if indices_or_sections is an integer it must evenly divide the split dimension or a runtime error will be thrown. This function is based on NumPy's `numpy.dspllit()`. input (Tensor) – tensor to split. indices_or_sections (int or list or tuple of ints) – See argument in `torch.tensor_split()`.

Function Signature

`torch.dspllit(input, indices_or_sections) → List of Tensors#`

Parameters

Code Examples

```
>>> t = torch.arange(16.0).reshape(2, 2, 4)
>>> t
tensor([[[ 0.,  1.,  2.,  3.],
         [ 4.,  5.,  6.,  7.]],
        [[ 8.,  9., 10., 11.],
         [12., 13., 14., 15.]])
>>> torch.dsplitt(t, 2)
(tensor([[[ 0.,  1.],
         [ 4.,  5.]],
        [[ 8.,  9.],
         [12., 13.]]]),
 tensor([[[ 2.,  3.],
         [ 6.,  7.]],
        [[10., 11.],
         [14., 15.]])])

>>> torch.dsplitt(t, [3, 6])
(tensor([[[ 0.,  1.,  2.],
         [ 4.,  5.,  6.]],
        [[ 8.,  9., 10.],
         [12., 13., 14.]]]),
 tensor([[[ 3.],
         [ 7.]],
        [[11.],
         [15.]]]),
 tensor([], size=(2, 2, 0)))
```

Detailed Documentation

Documentation

Splits input, a tensor with three or more dimensions, into multiple tensors depthwise according to indices_or_sections. Each split is a view of input.

This is equivalent to calling `torch.tensor_split(input, indices_or_sections, dim=2)` (the split dimension is 2), except that if `indices_or_sections` is an integer it must evenly divide the split dimension or a runtime error will be thrown.

This function is based on NumPy's `numpy.dsplitle()`.

input (Tensor) – tensor to split.

indices_or_sections (int or list or tuple of ints) – See argument in `torch.tensor_split()`.