

torch.flip#

<https://pytorch.org/docs/stable/generated/torch.flip.html>

Description:

Reverse the order of an n-D tensor along given axis in dims. torch.flip makes a copy of input's data. This is different from NumPy's np.flip, which returns a view in constant time. Since copying a tensor's data is more work than viewing that data, torch.flip is expected to be slower than np.flip. input (Tensor) – the input tensor. dims (a list or tuple) – axis to flip on

Function Signature

```
torch.flip(input, dims) → Tensor#
```

Parameters

Code Examples

```
>>> x = torch.arange(8).view(2, 2, 2)
>>> x
tensor([[[ 0,  1],
          [ 2,  3]],

        [[ 4,  5],
          [ 6,  7]]])
>>> torch.flip(x, [0, 1])
tensor([[[ 6,  7],
          [ 4,  5]],

        [[ 2,  3],
          [ 0,  1]]])
```

Notes & Warnings

NOTE Note `torch.flip` makes a copy of input's data. This is different from NumPy's `np.flip`, which returns a view in constant time. Since copying a tensor's data is more work than viewing that data, `torch.flip` is expected to be slower than `np.flip`.

Detailed Documentation

Documentation

Reverse the order of an n-D tensor along given axis in dims.

`torch.flip` makes a copy of input's data. This is different from NumPy's `np.flip`, which returns a view in constant time. Since copying a tensor's data is more work than viewing that data, `torch.flip` is expected to be slower than `np.flip`.

`input` (Tensor) – the input tensor.

`dims` (a list or tuple) – axis to flip on

Reverse the order of an n-D tensor along given axis in dims.

`torch.flip` makes a copy of input's data. This is different from NumPy's `np.flip`, which returns a view in constant time. Since copying a tensor's data is more work than viewing that data, `torch.flip` is expected to be slower than `np.flip`.

`input` (Tensor) – the input tensor.

`input` (Tensor) – the input tensor.

`dims` (a list or tuple) – axis to flip on

`dims` (a list or tuple) – axis to flip on