

torch.fliplr#

<https://pytorch.org/docs/stable/generated/torch.fliplr.html>

Description:

Flip tensor in the left/right direction, returning a new tensor. Flip the entries in each row in the left/right direction. Columns are preserved, but appear in a different order than before. Requires the tensor to be at least 2-D.

Function Signature

```
torch.fliplr(input) → Tensor#
```

Parameters

Code Examples

```
>>> x = torch.arange(4).view(2, 2)
>>> x
tensor([[0, 1],
        [2, 3]])
>>> torch.fliplr(x)
tensor([[1, 0],
        [3, 2]])
```

Notes & Warnings

NOTE Requires the tensor to be at least 2-D.

NOTE Note `torch.fliplr` makes a copy of input's data. This is different from NumPy's `np.fliplr`, which returns a view in constant time. Since copying a tensor's data is more work than viewing that data, `torch.fliplr` is expected to be slower than `np.fliplr`.

Detailed Documentation

Documentation

Flip tensor in the left/right direction, returning a new tensor.

Flip the entries in each row in the left/right direction. Columns are preserved, but appear in a different order than before.

Requires the tensor to be at least 2-D.

`torch.fliplr` makes a copy of input's data. This is different from NumPy's `np.fliplr`, which returns a view in constant time. Since copying a tensor's data is more work than viewing that data, `torch.fliplr` is expected to be slower than `np.fliplr`.

input (Tensor) – Must be at least 2-dimensional.