

torch.from_numpy#

https://pytorch.org/docs/stable/generated/torch.from_numpy.html

Description:

Creates a Tensor from a numpy.ndarray. The returned tensor and ndarray share the same memory. Modifications to the tensor will be reflected in the ndarray and vice versa. The returned tensor is not resizable. It currently accepts ndarray with dtypes of numpy.float64, numpy.float32, numpy.float16, numpy.complex64, numpy.complex128, numpy.int64, numpy.int32, numpy.int16, numpy.int8, numpy.uint8, and bool. Writing to a tensor created from a read-only NumPy array is not supported and will result in undefined behavior.

Function Signature

```
torch.from_numpy(ndarray) → Tensor#
```

Code Examples

```
>>> a = numpy.array([1, 2, 3])
>>> t = torch.from_numpy(a)
>>> t
tensor([ 1,  2,  3])
>>> t[0] = -1
>>> a
array([-1,  2,  3])
```

Notes & Warnings

WARNING

Warning Writing to a tensor created from a read-only NumPy array is not supported and will result in undefined behavior.

Detailed Documentation

Documentation

Creates a Tensor from a `numpy.ndarray`.

The returned tensor and ndarray share the same memory. Modifications to the tensor will be reflected in the ndarray and vice versa. The returned tensor is not resizable.

It currently accepts ndarray with dtypes of `numpy.float64`, `numpy.float32`, `numpy.float16`, `numpy.complex64`, `numpy.complex128`, `numpy.int64`, `numpy.int32`, `numpy.int16`, `numpy.int8`, `numpy.uint8`, and `bool`.

Writing to a tensor created from a read-only NumPy array is not supported and will result in undefined behavior.