

torch.full_like#

https://pytorch.org/docs/stable/generated/torch.full_like.html

Description:

Returns a tensor with the same size as input filled with fill_value. `torch.full_like(input, fill_value)` is equivalent to `torch.full(input.size(), fill_value, dtype=input.dtype, layout=input.layout, device=input.device)`.
input (Tensor) – the size of input will determine size of the output tensor.
fill_value – the number to fill the output tensor with. dtype (torch.dtype, optional) – the desired data type of returned Tensor. Default: if None, defaults to the dtype of input. layout (torch.layout, optional) – the desired layout of returned tensor. Default: if None, defaults to the layout of input.

Function Signature

```
torch.full_like(input, fill_value, \*, dtype=None,
layout=torch.strided, device=None, requires_grad=False,
memory_format=torch.preserve_format) → Tensor#
```

Parameters

Keyword Arguments

Parameters

Keyword

`dtype` (`torch.dtype`, optional) – the desired data type of returned Tensor. Default: if `None`, defaults to the `dtype` of input. `layout` (`torch.layout`, optional) – the desired layout of returned tensor. Default: if `None`, defaults to the layout of input. `device` (`torch.device`, optional) – the desired device of returned tensor. Default: if `None`, defaults to the device of input. `requires_grad` (`bool`, optional) – If autograd should record operations on the returned tensor. Default: `False`. `memory_format` (`torch.memory_format`, optional) – the desired memory format of returned Tensor. Default: `torch.preserve_format`.

Code Examples

```
>>> x = torch.ones(2, 3)
>>> torch.full_like(x, 3.141592)
tensor([[ 3.1416,  3.1416,  3.1416],
        [ 3.1416,  3.1416,  3.1416]])
>>> torch.full_like(x, 7)
tensor([[7., 7., 7.],
        [7., 7., 7.]])
>>> torch.full_like(x, 0.5, dtype=torch.int32)
tensor([[0, 0, 0],
        [0, 0, 0]], dtype=torch.int32)
>>> y = torch.randn(3, 4, dtype=torch.float64)
>>> torch.full_like(y, -1.0)
tensor([[ -1.,  -1.,  -1.,  -1.],
        [ -1.,  -1.,  -1.,  -1.],
        [ -1.,  -1.,  -1.,  -1.]], dtype=torch.float64)
```

Detailed Documentation

Documentation

Returns a tensor with the same size as input filled with fill_value. `torch.full_like(input, fill_value)` is equivalent to `torch.full(input.size(), fill_value, dtype=input.dtype, layout=input.layout, device=input.device)`.

input (Tensor) – the size of input will determine size of the output tensor.

fill_value – the number to fill the output tensor with.

dtype (torch.dtype, optional) – the desired data type of returned Tensor. Default: if None, defaults to the dtype of input.

layout (torch.layout, optional) – the desired layout of returned tensor. Default: if None, defaults to the layout of input.

device (torch.device, optional) – the desired device of returned tensor. Default: if None, defaults to the device of input.

requires_grad (bool, optional) – If autograd should record operations on the returned tensor. Default: False.

memory_format (torch.memory_format, optional) – the desired memory format of returned Tensor. Default: `torch.preserve_format`.