

# torch.imag#

<https://pytorch.org/docs/stable/generated/torch.imag.html>

## Description:

Returns a new tensor containing imaginary values of the self tensor. The returned tensor and self share the same underlying storage. `imag()` is only supported for tensors with complex dtypes. `input` (Tensor) – the input tensor.

## Function Signature

---

```
torch.imag(input) → Tensor#
```

Parameters

## Code Examples

---

```
>>> x=torch.randn(4, dtype=torch.cfloat)
>>> x
tensor([(0.3100+0.3553j), (-0.5445-0.7896j), (-1.6492-0.0633j),
        (-0.0638-0.8119j)])
>>> x.imag
tensor([ 0.3553, -0.7896, -0.0633, -0.8119])
```

## Notes & Warnings

---

 **WARNING** Warning `imag()` is only supported for tensors with complex dtypes.

# Detailed Documentation

---

## Documentation

Returns a new tensor containing imaginary values of the self tensor. The returned tensor and self share the same underlying storage.

`imag()` is only supported for tensors with complex dtypes.

`input (Tensor)` – the input tensor.

Returns a new tensor containing imaginary values of the self tensor. The returned tensor and self share the same underlying storage.

`imag()` is only supported for tensors with complex dtypes.

`input (Tensor)` – the input tensor.