

torch.logical_and#

https://pytorch.org/docs/stable/generated/torch.logical_and.html

Description:

Computes the element-wise logical AND of the given input tensors. Zeros are treated as False and nonzeros are treated as True. input (Tensor) – the input tensor. other (Tensor) – the tensor to compute AND with out (Tensor, optional) – the output tensor.

Function Signature

```
torch.logical_and(input, other, *, out=None) → Tensor#
```

Parameters

Keyword Arguments

Parameters

Keyword

out (Tensor, optional) – the output tensor.

Code Examples

```
>>> torch.logical_and(torch.tensor([True, False, True]),
torch.tensor([True, False, False]))
tensor([ True, False, False])
>>> a = torch.tensor([0, 1, 10, 0], dtype=torch.int8)
>>> b = torch.tensor([4, 0, 1, 0], dtype=torch.int8)
>>> torch.logical_and(a, b)
tensor([False, False,  True, False])
>>> torch.logical_and(a.double(), b.double())
tensor([False, False,  True, False])
>>> torch.logical_and(a.double(), b)
tensor([False, False,  True, False])
>>> torch.logical_and(a, b, out=torch.empty(4,
dtype=torch.bool))
tensor([False, False,  True, False])
```

Detailed Documentation

Documentation

Computes the element-wise logical AND of the given input tensors. Zeros are treated as False and nonzeros are treated as True.

input (Tensor) – the input tensor.

other (Tensor) – the tensor to compute AND with

out (Tensor, optional) – the output tensor.

Computes the element-wise logical AND of the given input tensors. Zeros are treated as False and nonzeros are treated as True.

input (Tensor) – the input tensor.

input (Tensor) – the input tensor.

other (Tensor) – the tensor to compute AND with

other (Tensor) – the tensor to compute AND with

out (Tensor, optional) – the output tensor.