

torch.logical_not#

https://pytorch.org/docs/stable/generated/torch.logical_not.html

Description:

Computes the element-wise logical NOT of the given input tensor. If not specified, the output tensor will have the bool dtype. If the input tensor is not a bool tensor, zeros are treated as False and non-zeros are treated as True. input (Tensor) – the input tensor. out (Tensor, optional) – the output tensor.

Function Signature

```
torch.logical_not(input, *, out=None) → Tensor#
```

Parameters

Keyword Arguments

Parameters

Keyword

out (Tensor, optional) – the output tensor.

Code Examples

```
>>> torch.logical_not(torch.tensor([True, False]))
tensor([False,  True])
>>> torch.logical_not(torch.tensor([0, 1, -10],
dtype=torch.int8))
tensor([ True, False, False])
>>> torch.logical_not(torch.tensor([0., 1.5, -10.],
dtype=torch.double))
tensor([ True, False, False])
>>> torch.logical_not(torch.tensor([0., 1., -10.],
dtype=torch.double), out=torch.empty(3, dtype=torch.int16))
tensor([1, 0, 0], dtype=torch.int16)
```

Detailed Documentation

Documentation

Computes the element-wise logical NOT of the given input tensor. If not specified, the output tensor will have the bool dtype. If the input tensor is not a bool tensor, zeros are treated as False and non-zeros are treated as True.

input (Tensor) – the input tensor.

out (Tensor, optional) – the output tensor.

Computes the element-wise logical NOT of the given input tensor. If not specified, the output tensor will have the bool dtype. If the input tensor is not a bool tensor, zeros are treated as False and non-zeros are treated as True.

input (Tensor) – the input tensor.

out (Tensor, optional) – the output tensor.