

torch.logical_xor#

https://pytorch.org/docs/stable/generated/torch.logical_xor.html

Description:

Computes the element-wise logical XOR of the given input tensors. Zeros are treated as False and nonzeros are treated as True. input (Tensor) – the input tensor. other (Tensor) – the tensor to compute XOR with out (Tensor, optional) – the output tensor.

Function Signature

```
torch.logical_xor(input: Tensor, other: Tensor, *, out: Optional[Tensor]) → Tensor#
```

Parameters

Keyword Arguments

Parameters

Keyword

out (Tensor, optional) – the output tensor.

Code Examples

```
>>> torch.logical_xor(torch.tensor([True, False, True]),
torch.tensor([True, False, False]))
tensor([False, False,  True])
>>> a = torch.tensor([0, 1, 10, 0], dtype=torch.int8)
>>> b = torch.tensor([4, 0, 1, 0], dtype=torch.int8)
>>> torch.logical_xor(a, b)
tensor([ True,  True, False, False])
>>> torch.logical_xor(a.double(), b.double())
tensor([ True,  True, False, False])
>>> torch.logical_xor(a.double(), b)
tensor([ True,  True, False, False])
>>> torch.logical_xor(a, b, out=torch.empty(4,
dtype=torch.bool))
tensor([ True,  True, False, False])
```

Detailed Documentation

Documentation

Computes the element-wise logical XOR of the given input tensors. Zeros are treated as False and nonzeros are treated as True.

input (Tensor) – the input tensor.

other (Tensor) – the tensor to compute XOR with

out (Tensor, optional) – the output tensor.

Computes the element-wise logical XOR of the given input tensors. Zeros are treated as False and nonzeros are treated as True.

input (Tensor) – the input tensor.

input (Tensor) – the input tensor.

other (Tensor) – the tensor to compute XOR with

other (Tensor) – the tensor to compute XOR with

out (Tensor, optional) – the output tensor.