

torch.rand_like#

https://pytorch.org/docs/stable/generated/torch.rand_like.html#torch.rand_like

Description:

Returns a tensor with the same size as input that is filled with random numbers from a uniform distribution on the interval $[0,1)[0, 1)[0,1)$. `torch.rand_like(input)` is equivalent to `torch.rand(input.size(), dtype=input.dtype, layout=input.layout, device=input.device)`. `input` (Tensor) – the size of input will determine size of the output tensor. `dtype` (torch.dtype, optional) – the desired data type of returned Tensor. Default: if None, defaults to the dtype of input. `layout` (torch.layout, optional) – the desired layout of returned tensor. Default: if None, defaults to the layout of input. `device` (torch.device, optional) – the desired device of returned tensor. Default: if None, defaults to the device of input.

Function Signature

```
torch.rand_like(input, *, dtype=None, layout=None,  
device=None, requires_grad=False,  
memory_format=torch.preserve_format) → Tensor#
```

Parameters

Keyword Arguments

Parameters

Keyword

`dtype` (`torch.dtype`, optional) – the desired data type of returned Tensor. Default: if `None`, defaults to the `dtype` of input. `layout` (`torch.layout`, optional) – the desired layout of returned tensor. Default: if `None`, defaults to the layout of input. `device` (`torch.device`, optional) – the desired device of returned tensor. Default: if `None`, defaults to the device of input. `requires_grad` (`bool`, optional) – If autograd should record operations on the returned tensor. Default: `False`. `memory_format` (`torch.memory_format`, optional) – the desired memory format of returned Tensor. Default: `torch.preserve_format`.

Detailed Documentation

Documentation

Returns a tensor with the same size as input that is filled with random numbers from a uniform distribution on the interval $[0,1)[0, 1)[0,1)$. `torch.rand_like(input)` is equivalent to `torch.rand(input.size(), dtype=input.dtype, layout=input.layout, device=input.device)`.

`input` (Tensor) – the size of input will determine size of the output tensor.

`dtype` (torch.dtype, optional) – the desired data type of returned Tensor. Default: if None, defaults to the dtype of input.

`layout` (torch.layout, optional) – the desired layout of returned tensor. Default: if None, defaults to the layout of input.

`device` (torch.device, optional) – the desired device of returned tensor. Default: if None, defaults to the device of input.

`requires_grad` (bool, optional) – If autograd should record operations on the returned tensor. Default: False.

`memory_format` (torch.memory_format, optional) – the desired memory format of returned Tensor. Default: `torch.preserve_format`.