

torch.randint_like#

https://pytorch.org/docs/stable/generated/torch.randint_like.html

Description:

Returns a tensor with the same shape as Tensor input filled with random integers generated uniformly between low (inclusive) and high (exclusive).
input (Tensor) – the size of input will determine size of the output tensor.
low (int, optional) – Lowest integer to be drawn from the distribution. Default: 0.
high (int) – One above the highest integer to be drawn from the distribution.
dtype (torch.dtype, optional) – the desired data type of returned Tensor. Default: if None, defaults to the dtype of input.

Function Signature

```
torch.randint_like(input, low=0, high, \*, dtype=None, layout=torch.strided, device=None, requires_grad=False, memory_format=torch.preserve_format) → Tensor#
```

Parameters

Keyword Arguments

Parameters

Keyword

`dtype` (`torch.dtype`, optional) – the desired data type of returned Tensor. Default: if `None`, defaults to the `dtype` of input. `layout` (`torch.layout`, optional) – the desired layout of returned tensor. Default: if `None`, defaults to the layout of input. `device` (`torch.device`, optional) – the desired device of returned tensor. Default: if `None`, defaults to the device of input. `requires_grad` (`bool`, optional) – If autograd should record operations on the returned tensor. Default: `False`. `memory_format` (`torch.memory_format`, optional) – the desired memory format of returned Tensor. Default: `torch.preserve_format`.

Detailed Documentation

Documentation

Returns a tensor with the same shape as Tensor input filled with random integers generated uniformly between low (inclusive) and high (exclusive).

input (Tensor) – the size of input will determine size of the output tensor.

low (int, optional) – Lowest integer to be drawn from the distribution. Default: 0.

high (int) – One above the highest integer to be drawn from the distribution.

dtype (torch.dtype, optional) – the desired data type of returned Tensor. Default: if None, defaults to the dtype of input.

layout (torch.layout, optional) – the desired layout of returned tensor. Default: if None, defaults to the layout of input.

device (torch.device, optional) – the desired device of returned tensor. Default: if None, defaults to the device of input.

requires_grad (bool, optional) – If autograd should record operations on the returned tensor. Default: False.

memory_format (torch.memory_format, optional) – the desired memory format of returned Tensor. Default: torch.preserve_format.