

torch.randint#

<https://pytorch.org/docs/stable/generated/torch.randint.html#torch.randint>

Description:

Returns a tensor filled with random integers generated uniformly between low (inclusive) and high (exclusive). The shape of the tensor is defined by the variable argument size. With the global dtype default (torch.float32), this function returns a tensor with dtype torch.int64. low (int, optional) – Lowest integer to be drawn from the distribution. Default: 0.

Function Signature

```
torch.randint(low=0, high, size, \*, generator=None,  
out=None, dtype=None, layout=torch.strided, device=None,  
requires_grad=False) → Tensor#
```

Parameters

Keyword Arguments

Parameters

Keyword

generator (torch.Generator, optional) – a pseudorandom number generator for sampling out (Tensor, optional) – the output tensor. dtype (torch.dtype, optional) – the desired data type of returned tensor. Default: if None, this function returns a tensor with dtype torch.int64. layout (torch.layout, optional) – the desired layout of returned Tensor. Default: torch.strided. device (torch.device, optional) – the desired device of returned tensor. Default: if None, uses the current device for the default tensor type (see torch.set_default_device()). device will be the CPU for CPU tensor types and the current CUDA device for CUDA tensor types. requires_grad (bool, optional) – If autograd should record operations on the returned tensor. Default: False.

Code Examples

```
>>> torch.randint(3, 5, (3,))
tensor([4, 3, 4])

>>> torch.randint(10, (2, 2))
tensor([[0, 2],
        [5, 5]])

>>> torch.randint(3, 10, (2, 2))
tensor([[4, 5],
        [6, 7]])
```

Notes & Warnings

NOTE

Note With the global dtype default (torch.float32), this function returns a tensor with dtype torch.int64.

Detailed Documentation

Documentation

Returns a tensor filled with random integers generated uniformly between low (inclusive) and high (exclusive).

The shape of the tensor is defined by the variable argument size.

With the global dtype default (`torch.float32`), this function returns a tensor with dtype `torch.int64`.

low (int, optional) – Lowest integer to be drawn from the distribution. Default: 0.

high (int) – One above the highest integer to be drawn from the distribution.

size (tuple) – a tuple defining the shape of the output tensor.

generator (`torch.Generator`, optional) – a pseudorandom number generator for sampling

out (`Tensor`, optional) – the output tensor.

dtype (`torch.dtype`, optional) – the desired data type of returned tensor. Default: if None, this function returns a tensor with dtype `torch.int64`.

layout (`torch.layout`, optional) – the desired layout of returned Tensor. Default: `torch.strided`.

device (`torch.device`, optional) – the desired device of returned tensor. Default: if None, uses the current device for the default tensor type (see `torch.set_default_device()`). device will be the CPU for CPU tensor types and the current CUDA device for CUDA tensor types.

requires_grad (bool, optional) – If autograd should record operations on the returned tensor. Default: False.