

# torch.renorm#

<https://pytorch.org/docs/stable/generated/torch.renorm.html#torch.renorm>

## Description:

Returns a tensor where each sub-tensor of input along dimension dim is normalized such that the p-norm of the sub-tensor is lower than the value maxnorm. If the norm of a row is lower than maxnorm, the row is unchanged. input (Tensor) – the input tensor. p (float) – the power for the norm computation.

## Function Signature

---

```
torch.renorm(input, p, dim, maxnorm, *, out=None) → Tensor#
```

Parameters

Keyword Arguments

## Parameters

---

### Keyword

out (Tensor, optional) – the output tensor.

## Code Examples

---

```
>>> x = torch.ones(3, 3)
>>> x[1].fill_(2)
tensor([ 2.,  2.,  2.])
>>> x[2].fill_(3)
tensor([ 3.,  3.,  3.])
>>> x
tensor([[ 1.,  1.,  1.],
        [ 2.,  2.,  2.],
        [ 3.,  3.,  3.]])
>>> torch.renorm(x, 1, 0, 5)
tensor([[ 1.0000,  1.0000,  1.0000],
        [ 1.6667,  1.6667,  1.6667],
        [ 1.6667,  1.6667,  1.6667]])
```

## Notes & Warnings

---

**NOTE** If the norm of a row is lower than maxnorm, the row is unchanged

# Detailed Documentation

---

## Documentation

Returns a tensor where each sub-tensor of input along dimension dim is normalized such that the p-norm of the sub-tensor is lower than the value maxnorm

If the norm of a row is lower than maxnorm, the row is unchanged

input (Tensor) – the input tensor.

p (float) – the power for the norm computation

dim (int) – the dimension to slice over to get the sub-tensors

maxnorm (float) – the maximum norm to keep each sub-tensor under

out (Tensor, optional) – the output tensor.

Returns a tensor where each sub-tensor of input along dimension dim is normalized such that the p-norm of the sub-tensor is lower than the value maxnorm

If the norm of a row is lower than maxnorm, the row is unchanged

input (Tensor) – the input tensor.

input (Tensor) – the input tensor.

p (float) – the power for the norm computation

p (float) – the power for the norm computation

`dim (int)` – the dimension to slice over to get the sub-tensors

`dim (int)` – the dimension to slice over to get the sub-tensors

`maxnorm (float)` – the maximum norm to keep each sub-tensor under

`maxnorm (float)` – the maximum norm to keep each sub-tensor under

`out (Tensor, optional)` – the output tensor.