

torch.set_flush_denormal#

https://pytorch.org/docs/stable/generated/torch.set_flush_denormal.html#torch.set_flush_denormal

Description:

Disables denormal floating numbers on CPU. Returns True if your system supports flushing denormal numbers and it successfully configures flush denormal mode. `set_flush_denormal()` is supported on x86 architectures supporting SSE3 and AArch64 architecture. `mode` (bool) – Controls whether to enable flush denormal mode or not

Function Signature

```
torch.set_flush_denormal(mode) → bool#
```

Parameters

Code Examples

```
>>> torch.set_flush_denormal(True)
True
>>> torch.tensor([1e-323], dtype=torch.float64)
tensor([ 0.], dtype=torch.float64)
>>> torch.set_flush_denormal(False)
True
>>> torch.tensor([1e-323], dtype=torch.float64)
tensor(9.88131e-324 *
      [ 1.0000], dtype=torch.float64)
```

Detailed Documentation

Documentation

Disables denormal floating numbers on CPU.

Returns True if your system supports flushing denormal numbers and it successfully configures flush denormal mode. `set_flush_denormal()` is supported on x86 architectures supporting SSE3 and AArch64 architecture.

mode (bool) – Controls whether to enable flush denormal mode or not

Disables denormal floating numbers on CPU.

Returns True if your system supports flushing denormal numbers and it successfully configures flush denormal mode. `set_flush_denormal()` is supported on x86 architectures supporting SSE3 and AArch64 architecture.

mode (bool) – Controls whether to enable flush denormal mode or not