

torch.sparse.log_softmax#

https://pytorch.org/docs/stable/generated/torch.sparse.log_softmax.html

Description:

Applies a softmax function followed by logarithm. See softmax for more details. input (Tensor) – input dim (int) – A dimension along which softmax will be computed. dtype (torch.dtype, optional) – the desired data type of returned tensor. If specified, the input tensor is casted to dtype before the operation is performed. This is useful for preventing data type overflows. Default: None

Function Signature

```
torch.sparse.log_softmax(input, dim, *, dtype=None) → Tensor#
```

Parameters

Detailed Documentation

Documentation

Applies a softmax function followed by logarithm.

See softmax for more details.

input (Tensor) – input

dim (int) – A dimension along which softmax will be computed.

dtype (torch.dtype, optional) – the desired data type of returned tensor. If specified, the input tensor is casted to dtype before the operation is performed. This is useful for preventing data type overflows. Default: None

Applies a softmax function followed by logarithm.

See softmax for more details.

input (Tensor) – input

input (Tensor) – input

dim (int) – A dimension along which softmax will be computed.

dim (int) – A dimension along which softmax will be computed.

dtype (torch.dtype, optional) – the desired data type of returned tensor. If specified, the input tensor is casted to dtype before the operation is performed. This is useful for preventing data type overflows. Default: None

dtype (torch.dtype, optional) – the desired data type of returned tensor. If specified, the input tensor is casted to dtype before the operation is performed. This is useful for preventing data type overflows. Default: None

