

torch.sparse.softmax#

<https://pytorch.org/docs/stable/generated/torch.sparse.softmax.html>

Description:

Applies a softmax function. Softmax is defined as:

$$\text{Softmax}(x_i) = \frac{\exp(x_i)}{\sum_j \exp(x_j)}$$

where i, j run over sparse tensor indices and unspecified entries are ignored. This is equivalent to defining unspecified entries as negative infinity so that $\exp(x_k) = 0$ when the entry with index k has not specified. It is applied to all slices along `dim`, and will re-scale them so that the elements lie in the range $[0, 1]$ and sum to 1.

Function Signature

```
torch.sparse.softmax(input, dim, *, dtype=None) → Tensor#
```

Parameters

Detailed Documentation

Documentation

Applies a softmax function.

Softmax is defined as:

$$\text{Softmax}(x_i) = \frac{\exp(x_i)}{\sum_j \exp(x_j)}$$

where i, j run over sparse tensor indices and unspecified entries are ignored. This is equivalent to defining unspecified entries as negative infinity so that $\exp(x_k) = 0$ when the entry with index k has not specified.

It is applied to all slices along `dim`, and will re-scale them so that the elements lie in the range `[0, 1]` and sum to 1.

`input (Tensor)` – input

`dim (int)` – A dimension along which softmax will be computed.

`dtype (torch.dtype, optional)` – the desired data type of returned tensor. If specified, the input tensor is casted to `dtype` before the operation is performed. This is useful for preventing data type overflows. Default: None