

Plot Delineation

APPN Aerial SOP — Locked revision 1.0

APPN – Plot Delineation

This protocol defines the APPN standard for plot delineation shapefiles — their structure, attributes, and storage location within the APPN folder hierarchy — and documents the supported methods for producing them from APPN aerial imagery (typically RGB orthomosaics captured by GRYFN UAV systems). Consistent plot delineation underpins repeatable phenotypic analysis across APPN trials.

Important

The APPN plot shapefile specification below must be followed for all trials, regardless of which method is used to generate the shapefile. For any deviations from this specification or these methods (e.g. alternative tools, non-standard plot layouts), keep detailed records of the changes made, the rationale, and any implications for downstream analysis.

Important

Document status — work in progress. This protocol is a draft and requires further revision before it can be considered final. The points below capture the state of each section after the **APPN Field EWG plot-delineation meeting**. A small working group has reviewed the this document

** Still outstanding — Field EWG follow-ups:**

Methods (see Methods)

- ☐ **Mickey to write the GPT plot-creation tool** (becomes Method 3, replacing the previous "GRYFN plot tool" placeholder).
- ☐ **FIELDimageR meeting with Bipul and Mickey** — still TBC; outcomes to be folded back into Method 1.
- ☐ For the **Omega** platform, capture **vegetation width** in trial metadata so it can be used to set track width.

Document Structure

This protocol is organised so you can read it top-to-bottom for the full APPN plot delineation standard, or jump straight to the section you need. Decisions made at the **APPN Field EWG plot-delineation meeting** are reflected inline; outstanding follow-ups are flagged in the Outstanding TODOs at the top.

- APPN Plot Delineation — rationale and the competing sources of error a standard delineation approach must manage.
- Recommended Buffer — minimum inward buffer values, real-world worked examples, and when to deviate.
- APPN Plot Shapefile Standard — the mandatory file format, attributes, storage location, and naming convention every plot layout file must follow.
- File format — **GeoJSON ratified as the primary format**; shapefile retained as legacy / companion only.
- Required attributes — the ratified minimum set (**fid**, **plot_id**, **row**, **range**, **crop**) plus optional columns (**is_buffer**, **block**, etc.).

- Storage location — confirmed as `Documentation/Plot_Layout/`.
- File naming convention — sensor tag in the file name (e.g. CALVIS, GOBI, HIRES, M3M).
- Joining Trial Information — how trial metadata is attached to the plot geometry via `plot_id`.
- Methods — supported procedures for generating an APPN-compliant plot layout file.
- Method 1: FIELDimageR (QGIS)
- Method 2: DPIRD Field Mapping Tool
- Method 3: GPT plot creation tool — to be written by Mickey.

Important

Summary — the one mandatory plot file. Every APPN field site **must** have a single main plot file:

- **Filename:** `{YYYYSiteName}_plots.geojson`
- **Location:** `{Node}/{YYYY_ProjectDesc[_I|E][_Researcher][_org]}/{YYYYSiteName[_F|C]}/Documentation/Plot_Layout/`
- **Example:** `USYD_Narrabri/2025_SIF0zBarley/2025IAWatson_F/Documentation/Plot_Layout/2025IAWatson_plots.geojson`

This file is the entry point every downstream pipeline depends on. It **must** carry the mandatory standard attributes described in Required attributes. All other files (`plots_*` variants, `sampling_*`, `gcp`) are optional. See Storage location and File naming convention for details.

APPN Plot Delineation

A standard APPN plot delineation approach ensures that comparable trials can be analysed consistently across nodes. The goal is to maximise the usable plot area sampled by the aerial data while minimising two competing sources of error:

- **Edge effects** — agronomic and radiometric contamination from neighbouring plots, alleys, and bare soil at plot boundaries.
- **Positional uncertainty** — small misalignments between the plot shapefile and the orthomosaic caused by GNSS/RTK error, orthorectification residuals, and sowing/layout drift (rows bowing or skewing relative to the design grid as the seeder tracks across the trial).

In practice, this is achieved by applying a consistent inward **buffer** to each plot polygon so the analysed region sits comfortably inside the true plot extent, regardless of which method is used to generate the shapefile.

Recommended Buffer

To keep results comparable across nodes, APPN trials should apply at least the inward buffer specified in the table below to every plot polygon. The current working rule is:

Important

APPN minimum buffer (working rule): 0.3 m from each plot end and 0.2 m from each plot side (across the drill direction), **or** the width of one row — whichever is larger.

Note

The "one row width" fallback is intended to handle **sorghum and other widely-spaced crops**, where the fixed 0.2 m side buffer is narrower than a single inter-row spacing and would still capture neighbouring rows. A more general species-specific rule is still pending with the EWG.

The buffer used must be recorded in the tool-specific configuration saved alongside the shapefile (e.g. the FIELD-imageR JSON) so the layout can be reproduced.

Worked examples (real-world APPN plot sizes)

Plot size (L × W)	Min. buffer (end / side)	Analysis area (L × W)	% of plot
6 m × 2 m (common cereal yield plot)	0.3 m / 0.2 m	5.4 m × 1.6 m	~72 %
6 m × 1.5 m (DPIRD standard)	0.3 m / 0.2 m	5.4 m × 1.1 m	~66 %
4 m × 1.5 m (UOA OzBarley)	0.3 m / 0.2 m	3.4 m × 1.1 m	~62 %
10 m × 3 m (Sorghum agronomy strip)	1.0 m / 0.5 m	8.0 m × 2.0 m	~53 %

Note

Plot widths can vary substantially between trials (Ingrid — UOA), so the table is **illustrative**, not exhaustive. Apply the working rule above to any plot size not listed.

When to increase the buffer

- Coarser GSD (e.g. hyperspectral at ~5 cm vs RGB at ~1 cm).
- Tall or lodging-prone canopies where canopy lean shifts the visible plot off its sown footprint.
- Narrow alleys (<0.5 m) where neighbouring canopies merge.
- Trials without RTK GNSS or without ground control points (GCPs) in the orthomosaic.

Note

Any deviation from the default buffer must be recorded with the trial's plot layout files and justified in the trial notes.

APPN Plot Shapefile Standard

All APPN plot shapefiles must conform to the following standard so that downstream pipelines can ingest them without trial-specific configuration.

File format

- **Primary format: GeoJSON** (.geojson) — a single, plain-text, self-contained file. See File Format — GeoJSON vs Shapefile in the Aerial Data QC protocol for the full rationale (single-file packaging, version-control friendliness, no field-name length or file size caps, open web-native standard).
- **Legacy / companion format:** ESRI Shapefile (.shp plus its sidecar files .shx, .dbf, .prj, .cpg). All sidecar files must be kept together with the .shp. Existing shapefiles do **not** need to be re-created, but **all new APPN files must be saved as .geojson**.
- **CRS:** the CRS of the source orthomosaic (typically the correct zone of GDA2020). For GeoJSON, keep the file in the projected CRS of the orthomosaic rather than reprojecting to WGS84 (see the linked rationale above). For shapefiles, the .prj file must be present and correct.
- **Geometry:** one polygon per plot. Polygons should be rectangular and aligned to the trial layout, sized to the plot dimensions minus the inward buffer applied to mitigate edge effects.
- **Optional companion copy:** a second copy of the same layer in shapefile form may be saved alongside the primary GeoJSON using the **same base file name** (e.g. MyTrial_plots.geojson → MyTrial_plots.shp). This is useful for tools that only consume shapefiles, but is not required.

Required attributes

Important

Field EWG decision: the **mandatory attribute set is now ratified** — see the table below. **species** has been **removed**. Optional columns must be **omitted entirely** when no data is available (rather than carried as empty / placeholder columns).

Every APPN plot polygon **must** carry the following attributes:

Column	Required?	Description
<code>fid</code>	Mandatory	Unique polygon identifier assigned by the delineation tool. Identifies the <i>geometry</i> only and may not match the trial's plot numbering.
<code>plot_id</code>	Mandatory	Plot number from the trial design / sowing plan. Join key for trial metadata (see Joining Trial Information).
<code>row</code>	Mandatory	Row index in the trial design.
<code>range</code>	Mandatory	Range (column) index in the trial design.
<code>crop</code>	Mandatory	Crop type (e.g. <i>Wheat</i>).

Note

`fid` and `plot_id` must be kept as **separate columns**. `fid` is the tool's internal polygon ID; `plot_id` is the agronomic plot number from the trial design. Conflating the two breaks reproducibility when the shapefile is regenerated and `fid` values shift.

`plot_id` (not `fid`) is the join key for trial metadata. Trial information arrives in a wide range of formats and structures across nodes and projects and cannot realistically be standardised into a single schema, so at a minimum the shapefile and the trial spreadsheet must share `plot_id` for the join described in Joining Trial Information to be performed reliably. `fid` must not be used as the join key — it is tool-assigned and may change when the shapefile is regenerated.

Optional attributes The following columns are **optional**. If the data is not available they should be **omitted entirely**.

Trial design:

- `is_buffer` — Boolean (`True/False`) flag marking *buffer plots* (filler / border plots that absorb edge effects and carry no experimental treatment). Not to be confused with the inward analysis **buffer** applied to every plot polygon (see Recommended Buffer).
- `block` — replication block / replicate identifier from the trial design. Include whenever the trial design defines blocks.

Biological / treatment:

- `genotype` / `entry` — variety, line, or accession code. If this information is proprietary, an anonymised code may be used instead.
- `treatment` — agronomic or experimental treatment applied to the plot.

Provenance (used to trace how the polygon was produced):

- `method` — delineation method (e.g. `FIELDimageR`, `DPIRD`, `GPT`).
- `buffer_end_m`, `buffer_side_m` — buffer values applied (in metres).
- `source_file` — filename or ID of the orthomosaic the polygon was fit to.
- `created` — ISO date the file was generated.
- `created_by` — Name of the person who produced the file, for provenance and follow-up queries.
- `notes` — Any additional information about creation or usage

Note

Both Method 1 (`FIELDimageR`) and Method 2 (`DPIRD Field Mapping Tool`) have their own metadata-capture conventions, and harmonising these into a single standard is still outstanding. Metadata should be saved alongside the layer file. Where additional metadata needs to be added manually, use the schema below.

```
{
  "type": "FeatureCollection",
  "name": "2025IAWatson_plots_v01",
  "crs": {
    "type": "name",
    "properties": { "name": "urn:ogc:def:crs:EPSG::7855" }
  },
  "provenance_metadata": {
    "datasetId": "2025IAWatson_plots_v01",
    "site": "2025IAWatson",
    "node": "USYD_Narrabri",
```

```

"method": "FIELDimager",
"source_file": "2025IAWatson_CALVIS_Orthomosaic.tif",
"sensor": "CALVIS",
"buffer_end_m": 0.3,
"buffer_side_m": 0.2,
"created": "2026-05-18",
"created_by": "Arden Burrell",
"originatingSystem": "QGIS 3.36 + FIELDimager",
"notes": "Buffer applied per APPN minimum working rule."
},
"features": [
{
"type": "Feature",
"geometry": {
"type": "Polygon",
"coordinates": [ [ [ /* ... */ ] ] ]
},
"properties": {
"fid": 1,
"plot_id": 1001,
"row": 1,
"range": 1,
"crop": "Wheat",
"is_buffer": false,
"block": 1,
"genotype": "Scepter",
"treatment": "NO"
}
}
/* ... one Feature per plot ... */
]
}

```

Note

`crs` should match the projected CRS of the source orthomosaic (typically the relevant GDA2020 / MGA zone — EPSG:7855 is shown here for Narrabri NSW). `provenance_metadata` is a top-level sidecar object that records how the layer was produced and mirrors the per-feature provenance attributes listed above. Per-feature `properties` must include the Required attributes and may include any of the optional attributes when the data is available.

Storage location

Save the plot layout file (GeoJSON, or shapefile with all its sidecar files) in the site-level `Documentation/Plot_Layout/` directory under the APPN folder structure (see the APPN folder structure wiki for the full naming convention).

Formal path:

```

{Node}/
{YYYY_ProjectDesc[_I|E][_Researcher][_org]}/
{YYYYSiteName[_F|C]}/Documentation/Plot_Layout/

```

Example:

```

USYD_Narrabri/2025_SIF0zBarley/2025IAWatson_F/Documentation/Plot_Layout/

```

Also save the tool-specific configuration used to generate the layout file (e.g. the FIELDimager JSON settings) alongside it so the layout can be reproduced.

Folder README

Each Plot_Layout/ folder **should** contain a README.md capturing site-specific context that doesn't fit cleanly into per-file provenance_metadata: which file is the current main plots layout, why any variant (plots_unbuffered, plots_rszone, plots_{sensor}) exists, a deprecation log, sampling-campaign notes, and any known quirks. Machine-readable provenance still lives in each file's provenance_metadata; the README is the human-readable companion for the folder as a whole.

Suggested template:

```
# Plot Layout - {YYYYSiteName}
```

Site-specific notes for the files in this folder. For the APPN-wide spec see the [\[Plot Delineation protocol\]\(../Plot_Delineation.md\)](#).

```
## Current main file
```

```
- `{YYYYSiteName}_plots.geojson` - fitted YYYY-MM-DD by <name>,
  method <FIELDimageR | DPIRD | GPT>.
```

```
## Variants in use
```

```
- `plots_unbuffered` - used by <pipeline / person> for <reason>.
- `plots_{sensor}` - justified because <CRS / portion-of-plot reason>;
  approved by EWG on <date>.
```

```
## Sampling campaigns
```

```
- `sampling_biomass_YYYYMMDD...` - operator, quadrat size, anything odd.
```

```
## Deprecated files
```

```
| File | Replaced on | Reason | Superseded by |
| --- | --- | --- | --- |
| `...plots_20250901_deprecated.geojson` | 2025-09-01 | Re-fit after RTK base correction |
| `...plots.geojson` |
```

```
## Known issues / quirks
```

```
- e.g. "HIRES flight 2025-10-12 had a 7 cm N-S offset - corrected in
  re-process."
```

File naming convention

A site's Plot_Layout/ directory holds **three families** of vector file, and the naming convention is built around that split:

1. **Plot files (plots*)** — define the **plot polygons** (the area to analyse). Every site has **one main plots file** with a short, simple name that is reused across every sensor wherever possible. Additional plot files may be added with longer, descriptive suffixes that record their more limited usage — for example, an unbuffered variant, a sensor-specific variant, or a remote-sensing- only sub-area.
2. **Sampling files (sampling_*)** — record the **portion of each plot that was actually sampled** by a destructive or in-field measurement (biomass cut, height measurement, emergence count, head count, etc.). One file per measurement type, named after the measurement.
3. **GCP file (gcp)** — **permanent ground control points only** (fixed, surveyed markers that persist across flights and seasons). Temporary or per-flight GCPs are **not** stored here — they belong with the flight that used them.

Important

The main plots file is the only mandatory vector file. Every APPN project and site **must** have a {YYYYSiteName}_plots.geojson in its Plot_Layout/ folder — it is the entry point every downstream pipeline depends on. All other files in the three families (plots_* variants, sampling_*, gcp) are **optional** and are added only when the trial actually needs them. A README.md in the folder (see Folder README) is **strongly recommended** for every site, even when only the main plots file is present.

Working format Three parallel patterns — one per family (plots, sampling, and gcp):

```
{YYYYSiteName}_plots[_{descriptor}][_{sensor}][_YYYYMMDD][_v{NN}][_deprecated].{ext} # plot files
{YYYYSiteName}_sampling_{measurement}[_{YYYYMMDD}][_v{NN}][_deprecated].{ext} # sampling files
{YYYYSiteName}_gcp[_{YYYYMMDD}][_v{NN}][_deprecated].{ext} # ground control points
```

Common fields (apply to all three patterns):

Field	Notes
{YYYYSiteName}	Site identifier (year + site name), matching the parent folder name with the _F suffix dropped. Plot layouts only apply to field sites.
{YYYYMMDD}	Optional ISO-style date tag (e.g. 20251104) identifying the date the file applies to — typically the sampling / measurement date on sampling files.
_v{NN}	Optional zero-padded revision (_v01, _v02, ...). Bump on any change to geometry or attributes.
_deprecated	Optional terminal tag flagging a file that has been superseded but retained for provenance (e.g. the older revision of a re-fit plot layout).
{ext}	geojson (mandated primary). shp (with sidecars) is also accepted as a legacy / companion file.

Plot-file fields (plots[_{descriptor}][_{sensor}]):

Field	Notes
{descriptor}	Optional short tag for a non-default plot variant (unbuffered, rszone, ...). Omit on the main file.
{sensor}	Optional sensor tag — use the platform name (CALVIS, GOBI, HIRES, M3M). Only add a sensor-specific file when the geometry genuinely differs —

Sampling-file fields (sampling_{measurement}):

Field	Notes
{measurement}	Mandatory on sampling files. Short tag identifying the measurement type (biomass, height, emergence, headcount, ...).

Plot file tags

- **plots** — **the main file**. Primary analysis layout (one polygon per plot, buffer applied per the APPN Plot Shapefile Standard). Used by every sensor unless a sensor-specific variant is justified.

Note

The main **plots** file is the entry point every downstream pipeline looks for, so it should keep its **short, unversioned name** ({YYYYSiteName}_plots.geojson) for the life of the trial. When the layout is re-fit and a new version supersedes the current main file, **prefer the _deprecated tag over bumping _v{NN} on the main file** — rename the old file to {YYYYSiteName}_plots_{YYYYMMDD}_deprecated.geojson (date tag disambiguates multiple deprecations) and save the new layout back under the plain {YYYYSiteName}_plots.geojson name. This keeps the main file easy to find and unambiguous, and keeps older copies clearly marked as superseded.

- **plots_unbuffered** — full plot footprint with **no inward analysis buffer**, for cases where the entire plot area is needed.
- **plots_rszone** — sub-area within each plot **reserved for remote sensing** and kept off-limits to destructive sampling.
- **plots_{sensor}** — sensor-specific geometry variant, where {sensor} is the platform name (CALVIS, GOBI, HIRES, or M3M). Only create one when the sensor geometry genuinely differs (see 5 cm rule above).

Important

When a plots_{sensor} file is justified. A sensor-specific plot file should only be created when the sensor *systematically* needs different polygons from the main **plots** file. The two accepted justifications are:

1. **The sensor exports in a different CRS** and cannot be reprojected losslessly into the standard GDA2020 / MGA zone of the main **plots** file.
2. **The sensor captures a different portion of the plot** (e.g. Omega capturing the entire plot without buffer), so a single shared polygon would systematically clip or over-extend the analysis area.

Hard rule: if plot-file differences **within a single sensor** exceed **~5 cm**, do **not** create extra files to work

around them — escalate and address the root cause (georeferencing, orthorectification, GCPs).

Strongly discouraged: stacking further tags such as `plots_{sensor}_{YYYYMMDD}` — or, worse, `plots_{sensor}_{YYYYMMDD}_{run}` — to paper over a single bad run (e.g. one flight with the wrong CRS or a spatial misalignment). This fragments the plot layout across files, breaks downstream pipelines that key on the main `plots` file, and hides a real data-capture problem. Re-process the offending run instead. Per-run overrides at this level are a **last resort** — use only after all other attempts to fix the data have failed, and record the justification in the file's `provenance_metadata.notes`.

Sampling file tags One file per measurement type. Extensible — add new tags as new measurements are introduced.

- `sampling_biomass` — footprints of biomass cuts within each plot. Whole-plot biomass collection (e.g. UOA all-of-plot workflow) uses the same `sampling_biomass` tag with polygons matching the full plot extent — differentiate it via the date tag, not a separate filename suffix.
- `sampling_height` — locations / quadrats where canopy height was measured.
- `sampling_emergence` — emergence-count quadrats.
- `sampling_headcount` — headcount quadrats.
- `sampling_{measurement}` — extensible for other destructive or in-field sampling (manual quadrats, soil cores, damage assessments, etc.).

Other tags

- `gcp` — **permanent** ground control point locations only (fixed, surveyed markers that persist across flights and seasons). Temporary or per-flight GCPs must **not** be stored here — they belong with the flight that used them.

Examples Within `USYD_Narrabri/2025_SIF0zBarley/2025IAWatson_F/Documentation/Plot_Layout/`:

```
# Plot files
2025IAWatson_plots.geojson (main file - used by every sensor)
2025IAWatson_plots_unbuffered_v01.geojson (full plot footprint, no inward buffer)
2025IAWatson_plots_rszone_v01.geojson (RS-safe sub-area, no destructive sampling)
2025IAWatson_plots_HIRES_v01.geojson (sensor variant - only if geometry differs)
2025IAWatson_plots_v01.shp (+ .shx .dbf .prj .cpg - optional companion)
2025IAWatson_plots_v01.json (FIELDimager settings sidecar)

# Sampling files (one per measurement type; date tag identifies the sampling event)
2025IAWatson_sampling_biomass_20251104_v01.geojson (single biomass cut, 2025-11-04)
2025IAWatson_sampling_biomass_20251104and20251125_v01.geojson (biomass cut spread over two discrete days)
2025IAWatson_sampling_biomass_20251201to20251205_v01.geojson (biomass cut over a 5-day window)
2025IAWatson_sampling_emergence_20250710_v01.geojson
2025IAWatson_sampling_headcount_20251018_v01.geojson

# Ground control points
2025IAWatson_gcp_v01.geojson

# Superseded but retained for provenance
2025IAWatson_plots_20250901_deprecated.geojson (previous main layout, replaced 2025-09-01 -
see notes)
```

Note

All `sampling_*` and `plots_*` variant files should use the **same CRS and plot_id scheme** as the main `plots` file so that downstream pipelines can spatially join, subtract, or flag affected plots without additional configuration. The **only** accepted exception is when a sensor cannot output in the standard GDA2020 CRS — in that case the variant file may use the sensor's native CRS, but the CRS must be declared in the file's

provenance_metadata and a reprojection step added to the downstream pipeline.

Joining Trial Information

Trial information arrives in a wide range of formats and structures across nodes, projects, and collaborators (trial designs, agronomy records, breeder spreadsheets, LIMS exports) and **cannot realistically be standardised** into a single APPN schema. Instead of mandating a spreadsheet layout, APPN mandates **one thing only**: the trial spreadsheet must carry a `plot_id` column whose values match the `plot_id` attribute of the plot GeoJSON exactly (same type, same zero-padding, no whitespace). Everything else is up to the trial.

Important

The only hard requirement is the join key. The trial spreadsheet **must** include a `plot_id` column that matches the plot file's `plot_id` one-to-one. `fid` must **not** be used as the join key — it is tool-assigned and changes when the plot file is regenerated.

Suggested columns

The columns below are **examples**, not a required schema. Include the ones the trial actually uses; omit the rest. Add any trial-specific columns you need.

Column	Typical use
<code>plot_id</code>	Required. Join key — must match the plot file.
<code>row, range</code>	Trial-design coordinates (handy for sanity-checking the join).
<code>block / replicate</code>	Replication block from the trial design.
<code>crop</code>	Crop type (e.g. <code>Wheat</code>).
<code>genotype / entry</code>	Variety, line, or accession code (anonymised if proprietary).
<code>treatment</code>	Agronomic / experimental treatment (e.g. <code>N0</code> , <code>Irrigated</code>).
<code>sowing_date</code>	ISO date sown.
<code>seed_rate, row_spacing_m</code>	Agronomy parameters when relevant.
<code>notes</code>	Free-text per-plot notes (damage, missing rows, etc.).

Example template (`{YYYYSiteName}_trial_info.csv`)

```
plot_id,row,range,block,crop,genotype,treatment,sowing_date,notes
1001,1,1,1,Wheat,Scepter,N0,2025-05-12,
1002,1,2,1,Wheat,Mace,N0,2025-05-12,
1003,1,3,1,Wheat,Scepter,N100,2025-05-12,
2001,2,1,2,Wheat,Mace,N100,2025-05-12,missing first row
...
```

CSV is preferred (plain text, diff-friendly, opens everywhere); XLSX is acceptable if the trial team already maintains it.

Storage location

Trial-information files live in a dedicated **Trial_Info/** subfolder alongside **Plot_Layout/** under the site's **Documentation/** directory:

```
{Node}/
{YYYY_ProjectDesc[_I|E][_Researcher][_org]}/
{YYYYSiteName[_F|C]}/Documentation/
Plot_Layout/
Trial_Info/
```

Example:

```
USYD_Narrabri/2025_SIF0zBarley/2025IAWatson_F/Documentation/Trial_Info/
2025IAWatson_trial_info.csv (current trial info)
2025IAWatson_trial_info_20250612_deprecated.csv (superseded version)
README.md (source spreadsheets, contacts, quirks)
```

The same `_deprecated` and `_v{NN}` conventions used for plot files apply here (see File naming convention). Record the current filename and any quirks in the folder's `README.md`, and reference it from the `Plot_Layout/ Folder README` so the two folders stay linked.

Methods

The following methods are supported for generating an APPN-compliant plot shapefile. Choose the method that best matches your imagery and tooling; the resulting shapefile must satisfy the APPN Plot Shapefile Standard above.

- Method 1: FIELDImageR (QGIS) — follow-up meeting with **Bipul and Mickey** is still TBC; outcomes to be folded back into this section.
 - Method 2: DPIRD Field Mapping Tool
 - Method 3: GPT plot creation tool — **to be written by Mickey** (replaces the previous "GRYFN plot tool" placeholder).
-

Method 1: FIELDImageR (QGIS)

FIELDImageR is an R-based plugin run from within QGIS that builds plot polygons from a georeferenced ortho-mosaic.

Software Installation

Install the following software to start the pipeline:


1. R
2. QGIS

Note

The first time you run FIELDImageR-QGIS it may take some time to install all required R packages.


Enable the Processing Toolbox in QGIS Make sure the **Processing Toolbox** panel is visible in QGIS:

1. Open the **View** menu.
2. Select **Panels**.
3. Enable **Processing Toolbox**.
4. Confirm the Processing Toolbox is now showing on the right-hand side.





Install the Processing R Provider plugin Install the Processing R Provider plugin in QGIS:


1. Open the **Plugins** menu.
2. Select **Manage and Install Plugins...**
3. Switch to the **All** tab.
4. Search for *Processing R Provider*.
5. Click **Install Plugin**.
6. Verify that **R** now appears in the Processing Toolbox.



Install FIELDImageR

1. Go to the FIELDImageR-QGIS GitHub repository: <https://github.com/filipematias23/FIELDImageR-QGIS>.
2. Click **Code**.
3. Select **Download ZIP**.
4. Unzip the archive and copy the functions from the **rscripts** folder into your **QGIS R scripts** folder.
5. To locate the QGIS R scripts folder, go to **QGIS → Processing Toolbox → Options** (the wrench icon).
6. Under **Providers**, click **R**.
7. Copy the path shown for **R scripts folder** and open it in your file explorer.
8. Paste the FIELDImageR functions downloaded from GitHub into the **rscripts** folder.







Generating the Plot Shapefile

With FIELDImageR set up, you can now generate plot shapefiles from your aerial imagery.

1. Load an image into QGIS. An RGB orthomosaic from a GRYFN drone is the easiest starting point.




2. Open the **fieldShape** module from the Processing Toolbox.



3. Fill in the module parameters:

- Number of **rows** and **columns**.
- The **corners** of the trial area (most critical for an accurate fit).
- **Plot size**.
- **Buffer** — essential for establishing a common analysis area by mitigating edge effects.

4. Click **Run**.



5. The plot shapefile will be generated.

Note

Achieving a perfect fit usually takes some iteration on the corner coordinates. (*TODO: improve this workflow.*)

Save your settings Save your fieldShape settings before closing the tool — inputs will be wiped if FIELDImageR is closed.

FIELDImageR - FIELDImageR FieldShape

Parameters
Log

num rows
11

num cols
17

input for grid
four_corner_point_coordinates

point shapefile layer [optional]

first point at left superior corner [optional]
769560.208859,6646696.473272 [EPSG:7855]

second point at right superior corner [optional]
769586.821149,6646720.191798 [EPSG:7855]

third point at right inferior corner [optional]
769629.529998,6646670.171029 [EPSG:7855]

fourth point at left inferior corner [optional]
769605.785635,6646648.571151 [EPSG:7855]

mosaic layer [optional]

buffer [optional]
-0.100000

x plot size [optional]
1.150000

y plot size [optional]
3.300000

fieldData [optional]

fieldMap [optional]

PlotID [optional]

output shapefile

Algorithm Settings...
Copy as Python Command
Copy as qgis_process Command
Copy as JSON
Paste Settings

Advanced
Run as Batch Process...
Run
Close

FIELDImageR fieldShape

The user should select the four experimental field corners and the shape file with plots will be automatically loaded using a grid with the number of ranges and rows.

Input parameters

num rows
Number of rows.

num cols
Number of columns.

input for grid
Choose how to inform the field corner (i) uploading four points-shapefile or (ii) clicking it each corner.


point shapefile layer
Four points-shapefile layer the field boundaries (e.g. GPS coordinate file or external layer shp.).

first point left superior corner
Set the 1st point at the left

Use **Copy as JSON** and save the contents as a text file alongside the shapefile in the trial's `Plot_Layout` directory.

Output

The shapefile produced by FIELDimager contains plots identified only by `fid`.



Attach trial metadata as described in [Joining Trial Information](#), then save the final shapefile to the trial's `Plot_Layout` directory per the APPN Plot Shapefile Standard.

Method 2: DPIRD Field Mapping Tool

The DPIRD Field Mapping Tool is a desktop application for digitising and managing agricultural field trial plot boundaries over drone orthomosaic imagery. Built with Streamlit and Python geospatial libraries, it runs locally in your web browser with no cloud dependency.

Developed at the Department of Primary Industries and Regional Development (DPIRD), Western Australia, as part of the Australian Plant Phenomics Network (APPN).

Features

- **Generate Grid** — Create regular plot grids over drone orthomosaics by drawing a trial boundary and specifying banks, rows, buffer, and plot dimensions.
- **Edit Grid** — Interactive browser-based polygon editor with drag, vertex editing, multi-select, copy/paste, measurements, undo, and keyboard shortcuts.
- **Convert File** — Convert between Shapefile, GeoJSON, GeoPackage, and KML formats with optional CRS reprojection (GDA2020, GDA94, WGS 84, or custom EPSG).
- **Cropping Tool** — Crop rasters (orthophotos, DSMs, GeoTIFFs) to individual plot polygon boundaries, producing one file per plot.

All data is processed locally. No internet connection is required after installation.

Detailed installation instruction and documentation is provided in the DPIRD Field Mapping Tool Documentation within the GitHub repository. Basic guidelines are provided below.

Software Installation

Go to the GitHub repository [appndpird/DPIRDFieldMappingTool](#) and download the repository (click **Code** → **Download ZIP**, or `git clone`). The repository contains two platform-specific distributions — choose the one that matches your operating system.

Requirements

	Windows	Linux / macOS
OS	Windows 10+ (64-bit)	Ubuntu 20.04+, Fedora, macOS 11+
Python	Bundled via Miniconda	User-installed Anaconda/Miniconda
Disk space	~2 GB	~2 GB
Internet	First-time setup only	First-time setup only

Windows

1. Extract `DPIRD_Field_Mapping_Tool_windows_v1.6.0`.
2. Place `Miniconda3-latest-Windows-x86_64.exe` in the folder.
3. Double-click `Install_DPIRD_Tool.bat` and press Y.
4. Double-click `Run_DPIRD_Tool.bat` to launch.

Linux / macOS

1. Extract `DPIRD_Field_Mapping_Tool_linux_v1.6.0`.
2. Ensure Anaconda or Miniconda is installed.
3. Run:

```
chmod +x install_dpird_tool.sh run_dpird_tool.sh
./install_dpird_tool.sh
./run_dpird_tool.sh
```

The tool opens in your browser at <http://localhost:8501>.

Generating the Plot Shapefile

1. Open the tool and navigate to the **Generate Grid** tab.
2. Enter your project folder path (the folder containing the orthomosaic `.tif` file). Click **Browse** or paste the path directly.
3. Select the orthomosaic file from the dropdown. Optionally select a CSV file to attach additional plot metadata.
4. Set the grid parameters:

Parameter	Description
Banks	Number of banks (columns) in the X direction.
Rows	Number of rows in the Y direction within each bank.
Buffer (m)	Gap between adjacent plots in metres.
Plot Size (W,H)	Width and height of each plot in metres, comma-separated (e.g. 4,1).

5. Draw a boundary polygon on the map by clicking the four corners of the trial area in this order:

Top-left (B1R1) → Top-right (BXR1) → Bottom-right (BXYR) → Bottom-left (B1RY)

The first point defines the origin of the grid (plot B1R1). The orientation of the boundary polygon determines the rotation of the generated grid.

6. Click **Generate Grid**. Review the generated grid on the map and in the data table.
7. Fine-tune if needed — changing any grid parameter after generation automatically regenerates the grid using the same boundary.
8. Click **Save Initial Grid** to save as a shapefile.

Plot ID Convention Plots are assigned IDs automatically:

Field	Formula	Examples
Plot_ID	$\text{Bank} \times 1000 + \text{Row}$	B1R1 = 1001, B2R3 = 2003
B/R	Bank-Row label	B1R1, B2R3, B12R6
Bank	Bank number	1, 2, 3, ...
Row	Row number	1, 2, 3, ...

Editing the Plot Shapefile

After generating (or loading an existing grid via the **Edit Grid** tab), click **Edit Grid** to open the interactive browser-based polygon editor in a new tab. The editor provides:

Tool	Shortcut	Description
Navigate	Esc	Pan and zoom. Click a polygon to select it.
Drag Plots	D	Drag polygons to reposition. Ctrl/Cmd+Click to multi-select.
Edit Vertices	V	Drag individual corner vertices to reshape polygons.
Delete	X	Click a polygon to remove it.
Draw New	N	Click to place vertices; double-click to close.
Measurements	M	Toggle edge length labels (metres) on all polygons.
Copy / Paste	Ctrl+C / Ctrl+V	Duplicate selected polygons.
Undo	Ctrl+Z	Revert the last action (up to 50 steps).
Select All	Ctrl+A	Select all polygons.

Note

On macOS, use **Cmd** instead of **Ctrl** for all keyboard shortcuts.

Click **Save Shapefile** in the editor to write the edited grid to disk, or **Export GeoJSON** to download a GeoJSON file.

Converting Vector Data File Formats

Use the **Convert File** tab to convert the output shapefile to GeoJSON or reproject to a different CRS:

1. Load the shapefile via **Browse Input File**.
2. Set the output format to **GeoJSON**.
3. Select the target CRS (typically the CRS of the source orthomosaic, e.g. GDA2020 / MGA Zone 50).
4. Click **Convert & Save**.

Cropping Rasters to Plots

Use the **Cropping Tool** tab to crop the orthomosaic (or DSM) to individual plot boundaries:

1. Load the plot shapefile and the raster file.
2. Choose a save folder and base filename.
3. Click **Crop and Save**.

For a grid with multiple polygons, one raster is saved per plot (e.g. `cropped_1001.tif`, `cropped_2003.tif`). The tool automatically reprojects the vector to match the raster's CRS if they differ.

Output

The shapefile produced by the DPIRD Field Mapping Tool contains plots identified by `Plot_ID` ($\text{Bank} \times 1000 + \text{Row}$), `B/R`, `Bank`, and `Row`. To produce an APPN-compliant plot shapefile:

1. **Rename** `Plot_ID` to `plot_id` (or add a `plot_id` column mapped from `Plot_ID`) to match the Required attributes specification.
2. **Add** an `fid` column if not already present (sequential polygon identifier).
3. **Convert** to GeoJSON using the Convert File tab if the primary deliverable should be `.geojson`.
4. Attach trial metadata as described in Joining Trial Information, then save the final file to the trial's `Plot_Layout` directory per the APPN Plot Shapefile Standard.

Further Documentation

Detailed installation instruction and documentation: DPIRD Field Mapping Tool Documentation.

Method 3: GPT plot creation tool

Important

TODO — Mickey to write. This section will document the GRYFN Processing Tool (GPT) plot-creation workflow as the third supported APPN method. Replaces the previous placeholder "*GRYFN plot tool — TODO*".

Note

Additional plot delineation methods will be documented here as they are adopted by APPN.
