



VLSI DESIGN FLOW: RTL TO GDS

Lecture 14
Logic Optimization: Part I




Sneh Saurabh
Electronics and Communications
Engineering
IIT Delhi

Lecture Plan



- Two-level Combinational Logic Optimization

Simplicity and beauty ...



‘We ascribe beauty to that which is simple; which has no superfluous parts; which exactly answers its end...’

—R. W. Emerson, *The Conduct of Life*, on “Beauty,” 1871



Source:

https://commons.wikimedia.org/wiki/File:Ralph_Waldo_Emerson_by_Josiah_Johnson_Hawes_1857.jpg Josiah Johnson Hawes, Public domain, via Wikimedia Commons



Logic Optimization



Two-level

Boolean Function: Definitions

Boolean variable: variable that can take one of the two values 0 or 1

Boolean function: function that takes Boolean variables as arguments and evaluates to 0 or 1.

Denoted as: $y = f(x_1, x_2, x_3, \dots, x_N)$ where the variables $\{x_1, x_2, x_3, \dots, x_N\}$ are Boolean variables.

Literal: a Boolean variable or its complement.

Example: x_1, x_2, x_1', x_3' etc.

Cube: a product of literals.

Example: $x_1x_2x_3, x_1x_2', x_3'$ etc.

Consider a Boolean function of N variables:

Minterm: the cube of N literals in which each variable or its complement appears exactly once.

Maxterm: the sum of N literals in which each variable or its complement appears exactly once.

Example: Consider a function of three variables x_1, x_2, x_3 :

Minterms are: $x_1x_2x_3, x_1'x_2x_3, x_1'x_2'x_3$ etc.

Maxterms are $(x_1 + x_2 + x_3), (x_1 + x_2' + x_3)$, etc.

Boolean Function Representations

Truth Table: The row of a truth table shows the value (0 or 1) assigned to each input variable x_1, x_2, \dots, x_N and its corresponding output value.

- Will contain 2^N rows in the table.

Minterm representation of a function:

- Each row of a truth table corresponds to a minterm.
 - The minterm evaluates to 1 only for the assignment of variables corresponding to that row in the truth table.
 - For all other assignments of variables, the minterm evaluates to 0
- **Sum of minterms:** From the truth table, we take the sum of only those minterms for which the function evaluates to 1.

$$y = x_1x_2 + x_2x_3 + x_3x_1$$

x_1	x_2	x_3	y	Minterm
0	0	0	0	$x_1'x_2'x_3'$
0	0	1	0	$x_1'x_2'x_3$
0	1	0	0	$x_1'x_2x_3'$
0	1	1	1	$x_1'x_2x_3$
1	0	0	0	$x_1x_2'x_3'$
1	0	1	1	$x_1x_2'x_3$
1	1	0	1	$x_1x_2x_3'$
0	1	1	1	$x_1x_2x_3$


$$y = x_1'x_2x_3 + x_1x_2'x_3 + x_1x_2x_3' + x_1x_2x_3$$

Boolean Space and Hypercube: Definition


- Boolean functions of N variables [$y = f(x_1, x_2, x_3, \dots, x_N)$] spans an N –dimensional Boolean space
- An N –dimensional Boolean space can be represented and visualized using an N –dimensional Boolean hypercube

Boolean Hypercube:

- Associate each variable with one dimension of the hypercube.
- The corners of the hypercube represent binary-valued N -dimensional vectors
 - i -th entry in the vector corresponds to the value of variable x_i .
- A Boolean hypercube has 2^N corners, representing 2^N input combinations (or the associated minterms)



S. Saurabh, "Introduction to VLSI Design Flow",
Cambridge University Press, 2023.





S. Saurabh, "Introduction to VLSI Design Flow",
Cambridge University Press, 2023.

Boolean Function Representation: Hypercube

- Mark the corners in the Boolean hypercube with the value of the function for the associated input combination.

$$y = x_1'x_2'x_3' + x_1'x_2x_3 + x_1x_2x_3$$

S. Saurabh, "Introduction to VLSI Design Flow".
Cambridge University Press, 2023.



Don't Care (DC) Conditions

Don't Care (DC) conditions:

- For some input combinations, the function $y = f(x_1, x_2, x_3, \dots, x_N)$ may not be specified.
 - These input combinations are known as don't care
 - DC conditions are denoted by X
-
- DC conditions are related to the input combinations that can never occur
 - Example: If a function receives binary coded decimal (BCD) digits it cannot receive input combinations {1010, 1011, ..., 1111}
 - Can also be those input combinations for which the output is not observed
 - Example: A function producing an output for a block that is in a sleep state

Incompletely-specified Boolean Function


Incompletely-specified Boolean function:

- A Boolean function with DC conditions
- Can represent using three sets:
 - **ON-set:** input combinations for which the output is 1
 - **OFF-set:** input combinations for which the output is 0
 - **DC-set:** input combinations for which the output is X

Example:

- A function of three variables x_1, x_2 , and x_3 .
ON-set={010, 011},
OFF-set={000, 001, 100, 101}, and
DC-set={110, 111}.


S. Saurabh, "Introduction to VLSI Design Flow".
Cambridge University Press, 2023.



Implicant of a Boolean Function

Implicant of a Boolean function:

- A cube whose corners are all in the ON-set or DC-set of that function



Implicants:

- $x_1'x_2x_3'$
- x_1x_2
- x_2x_3'
- x_2


Not an implicant:

- $x_1'x_3'$
- x_1'

Cover of a Boolean Function


Cover of a Boolean function:

- Set of implicants that includes all its minterms
- The number of implicants in a cover is known as the **size of the cover**.
- The cover with the minimum size is known as the **minimum cover**




S. Saurabh, "Introduction to VLSI Design Flow".
Cambridge University Press, 2023.

$$y = x_1'x_2x_3' + x_1'x_2x_3$$




$$y = x_1'x_2x_3' + x_1'x_2x_3 + x_1x_2x_3$$



S. Saurabh, "Introduction to VLSI Design Flow".
Cambridge University Press, 2023.

$$y = x_1'x_2$$




$$y = x_2$$

Prime Implicant

Prime Implicant of a function:

- An implicant of a function that is not covered by any other implicant of that function
- Also called prime (in short)

S. Saurabh, "Introduction to VLSI Design Flow".
Cambridge University Press, 2023.



Prime Implicants:


- x_2 : Yes
- $x_1'x_2x_3'$: No
- x_1x_2 : No

Essential Prime Implicant and Prime Cover

Essential prime implicant:


- If there is at least one minterm that is covered by only that prime implicant.

S. Saurabh, "Introduction to VLSI Design Flow".
Cambridge University Press, 2023.



- Both x_1' and $x_2'x_3$ are essential primes

S. Saurabh, "Introduction to VLSI Design Flow".
Cambridge University Press, 2023.



- Prime implicants: $x_1'x_2'$, $x_2'x_3$, x_1x_3 , and x_1x_2
- Essential primes: $x_1'x_2'$ and x_1x_2
- Non-essential primes: $x_2'x_3$ and x_1x_3

Exact Two-level Logic Minimization

- **Aim:** To find the minimum cover.
 - **Reason:** correlates with the circuit's reduced hardware or reduced area.
-
- **For simple problem:** conventional techniques such as Boolean algebra-based manipulations and Karnaugh maps.
 - **For problems with more than 20 variables:** conventional techniques becomes too complicated.
-
- In finding the minimum cover, we can reduce the search space by employing Quine's theorem

NPTEL

Quine's Theorem

Prime cover: a cover that consists only of prime implicants

Quine's Theorem:

- There exists a minimum cover consisting only of prime implicants (prime cover)

Proof:

- Consider a minimum cover that is not a prime cover.
 - It implies that it contains some implicants that are not prime implicants.
 - Can replace each non-prime implicant with a prime implicant that contains it.
 - A new cover is obtained that consists of primes only and is of the same size.
 - Hence, there exists a minimum cover that is a prime cover.

Application:

- We can focus on only prime cover for finding minimum cover.


Prime Implicant Table

How to find minimum cover among prime covers?


- By finding the set of **prime implicants** and building a **prime implicant table**.

How to build prime implicant table?

- Arrange the prime implicants in separate columns and the minterms in individual rows of the prime implicant table.
- Fill entries in the table: If a given prime (column) covers a given minterm (row), then the corresponding entry is made 1, else it is made 0.



Prime Implicant Table: Illustration



	Prime Implicants			
Minterms	$x_1'x_2'$	$x_2'x_3$	x_1x_3	x_1x_2
$x_1'x_2'x_3'(000)$	1	0	0	0
$x_1'x_2'x_3(001)$	1	1	0	0
$x_1x_2'x_3(101)$	0	1	1	0
$x_1x_2x_3'(110)$	0	0	0	1
$x_1x_2x_3(111)$	0	0	1	1

How to find minimum cover using prime implicant table?

- Find the minimum set of columns that covers all the rows in the prime implicant table.
- Solve set covering problem (can grow exponentially with the number of variables)

Simplification:

- Identify essential primes: $(x_1'x_2'$ and $x_1x_2)$
- Work on remaining minterms $[x_1x_2'x_3(101)]$: cover either using $x_2'x_3$ or x_1x_3
- Efficient reduction and covering algorithms

Heuristic Minimizer: Basics

For large problems we prefer heuristic minimizer over exact minimization.

- Heuristic minimizers are faster for large problem sizes.
- We often do not need the exact minimum cover.
 - Any solution that can be found quickly and is near-optimal is acceptable.

Minimal Cover:

- A minimal cover satisfies certain local minimum cover property rather than the global minimum property.
 - For example, a cover in which no implicant is contained in any other implicant of the cover.
 - Minimal with respect to single-implicant containment.
- The size of a minimal cover can be more than the size of the minimum cover.

Heuristic Minimizer: Approach


Approach:

- Starts with an initial cover and iteratively improves the solution by applying **some operators** on it.
- The iteration terminates when the algorithm can no longer improve the solution.

Operators:

- **Expand:** expands a non-prime implicant to make it prime (removes implicants covered by the expanded implicant)
- **Reduce:** replaces an implicant with a reduced implicant (covering fewer minterms) such that the function is still covered.
- **Reshape:** operates on a pair of implicants (expands one implicant and reduces others such that the function is still covered).
- **Irredundant:** makes a cover irredundant
 - Cover in which, if we remove any implicant, then it will be no more a cover.

Heuristic Minimizer: Illustration



- Can carry irredundant operation at the end of iterations
- Not guaranteed to be minimum
- ESPRESSO two-level minimizer: practically very efficient

References

- G. D. Micheli. “Synthesis and Optimization of Digital Circuits”. *McGraw-Hill Higher Education*, 1994.
- S. Saurabh, “Introduction to VLSI Design Flow”. Cambridge: *Cambridge University Press*, 2023.

