

CSGE602055 Operating Systems

CSF2600505 Sistem Operasi

Week 09: Storage, Firmware, Bootloader, & Systemd

Rahmat M. Samik-Ibrahim (ed.)

University of Indonesia

<https://os.vlsm.org/>

Always check for the latest revision!

REV207 30-Aug-2019

Operating Systems 2019-2

A (Rm 3114) [Tu/Th 08-10] — I (Rm A714) [Tu 13-15/Th 14-16]

| Week | Schedule | Topic | OSC10 |
|----------------|-------------------------------------|--|--|
| Week 00 | 03 Sep - 09 Sep 2019 | Overview 1, Virtualization & Scripting | Ch. 1, 2, 18. |
| Week 01 | 10 Sep - 16 Sep 2019 | Overview 2, Virtualization & Scripting | Ch. 1, 2, 18. |
| Week 02 | 17 Sep - 23 Sep 2019 | Security, Protection, Privacy, & C-language | Ch. 16, 17 |
| Week 03 | 24 Sep - 30 Sep 2019 | File System & FUSE | Ch. 13, 14, 15 |
| Week 04 | 01 Oct - 07 Oct 2019 | Addressing, Shared Lib, & Pointer | Ch. 9 |
| Week 05 | 08 Oct - 14 Oct 2019 | Virtual Memory | Ch. 10 |
| Reserved | 15 Oct - 18 Oct 2019 | Q & E | |
| MidTerm | 19 Oct - 25 Oct 2019 | TBA — MidTerm (UTS) | |
| Week 06 | 29 Oct - 04 Nov 2019 | Concurrency: Processes & Threads | Ch. 3, 4 |
| Week 07 | 05 Nov - 11 Nov 2019 | Synchronization & Deadlock | Ch. 6, 7, 8 |
| Week 08 | 12 Nov - 18 Nov 2019 | Scheduling + W06/W07 | Ch. 5 |
| Week 09 | 19 Nov - 25 Nov 2019 | Storage, Firmware, Bootldr, & Systemd | Ch. 11 |
| Week 10 | 26 Nov - 02 Dec 2019 | I/O & Programming | Ch. 12 |
| Reserved | 03 Dec - 13 Dec 2019 | Q & E | |
| Final Extra | 14 Dec - 21 Dec 2019 09 Jan 2020 | TBA — Final (UAS) Extra assignment confirmation | This schedule is subject to change. |

STARTING POINT — <https://os.vlsm.org/>

- ❑ **Text Book** — Any recent/decent OS book. Eg. (**OSC10**) Silberschatz et. al.: **Operating System Concepts**, 10th Edition, 2018. See also <http://codex.cs.yale.edu/avi/os-book/OS10/>.
- ❑ **Weekly**
 - ❑ Encode your **QRC** with size about 5cm x 5cm (ca. 400x400 pixels):
"OS192 CLASS ID SSO-ACCOUNT Your-Full-Name"
Write your Memo (with QRC) **every week**.
See also Assignment#0: Generate your QR Code.
 - ❑ Login to badak.cs.ui.ac.id via kawung.cs.ui.ac.id for at least **10 minutes** every week. Copy all weekly demo folders into your own badak home directory.
Eg.: `cp -r /extra/Demos/ .`
- ❑ **Resources**
 - ❑ **All In One** — BADAK.cs.ui.ac.id:///extra/ (**FASILKOM only!**).
 - ❑ **Download Slides and Demos from GitHub.com**
<https://github.com/UI-FASILKOM-OS/SistemOperasi/>
 - ❑ **Problems** — <https://rms46.vlsm.org/2/>:
195.pdf (W00), 196.pdf (W01), 197.pdf (W02), 198.pdf (W03),
199.pdf (W04), 200.pdf (W05), 201.pdf (W06), 202.pdf (W07),
203.pdf (W08), 204.pdf (W09), 205.pdf (W10).

Agenda

- 1 Start
- 2 Schedule
- 3 Agenda
- 4 Week 09
- 5 Storage, Firmware, Bootloader, & Systemd
- 6 Storage Management
- 7 RAID
- 8 Legacy BIOS
- 9 UEFI
- 10 Operating System (Boot) Loader
- 11 GRUB Map
- 12 init (SYSV legacy)
- 13 UpStart - Ubuntu
- 14 The All New "systemd"
- 15 systemctl
- 16 The End

Week 09 Storage, Firmware, Bootloader, & Systemd: Topics¹

- Storage
- Storage Arrays
- BIOS
- Loader
- Systemd

¹Source: ACM IEEE CS Curricula 2013

Week 09 Storage, Firmware, Bootloader, & Systemd: Learning Outcomes¹

- Storage [Usage]
- Storage Arrays [Usage]
- BIOS [Usage]
- Loader [Usage]
- Systemd [Usage]

¹Source: ACM IEEE CS Curricula 2013

Storage, Firmware, Bootloader, & Systemd

- Reference: (OSC10-ch11)
- Storage Capacity (2019)¹
 - Legacy 3.5" Floppy Disk (1.4MB) – obsolete?
 - SuperDisk (up to 240 MB) — never took off.
 - 4.7" Compact Disc (700MB) – obsolete?
 - 4.7" Digital Versatile Disc (up to 9GB) – ?
 - 4.7" Blu Ray (up to 128 GB) ⇒ DVD++.
 - Tape Cartridge (up to 15TB)
 - Robotic System (up to 250 PB per unit)
 - NASA, Google, Microsoft are still using this!
 - Cheap but slow.
 - Hard Disk Drives (up to 16 TB).
 - From Perpendicular Magnetic Recording to Shingled Magnetic Recording technology (+25% – writing problems).
 - Mechanical Disk Arm Scheduling (Until When?).
 - Solid-State Disks (up to 16 TB).
 - SSD Price > HDD Price.
 - Write Speed >> Read Speed.
 - (What is a) Flash Disk?


¹Subject to change

Storage Failure Rates

- MTDDL: Mean Time To Data Loss
- MTTF: Mean Time To Failure
- BackBlaze (Cloud Backup Services)

Drives Have 3 Distinct Failure Rates General Predicted Failure Rates

Hard Drive Survival Rates - Chart 1



<https://www.extremetech.com/computing/170748-how-long-do-hard-drives-actually-live-for>



Figure: BackBlaze — Failure Rates of 25000 DISKS

Storage Management

- Attached-Storage.
 - Host-Attached Storage: via I/O.
 - Network-Attached Storage (NAS): via distributed FileSystem.
 - Storage Area Network (SAN): dedicated Network.
- Formatting
 - Low Level (Physical)
 - High Level (FileSystem)
- Boot Block
- Disk Partition
 - "MBR"-scheme
 - upto 4 primary partition
 - upto 2 TB disk
 - "GPT"-scheme
 - "unlimited" partition
 - "unlimited" disk
 - redundancy
- Swap Space Management: On Partition or FileSystem?

RAID: Redundant Array of In* Disks

- RAID 0, 1, 5, 6, 10, 100
- Note (<http://www.commodore.ca/windows/raid5/raid5.htm>):
 - RAID was created to enhance data performance, reliability and availability.
 - Striping, parity checking and mirroring are three primary functions of RAID systems.
 - RAID performs its functions transparent to the operating system.
 - Systems are typically defined by ranks consisting of five disks each connected to one or two Disk Array Controllers.
 - Different RAID levels provide varying degrees of speed and data protection.
- Problems with RAID
- Stable-Storage Implementation

BIOS, Boot, & Systemd

- Firmware
 - BIOS: Basic Input Output System.
 - UEFI: Unified Extensible Firmware Interface.
 - ACPI: Advanced Configuration and Power Interface.
- Operating System (Boot) Loader
 - BOOTMGT: Windows Bootmanager / Bootloader.
 - LILO: Linux Loader.
 - GRUB: GRand Unified Bootloader.
- Operating System Initialization
 - Init (legacy)
 - UpStart
 - Systemd

- Check Settings.
- Initialize CPU & RAM.
- POST: Power-On Self-Test.
- Initialize ports, LANS, etc.
- Load a Boot Loader.
- Handover to the Boot Loader.
- Provides "Native" (obsolete) Drivers only (not loadable).
- Provides "INT" services .
- Limitation.
 - Technology of 1970s.
 - 16 bits software.
 - 20 bits address space (1 MB).
 - 31 bits disk space (2 TB).



Figure: BIOS

- A Firmware Specification, not an Implementation!
- No (INT) service after boot.
- HII: Human Interface Infrastructure.
- Protected Mode.
- Flexible.
 - Technology of 2000s.
 - written in C.
 - (third party) loadable drivers and tools.
 - Emulate Legacy BIOS transition (MBR block, INT service).
 - UEFI Shell: environment shell for diagnostic (no need for DOS).
- Problems
 - Who controls the Hardware?
 - Is "Secure Boot" a good thing?
 - How about a **NASTY/LOCKING/TROJAN** UEFI implementation?
 - Different **DRIVERS**.



Figure: UEFI

Platform Initialization (PI) Boot Phases



Figure: UEFI Boot Process¹.


Operating System (Boot) Loader

- General
 - How/Where to start the operating system?
 - What to do?
 - How many ways to boot?
 - How many types of OS?
- Disk Partition
 - MBR: Master Boot Record (1983).
 - GPT: GUID (Globally Unique Identifiers) Partition Table (2010s).
- GRUB: GRand Unified Boot system
 - Stage 1: a small boot.img inside the MBR.
 - Stage 1.5 (core.img): FileSystem drivers after MBR.
 - Stage 2: Kernel Selection: Windows, Linux, BSD, etc.
- GRUB2
 - More flexible than GRUB legacy.
 - More automated than GRUB legacy.
 - Accept MBR and GPT.
 - Stage 1.5 (core.img): generated from diskboot.img.
 - No 1024 cylinder restriction.

GNU GRUB 2

Locations of *boot.img*, *core.img* and the */boot/grub/* directory

Example 1: an MBR-partitioned harddisc with sector size of 512 or 4096Bytes



Example 2: a GPT-partitioned harddisc with sector size of 512 or 4096Bytes



Figure: GRUB¹.

¹Source Shmuel Csaba Otto Traian 2013

init (SYSV legacy)

- File: `/etc/inittab`.
- Folders: `/etc/rcX.d` — `X` = runlevel.
 - Seven (7) different runlevels:
 - 0 (shutdown).
 - 1 (single-user/admin).
 - 2 (multi-user non net).
 - 3 (standard).
 - 4 (N/A).
 - 5 (3+GUI).
 - 6 (reboot).
 - `SXX-YYY`: Start
 - `KXX-YYY`: Kill.
- One script at a time in order.
- dependency is set manually.

- Developer: Ubuntu.
- Folder: `/etc/init/`.
- Control: `initctl`.
 - `initctl list` – listing all processes managed by upstart.
- better support for hotplug devices.
- cleaner service management.
- faster service management.
- asynchronous.

The All New "systemd"

- Replaces (SYSV) init and UpStart.
 - better concurrency handling: Faster!
 - better dependencies handling: No more "S(tarts)" and "K(ills)".
 - better crash handling: automatic restart option.
 - better security: group protection from anyone including superusers.
 - simpler config files: reliable and clean scripts.
 - hotplug: dynamic start/stop.
 - supports legacy systems (init).
 - overhead reducing.
 - unified management way for all distros.
 - bloated: doing more with more resources.
 - linux specific: NOT portable.

systemctl

```
for II in \
    'systemctl list-unit-files | head -8; echo "(...)";
      systemctl list-unit-files| tail -8' \
    'systemd-analyze blame | wc -l; echo "===";
      systemd-analyze blame | head -15' \
    'systemctl --full | wc -l; echo "===";
      systemctl --full | head -10' \
    'systemctl list-units | wc -l; echo "===";
      systemctl list-units | head -10' \
    'systemctl list-units |grep .service|wc -l;echo "===";
      systemctl list-units|grep .service|head -10' \
    'systemctl list-units | grep ssh.service' \
    'systemctl status ssh.service' \
    'systemctl is-enabled ssh' \
    'journalctl' \
    'journalctl -b' \
do
...
```

The End

- ☐ This is the end of the presentation.
- ☒ This is the end of the presentation.
 - This is the end of the presentation.