

Aplic---1.5V Battery Product Model Table

Serialnumber	model	Product images	Battery specifications	Rated voltage (A)	Capacity (mAh)	Voltage (V)	1.5V actual output capacity (mAh)	Tag capacity (mwh)	Number of cycles	Discharge cut-off voltage (V)	Continuous discharge current (A)	Maximum discharge current (A)	Charger charging requirements	Type-C port charging requirements	Battery full charge time (H)	Cut-off voltage protection value (V)	Cut-off current protection value (A)	Short-circuit protection	Charging indicator light	Product weight(g)
1	TCAA-1.5V-550-H		AA Type-C charging port	1.5	550mAh	3.7V	1200mAh	2000Mwh	1000	1.0V	0.5A	3.5A	4.5v/400mA	400mA	1.5H	2.7V±0.1V	3.8A±0.5A	"	Charging green light flashes, fully charged green light is always on	/
2	TCAA-1.5V-750-H		AA Type-C charging port	1.5	750mAh	3.7V	1800mAh	2800mWh	1000	1.0V	0.5A	3.8A	4.5v/400mA	400mA	1.8H	2.7V±0.1V	3.8A±0.5A	"		18.2
3	AA-1.5V-750-H	/	AA without charging port	1.5	750mAh	3.7V	1800mAh	2800mWh	1000	1.0V	0.5A	3.8A	4.5v/400mA	/	1.8H	2.7V±0.1V	3.8A±0.5A	"	There is no charging indicator light when charging, so you need to bring your own charger	18.2
4	TCAA-1.5V-920-H		AA Type-C charging port	1.5	920mAh	3.7V	2200mAh	3400mWh	1000	1.0V	0.5A	3.8A	4.5v/400mA	400mA	2.5H	2.7V±0.1V	3.8A±0.5A	"	Charging green light flashes, fully charged green light is always on	18.5
5	AA-1.5V-920-H	/	AA without charging port	1.5	920mAh	3.7V	2200mAh	3400mWh	1000	1.0V	0.5A	3.8A	4.5v/400mA	/	2.5H	2.7V±0.1V	3.8A±0.5A	"	There is no charging indicator light when charging, so you need to bring your own charger	18.5
6	TCAA-1.5V-1100-H		AA Type-C charging port	1.5	1100mAh	3.7V	2400mAh	4070mwh	1000	1.0V	0.5A	3.8A	4.5v/400mA	400mA	3H	2.7V±0.1V	3.8A±0.5A	"	Charging green light flashes, fully charged green light is always on	19
7	AA-1.5V-1100-H	/	AA without charging port	1.5	1100mAh	3.7V	2400mAh	4070mwh	1000	1.0V	0.5A	3.8A	4.5v/400mA	/	3H	2.7V±0.1V	3.8A±0.5A	"	There is no charging indicator light when charging, so you need to bring your own charger	19
8	TCAAA-1.5V-250-H		AAA Type-C charging port	1.5	250mAh	3.7V	590mAh	880mWh	1000	1.0V	0.2A	1A	4.5v/180mA	180mA	1.5H	2.7V±0.1V	1.5A±0.5A	"	Charging green light flashes, fully charged green light is always on	7.6
9	AAA-1.5V-250-H	/	AAA without charging port	1.5	250mAh	3.7V	700mAh	1100mWh	1000	1.0V	0.2A	1A	4.5v/180mA	/	1.5H	2.7V±0.1V	1.5A±0.5A	"	There is no charging indicator light when charging, so you need to bring your own charger	8

[VERIFIED LAB DATA]

Chief Hardware Engineer
Aplic Battery Testing Facility