

Cylindrical battery cell products

1865021700- No Type Rated Capacity (mAh) Min. Capacity (mAh) Standard Current (mA) Max.Current (mA) D

1	18650-20HL	2000 @0.2C	1950 @0.2C	1000	2000	4000	30000	18.35±0.15	65.05±0.15	"d 18	"d 46.5	+4A/30A,4.2-2.5V 70%@200(cut of 75!)
2	18650-25M	2500 @0.2C	2450 @0.2C	1250	2500	4000	30000	18.35±0.15	65.05±0.15	"d 18	"d 46.5	+4A/30A,4.2-2.5V 60%@300(cut of 75!)
3	18650-30M	3000 @0.2C	2900 @0.2C	1500	3000	6000	30000	18.35±0.15	65.05±0.15	"d 20	"d 50	+4.5A/30A,4.2-2.5V 60%@300(cut of 75!)
4	18650-2500mAh	2500 @0.2C	2450 @0.2C	1250	2500	2500	7500	18.35±0.15	65.05±0.15	"d 25	"d 48	+0.5C/1C,4.2-2.75V 80%@600
5	18650-2600mAh	2600 @0.2C	2500 @0.2C	1300	2600	2600	7800	18.35±0.15	65.05±0.15	"d 25	"d 48	+0.5C/1C,4.2-2.75V 80%@800
6	18650-2900mAh	2900 @0.2C	2800 @0.2C	1450	2900	2900	8700	18.35±0.15	65.05±0.15	"d 25	"d 47	+0.5C/1C,4.2-2.75V 80%@800
7	18650-3300mAh	3300 @0.2C	3200 @0.2C	1650	3300	3300	9900	18.35±0.15	65.05±0.15	"d 25	"d 48	+0.5C/1C,4.2-2.75V 70%@800
8	18650-3500mAh	3500 @0.2C	3350 @0.2C	1750	3500	3500	7000	18.35±0.15	65.05±0.15	"d 25	"d 48	+0.5C/1C,4.2-2.75V 70%@600
9	18650-3800mAh	3800 @0.2C	3650 @0.2C	1900	3800	3800	7600	18.35±0.15	65.05±0.15	"d 25	"d 49	+0.5C/1C,4.2-2.75V 70%@600
10	18650-4000mAh	4000 @0.2C	3850 @0.2C	2000	4000	4000	8000	18.35±0.15	65.05±0.15	"d 25	"d 50	+0.5C/1C,4.2-2.75V 70%@500
1	21700-4000mAh	4000 @0.2C	3900 @0.2C	2000	4000	4000	12000	21.65±0.2	70.95±0.2	"d 25	"d 71	+0.5C/1C,4.2-2.75V 90%@500 or 80%@1000
2	21700-4500mAh	4500 @0.2C	4400 @0.2C	2250	4500	4500	13500	21.65±0.2	70.95±0.2	"d 25	"d 71	+0.5C/1C,4.2-2.75V 90%@500 or 80%@1000
3	21700-5000mAh	5000 @0.2C	4850 @0.2C	2500	5000	5000	10000	21.65±0.2	70.95±0.2	"d 25	"d 73	+0.5C/1C,4.2-2.75V 70%@800
4	21700-5500mAh	5500 @0.2C	5350 @0.2C	2750	5500	3850	11000	21.65±0.2	70.95±0.2	"d 25	"d 73	+0.5C/1C,4.2-2.75V 70%@600
5	21700-6000mAh	6000 @0.2C	5850 @0.2C	3000	6000	4200	12000	21.65±0.2	70.95±0.2	"d 25	"d 75	+0.5C/1C,4.2-2.75V 70%@500

[VERIFIED LAB DATA]

Chief Hardware Engineer
Aplic Battery Testing Facility