

SMART LITHIUMPOLYMER BATTERY SERIES

Model	Nominal Voltage(V)	Nominal Capacity(mAh)	Continuous Discharge Rate(C)	Instantaneous Discharge Rate(C)	Standard Charging Rate(C)	Maximum Charging Rate(C)	Dimension(mm)	Weight Approx(g)
W<S÷	h yðu5S<	h yð[⁺ í	c ~íe>u5u5mA	w~*ðe>u5u5mA	h Q/ÆQEu5u5mA	g Y'QEu5u5mA	\: [ø	íí
T11423S	11.4V	2350mAh	10C	20C	0.5C	3C	85*60*30	200
T22810S	22.8V	10000mAh	15C	30C	0.5C	3C	185*74*46	1200
T22812S	22.8V	12000mAh	15C	30C	0.5C	3C	185*74*52	1400
T22816S	22.8V	16000mAh	15C	30C	0.5C	3C	185*74*64	1800
T22822S	22.8V	22000mAh	15C	30C	0.5C	3C	205*102*58	2400
T45616S	45.6V	16000mAh	15C	30C	0.5C	3C	185*74*124	3800
T45622S	45.6V	22000mAh	15C	30C	0.5C	3C	205*102*113	5000
FPV LITHIUM POLYMERBATTERY								
Model	Nominal Voltage(V)	Nominal Capacity(mAh)	Continuous Discharge Rate(C)	Pluse Discharge Rate(C)	Dimension (mm) \: [ø			Weight Approx(g)
W<S÷	h yðu5S<	h yð[⁺ í	c ~íP s‡í	g Y'P s‡	Thickness SŠ^í	Width [½^í	Height ŠØ^í	íí
TA001	7.4	1000	45	90	13	35.5	72	72
TA002	11.1	1000	45	90	19	35.5	72	98
TA007	11.1	1200	75	150	19	31	86	125
TA003	11.1	1350	45	90	22	35.5	68	118
TA008	11.1	1550	90	135	25	35.5	68	135
TA013	11.1	1800	75	150	21	35	105	160
TA014	11.1	1500	80	160	25	31	85	140
TA005	14.8	1350	45	90	29	35.5	68	162
TA011	14.8	1550	75	150	37	35.5	68	176
TA015	14.8	1800	45	90	32	30.5	95	208
TA018	18.5	1800	75	150	42	30.5	95	246
TA020	22.2	1800	75	100	50	30.5	95	286
TA025	22.2	2700	45	90	39	37	123	435

Model	Nominal Voltage(V)	Nominal Capacity(mAh)	Continuous Discharge Rate(C)	Instantaneous Discharge Rate(C)	Standard Charging Rate(C)	Maximum Charging Rate(C)	Dimension(mm)	Weight Approx(g)
STANDARD LITHIUMPOLYMER BATTERY SERIES								
Model	Nominal Voltage(V)	Nominal Capacity(mAh)	Continuous Discharge Rate(C)	Instantaneous Discharge Rate(C)	Standard Charging Rate(C)	Maximum Charging Rate(C)	Dimension(mm)	Weight Approx(g)
W<S÷	h yðu5S<	h yð[˚ĩ	c ~íe>u5u5mA	w~˚ðe>u5u5mA	h Q/ÆQEu5u5mA	g Y˚QEu5u5mA	\: [ø	íĩ
T22210H	22.2V	10000mAh	15C	30C	0.5C	3C	185*74*50	1400
T22212H	22.2V	12000mAh	15C	30C	0.5C	3C	185*74*58	1500
T22216H	22.2V	16000mAh	15C	30C	0.5C	3C	185*74*73	2000
T22222H	22.2V	22000mAh	15C	30C	0.5C	3C	205*102*65	2600
T22225H	22.2V	25000mAh	15C	30C	0.5C	3C	205*102*73	3000
T44416H	44.4V	16000mAh	15C	30C	0.5C	3C	185*74*139	4200
T44422H	44.4V	22000mAh	15C	30C	0.5C	3C	205*102*128	5400
T44425H	44.4V	25000mAh	15C	30C	0.5C	3C	205*102*139	6200
MICRO QUADCOPTERLITHIUM POLYMER BATTERY								
Model	Nominal Voltage(V)	Nominal Capacity(mAh)	Continuous Discharge Rate(C)	Pluse Discharge Rate(C)	Dimension (mm) \: [ø			Weight Approx(g)
W<S÷	h yðu5S<	h yð[˚ĩ	c ~íP s÷ĩ	g Y˚P s‡	Thickness SŠ^ĩ	Width [½^ĩ	Height ŠØ^ĩ	íĩ
T5055	3.7	150	30	60	6 ± 1	12 ± 1	43 ± 3	6 ± 2
T5055-A	3.7	200	45	90	5.5 ± 1	12 ± 1	51 ± 3	6 ± 2
T5055-B	3.7	250	45	90	6 ± 1	12 ± 1	51 ± 3	6.5 ± 2
T5056	3.7	250	30	60	6.5 ± 1	20 ± 1	38 ± 3	9 ± 3
T5057	3.7	400	30	60	8.5 ± 1	20 ± 1	38 ± 3	12 ± 3
T5058	3.7	500	30	60	6.5 ± 1	18.5 ± 1	58 ± 3	15 ± 4
T5060	3.7	600	15	30	7.5 ± 1	17.5 ± 1	58 ± 3	15 ± 4
T5061	3.7	600	30	60	9.0 ± 1	25.5 ± 1	46 ± 3	21 ± 4
T5097	7.4	200	15	30	13 ± 1	21 ± 1	34 ± 2	14 ± 3
T5097-A	7.4	250	35	70	13.5 ± 1.5	21 ± 1	37 ± 2	17 ± 5
T5097-B	7.4	280	15	30	11.5 ± 1	21 ± 1	37 ± 2	17 ± 5

[VERIFIED LAB DATA]

Chief Hardware Engineer
Aplic Battery Testing Facility