

Solid-state standard voltage upgrade to ultra-high energy density (3.7V)

Specifications/Capacity (AH)		Nominal voltage (V)	size	Weight approximately KG	m a g n i f i c a t i o n ŷ	Energy density (Wh/kg)
6S-12.5AH		22.2V	176*60*41	1KG	10C	350Wh/kg
12S-12.5AH		44.4V	176*60*80	1.80KG	10C	350Wh/kg
14S-12.5AH		51.8V	176*60*95	2.5KG	10C	350Wh/kg
6S-14.2AH		22.2V	176*60*45	1.2KG	10C	350Wh/kg
12S-14.2AH		44.4V	176*60*89	2.1KG	10C	350Wh/kg
14S-14.2AH		51.8V	176*60*102	2.4KG	10C	350Wh/kg
6S-15AH		22.2V	176*60*48	1.2KG	10C	350Wh/kg
12S-15AH		44.4V	176*60*94	2.1KG	10C	350Wh/kg
14S-15AH		51.8V	176*60*110	2.4KG	10C	350Wh/kg
6S-18AH		22.2V	190*75*47	1.4KG	10C	340Wh/kg
12S-18AH		44.4V	190*75*93	2.60KG	10C	340Wh/kg
14S-18AH		51.8V	190*75*108	3.0KG	10C	340Wh/kg
6S-21AH		22.2V	210*80*43	1.6KG	10C	340Wh/kg
12S-21AH		44.4V	210*80*86	3.1KG	10C	340Wh/kg
14S-21AH		51.8V	210*80*102	3.5KG	10C	340Wh/kg
6S-22AH		22.2V	195*75*53	1.6KG	10C	350Wh/kg
12S-22AH		44.4V	195*75*105	3.1KG	10C	350Wh/kg
14S-22AH		51.8V	195*75*124	3.5KG	10C	350Wh/kg
6S-20AH		22.2V	190*75*52	1.5KG	10C	340Wh/kg
12S-20AH		44.4V	190*75*103	2.9KG	10C	340Wh/kg
14S-20AH		51.8V	190*75*122	3.3KG	10C	340Wh/kg
6S-29.5AH		22.2V	195*75*65	2.1KG	10C	350Wh/kg
12S-29.5AH		44.4V	195*75*128	3.9KG	10C	350Wh/kg
14S-29.5AH		51.8V	195*75*152	4.46KG	10C	350Wh/kg

Specifications/Capacity (AH)		Nominal voltage (V)	size	Weight approximately KG	m a g n i f i c a t i o n ŷ	Energy density (Wh/kg)
6S-30AH		22.2V	205*90*56	2.2KG	10C	340Wh/kg
12S-30AH		44.4V	205*90*111	4.2KG	10C	340Wh/kg
14S-30AH		51.8V	205*90*130	4.9KG	10C	340Wh/kg
6S-33AH		22.2V	211*88*62	2.3KG	10C	350Wh/kg
12S-33AH		44.4V	211*88*123	4.4KG	10C	350Wh/kg
14S-33AH		51.8V	211*88*143	5.1KG	10C	350Wh/kg
6S-36AH		22.2V	211*88*66	2.5KG	10C	350Wh/kg
12S-36AH		44.4V	211*88*130	4.8KG	10C	350Wh/kg
14S-36AH		51.8V	211*88*153	5.6KG	10C	350Wh/kg
6S-39AH		22.2V	213*87*68	2.7KG	10C	350Wh/kg
12S-39AH		44.4V	213*88*130	5.1KG	10C	350Wh/kg
14S-39AH		51.8V	213*89*155	6.1KG	10C	350Wh/kg
Solid-state ultra-high voltage 4.45V high energy density						
Specifications/Capacity (AH)		Nominal voltage (V)	size	Weight approximately KG	m a g n i f i c a t i o n ŷ C)	Energy density (Wh/kg)
6S-35AH		23.7V	220*118*60	3.2KG	10C	300
12S-35AH		47.4V	220*118*117	6.2KG	10C	300
14S-35AH		55.3V	220*118*136	7.2KG	10C	300
6S-33AH		23.7V	211*88*74	2.9KG	10C	300
12S-33AH		47.4V	211*88*146	5.7KG	10C	300
14S-33AH		55.3V	211*88*171	6.6KG	10C	300
6S-33AH		23.7V	205*90*68	2.7KG	10C	300
12S-33AH		47.4V	205*90*135	5.2KG	10C	300
14S-33AH		55.3V	205*90*157	6.1KG	10C	300
6S-2.5AH		23.7V	75*35*48	0.25KG	10C	290
12S-2.5AH		47.4V	75*35*97	0.46KG	10C	290
6S-2.6AH		23.7V	75*35*53	0.27KG	10C	295
12S-2.6AH		47.4V	75*35*105	0.49KG	10C	295

[VERIFIED LAB DATA]
Chief Hardware Engineer
Aplic Battery Testing Facility