Lab 2 Class Task: Arrays, Binary Search and Sorting

Data Structures Lab (CSDS-224L)

Name: Areeba Shahzadi Roll No: 9250097 Date: 21-oct-2026

Instructions

- Complete the tasks in order. Save each one as its own file: task1.cpp, task2.cpp, and so on.
- Type the code yourself. Run it and check that your output matches the sample run.
- Show each working task to your instructor and get it signed in the checklist at the end.
- Functions go **above** main. Calls go **inside** main.
- Binary search only works on a **sorted** array.

Task 1: Iterative binary search (ages)

The ages of 8 students are stored in ascending order:

12 15 18 21 25 30 34 41

Write a function that uses **iterative** binary search to find an age. In main, ask the user to enter an age, call the function, and print the index where it was found, or a message that it was not found.

Hint: start with this function header.

```
int binarySearch(int arr[], int size, int key)
```

Sample runs:

```
Enter age to search: 25
25 found at index 4

Enter age to search: 20
20 not found
```

```cpp
#include <iostream>
using namespace std;

int binarySearch(int arr[], int size, int key) {
    int low = 0;
    int high = size - 1;

    while (low <= high) {
        int mid = low + (high - low) / 2;

        if (arr[mid] == key) {
            return mid;
        }
        else if (arr[mid] < key) {
            low = mid + 1;
        }
        else {
            high = mid - 1;
        }
    }

    return -1;
}

int main() {
    int ages[8] = {12, 15, 18, 21, 25, 30, 34, 41};
    int age;

    cout << "Enter age to search: ";
    cin >> age;
```

```cpp
int main() {
    int ages[8] = {12, 15, 18, 21, 25, 30, 34, 41};
    int age;

    cout << "Enter age to search: ";
    cin >> age;

    int index = binarySearch(ages, 8, age);

    if (index != -1) {
        cout << age << " found at index " << index << endl;
    }
    else {
        cout << age << " not found" << endl;
    }

    return 0;
}
```

Task 2: Recursive binary search (prices)

The prices of 7 items are stored in ascending order:

50 120 175 240 300 450 620

Write a **recursive** binary search function. Ask the user for a price and print the index or a not-found message, in the same way as Task 1.

Hint: you need two base cases. Do not forget the return before each recursive call.

```
int binarySearch(int arr[], int low, int high, int key)
```

Sample runs:

```
Enter price to search: 300
300 found at index 4

Enter price to search: 100
100 not found
```

```cpp
#include <iostream>
using namespace std;

int binarySearch(int arr[], int low, int high, int key) {
    if (low > high) {
        return -1;
    }

    int mid = low + (high - low) / 2;
    if (arr[mid] == key) {
        return mid;
    }
    if (arr[mid] < key) {
        return binarySearch(arr, mid + 1, high, key);
    }
    return binarySearch(arr, low, mid - 1, key);
}

int main() {
    int prices[7] = {50, 120, 175, 240, 300, 450, 620};
    int price;

    cout << "Enter price to search: ";
    cin >> price;

    int index = binarySearch(prices, 0, 6, price);

    if (index != -1) {
        cout << price << " found at index " << index << endl;
    }
```

```cpp
int main() {
    int prices[7] = {50, 120, 175, 240, 300, 450, 620};
    int price;

    cout << "Enter price to search: ";
    cin >> price;

    int index = binarySearch(prices, 0, 6, price);

    if (index != -1) {
        cout << price << " found at index " << index << endl;
    }
    else {
        cout << price << " not found" << endl;
    }

    return 0;
}
```

Task 3: Selection sort (read and sort)

Read 6 integers from the keyboard into an array. Sort them in **ascending** order using **selection sort**. Print the sorted array, then print the smallest and the largest value.

Hint: after sorting, the smallest value is arr[0] and the largest is arr[size - 1].

```
void selectionSort(int arr[], int size)
```

Sample run:

```
Enter 6 numbers: 40 15 72 8 33 21
Sorted: 8 15 21 33 40 72
Smallest: 8
Largest: 72
```

```cpp
#include <iostream>
using namespace std;

void selectionSort(int arr[], int size) {
    for (int i = 0; i < size - 1; i++) {
        int minIndex = i;

        for (int j = i + 1; j < size; j++) {
            if (arr[j] < arr[minIndex]) {
                minIndex = j;
            }
        }
        int temp = arr[i];
        arr[i] = arr[minIndex];
        arr[minIndex] = temp;
    }
}

int main() {
    int arr[6];

    cout << "Enter 6 numbers: ";

    for (int i = 0; i < 6; i++) {
        cin >> arr[i];
    }

    selectionSort(arr, 6);

    cout << "Sorted: ";
```

```cpp
int main() {
    int arr[6];

    cout << "Enter 6 numbers: ";

    for (int i = 0; i < 6; i++) {
        cin >> arr[i];
    }

    selectionSort(arr, 6);

    cout << "Sorted: ";
    for (int i = 0; i < 6; i++) {
        cout << arr[i] << " ";
    }

    cout << endl;
    cout << "Smallest: " << arr[0] << endl;
    cout << "Largest: " << arr[5] << endl;

    return 0;
}
```

Task 4: Bubble sort with a pass counter

Write a bubble sort (ascending) that uses a swapped flag to stop early, and make the function **return the number of passes** it made (count the last pass that finds nothing to swap). Test it on two arrays:


- 9 7 5 3 1 (reverse order)
- 1 2 3 4 5 (already sorted)

Hint: add one to passes at the start of every pass. Why does the already sorted array need fewer passes?

```
int bubbleSort(int arr[], int size)
```

Expected output:

```
Array 1 sorted: 1 3 5 7 9   Passes: 4
Array 2 sorted: 1 2 3 4 5   Passes: 1
```



```cpp
#include <iostream>
using namespace std;

int bubbleSort(int arr[], int size) {
    int passes = 0;


    for (int i = 0; i < size - 1; i++) {
        bool swapped = false;
        passes++;

        for (int j = 0; j < size - 1 - i; j++) {
            if (arr[j] > arr[j + 1]) {
                int temp = arr[j];
                arr[j] = arr[j + 1];
                arr[j + 1] = temp;

                swapped = true;
            }
        }

        if (swapped == false) {
            break;
        }
    }

    return passes;
}
```



```cpp
int main() {
    int arr1[5] = {9, 7, 5, 3, 1};
    int arr2[5] = {1, 2, 3, 4, 5};

    int passes1 = bubbleSort(arr1, 5);
    int passes2 = bubbleSort(arr2, 5);

    cout << "Array 1 sorted: ";
    for (int i = 0; i < 5; i++) {
        cout << arr1[i] << " ";
    }
    cout << " Passes: " << passes1 << endl;

    cout << "Array 2 sorted: ";
    for (int i = 0; i < 5; i++) {
        cout << arr2[i] << " ";
    }
    cout << " Passes: " << passes2 << endl;

    return 0;
}
```

Task 5: Insertion sort with a shift counter

Sort the array 23 11 45 8 30 in ascending order using **insertion sort**. Make the function return the **total number of shifts**, which is the number of times a value is moved one place to the right inside the while loop.

Hint: add one to shifts each time you run arr[j + 1] = arr[j];.

```
int insertionSort(int arr[], int size)
```

Expected output:

```
Sorted: 8 11 23 30 45
Shifts: 5
```

```cpp
#include <iostream>
using namespace std;

int insertionSort(int arr[], int size) {
    int shifts = 0;

    for (int i = 1; i < size; i++) {
        int key = arr[i];
        int j = i - 1;

        while (j >= 0 && arr[j] > key) {
            arr[j + 1] = arr[j];
            shifts++;
            j--;
        }

        arr[j + 1] = key;
    }

    return shifts;
}
```

```cpp
int main() {
    int arr[5] = {23, 11, 45, 8, 30};

    int shifts = insertionSort(arr, 5);

    cout << "Sorted: ";
    for (int i = 0; i < 5; i++) {
        cout << arr[i] << " ";
    }

    cout << endl;
    cout << "Shifts: " << shifts << endl;

    return 0;
}
```

Task 6: Sort first, then search

Combine what you have learned. Read 8 integers from the keyboard (in any order). Sort them with **any** sorting function from Tasks 3 to 5. Print the sorted array. Then ask the user for a value and search for it with **binary search** (iterative or recursive). Print its index in the sorted array, or a not-found message.

Then run it again and search for 40. It should print 40 not found.

Question to answer in your notebook: what goes wrong if you run binary search **before** sorting?

Sample run:

```
Enter 8 numbers: 52 17 83 24 9 61 38 70
Sorted: 9 17 24 38 52 61 70 83
Enter value to search: 61
61 found at index 5
```

```cpp
#include <iostream>
using namespace std;

void selectionSort(int arr[], int size) {
    for (int i = 0; i < size - 1; i++) {
        int minIndex = i;

        for (int j = i + 1; j < size; j++) {
            if (arr[j] < arr[minIndex]) {
                minIndex = j;
            }
        }

        int temp = arr[i];
        arr[i] = arr[minIndex];
        arr[minIndex] = temp;
    }
}

int binarySearch(int arr[], int size, int key) {
    int low = 0;
    int high = size - 1;

    while (low <= high) {
        int mid = low + (high - low) / 2;

        if (arr[mid] == key) {
            return mid;
        }
        else if (arr[mid] < key) {
```

```cpp
int binarySearch(int arr[], int size, int key) {
    int low = 0;
    int high = size - 1;

    while (low <= high) {
        int mid = low + (high - low) / 2;

        if (arr[mid] == key) {
            return mid;
        }
        else if (arr[mid] < key) {
            low = mid + 1;
        }
        else {
            high = mid - 1;
        }
    }

    return -1;
}
```

```
int main() {
    int arr[8];
    int value;

    cout << "Enter 8 numbers: ";
    for (int i = 0; i < 8; i++) {
        cin >> arr[i];
    }

    selectionSort(arr, 8);

    cout << "Sorted: ";
    for (int i = 0; i < 8; i++) {
        cout << arr[i] << " ";
    }
    cout << endl;

    cout << "Enter value to search: ";
    cin >> value;

    int index = binarySearch(arr, 8, value);

    if (index != -1) {
        cout << value << " found at index " << index << endl;
    }
    else {
        cout << value << " not found" << endl;
    }

    return 0;
```

Task 7 (Challenge): Binary search on a descending array

This array is sorted from **highest to lowest**:

90 75 60 45 30 15

The normal binary search will fail on it. Change **one comparison** so that it works for a descending array. Search for 45 and for 50.

Expected output:

```
45 found at index 3
50 not found
```

```cpp
#include <iostream>
using namespace std;

int binarySearch(int arr[], int size, int key) {
    int low = 0;
    int high = size - 1;

    while (low <= high) {
        int mid = low + (high - low) / 2;

        if (arr[mid] == key) {
            return mid;
        }
        else if (arr[mid] > key) {
            low = mid + 1;
        }
        else {
            high = mid - 1;
        }
    }

    return -1;
}
```

```cpp
int main() {
    int arr[6] = {90, 75, 60, 45, 30, 15};

    int index1 = binarySearch(arr, 6, 45);

    if (index1 != -1) {
        cout << "45 found at index " << index1 << endl;
    }
    else {
        cout << "45 not found" << endl;
    }

    int index2 = binarySearch(arr, 6, 50);

    if (index2 != -1) {
        cout << "50 found at index " << index2 << endl;
    }
    else {
        cout << "50 not found" << endl;
    }

    return 0;
}
```

Checklist

Task	What it practises	Output correct	Instructor sign
1	Iterative binary search		
2	Recursive binary search		
3	Selection sort		
4	Bubble sort and passes		
5	Insertion sort and shifts		
6	Sort, then search		
7	Challenge: descending search		