Description | Accepted | Editorial | Solutions | Submissions

977. Squares of a Sorted Array

Solved

Easy | Topics | Companies

Given an integer array `nums` sorted in **non-decreasing** order, return *an array of **the squares of each number** sorted in non-decreasing order.*

Example 1:

```
Input: nums = [-4,-1,0,3,10]
Output: [0,1,9,16,100]
Explanation: After squaring, the array becomes [16,1,0,9,100].
After sorting, it becomes [0,1,9,16,100].
```

Example 2:

```
Input: nums = [-7,-3,2,3,11]
Output: [4,9,9,49,121]
```

Constraints:

- `1 <= nums.length <= 10^4`
- `-10^4 <= nums[i] <= 10^4`
- `nums` is sorted in **non-decreasing** order.

10.2K | 171 | 116 Online

Code

Java | Auto

```java
class Solution {
    public int[] sortedSquares(int[] nums) {
        int n = nums.length;
        int[] result = new int[n];

        int left = 0, right = n - 1;
        int pos = n - 1;

        while (left <= right) {
            if (Math.abs(nums[left]) > Math.abs(nums[right])) {
                result[pos] = nums[left] * nums[left];
```

Saved | Ln 22, Col 2

Testcase | Test Result

Accepted Runtime: 0 ms

Case 1 | Case 2

Input

nums =
[-4,-1,0,3,10]

Output

[0,1,9,16,100]

Expected

Humid Now | Search | ENG IN | 09:55 26-03-2026

Description | Accepted | Editorial | Solutions | Submissions

219. Contains Duplicate II

Solved

Easy | Topics | Companies

Given an integer array `nums` and an integer `k`, return `true` *if there are two* ***distinct indices*** `i` *and* `j` *in the array such that* `nums[i] == nums[j]` *and* `abs(i - j) <= k`.

Example 1:

```
Input: nums = [1,2,3,1], k = 3
Output: true
```

Example 2:

```
Input: nums = [1,0,1,1], k = 1
Output: true
```

Example 3:

```
Input: nums = [1,2,3,1,2,3], k = 2
Output: false
```

Constraints:

- `1 <= nums.length <= 10^5`
- `-10^9 <= nums[i] <= 10^9`

7.5K | 432 | 101 Online

Code

Java | Auto

```java
class Solution {
    public boolean containsNearbyDuplicate(int[] nums, int k) {
        HashSet<Integer> set = new HashSet<>();

        for (int i = 0; i < nums.length; i++) {
            // Check if duplicate exists in current window
            if (set.contains(nums[i])) {
                return true;
            }

            set.add(nums[i]);

            // Maintain window size of k
            if (set.size() > k) {
```

Saved | Ln 23, Col 2

Testcase | Test Result

Accepted Runtime: 0 ms

Case 1 | Case 2 | Case 3

Input

nums =
[1,2,3,1]

k =

Problem List | Submit | 0 | 359:00:56 | Premium

Description | Editorial | Solutions | Submissions

1480. Running Sum of 1d Array

Solved

Easy | Topics | Companies | Hint

Given an array `nums`. We define a running sum of an array as `runningSum[i] = sum(nums[0]…nums[i])`.

Return the running sum of `nums`.

Example 1:

```
Input: nums = [1,2,3,4]
Output: [1,3,6,10]
Explanation: Running sum is obtained as follows: [1, 1+2, 1+2+3, 1+2+3+4].
```

Example 2:

```
Input: nums = [1,1,1,1,1]
Output: [1,2,3,4,5]
Explanation: Running sum is obtained as follows: [1, 1+1, 1+1+1, 1+1+1+1,
1+1+1+1+1].
```

Example 3:

```
Input: nums = [3,1,2,10,1]
Output: [3,4,6,16,17]
```

8.8K | 204 | 56 Online

Code

Java | Auto

```java
class Solution {
    public int[] runningSum(int[] nums) {
        int[] result = new int[nums.length];
        result[0] = nums[0];

        for (int i = 1; i < nums.length; i++) {
            result[i] = result[i - 1] + nums[i];
        }

        return result;
    }
}
```

Saved | Ln 12, Col

Testcase | Test Result

Accepted Runtime: 0 ms

Case 1 | Case 2 | Case 3

Input

nums =

[1,2,3,4]

Output

Problem List | Submit | 0 | 359:00:56 | Premium

Description | Accepted | Editorial | Solutions | Submissions

1685. Sum of Absolute Differences in a Sorted Array

Solved

Medium | Topics | Companies | Hint

You are given an integer array `nums` sorted in **non-decreasing** order.

Build and return *an integer array* `result` *with the same length as* `nums` *such that* `result[i]` *is equal to the* ***summation of absolute differences*** *between* `nums[i]` *and all the other elements in the array.*

In other words, `result[i]` is equal to `sum(|nums[i]-nums[j]|)` where `0 <= j < nums.length` and `j != i` (**0-indexed**).

Example 1:

```
Input: nums = [2,3,5]
Output: [4,3,5]
Explanation: Assuming the arrays are 0-indexed, then
result[0] = |2-2| + |2-3| + |2-5| = 0 + 1 + 3 = 4,
result[1] = |3-2| + |3-3| + |3-5| = 1 + 0 + 2 = 3,
result[2] = |5-2| + |5-3| + |5-5| = 3 + 2 + 0 = 5.
```

Example 2:

```
Input: nums = [1,4,6,8,10]
Output: [24,15,13,15,21]
```

2.2K | 87 | 8 Online

Code

Java | Auto

```java
            int leftSum = 0;
            if (i > 0) {
                leftSum = nums[i] * i - prefixSum[i - 1];
            }

            int rightSum = (prefixSum[n - 1] - prefixSum[i])
                           - nums[i] * (n - i - 1);

            result[i] = leftSum + rightSum;
        }

        return result;
    }
}
```

Saved | Ln 28, Col 2

Testcase | Test Result

Accepted Runtime: 0 ms

Case 1 | Case 2

Input

nums =
[2,3,5]

Output

Problem List | Submit | 0 | 359:00:56 | Premium

Description | Accepted | Editorial | Solutions | Submissions

704. Binary Search

Solved

Easy | Topics | Companies

Given an array of integers `nums` which is sorted in ascending order, and an integer `target`, write a function to search `target` in `nums`. If `target` exists, then return its index. Otherwise, return `-1`.

You must write an algorithm with `O(log n)` runtime complexity.

Example 1:

```
Input: nums = [-1,0,3,5,9,12], target = 9
Output: 4
Explanation: 9 exists in nums and its index is 4
```

Example 2:

```
Input: nums = [-1,0,3,5,9,12], target = 2
Output: -1
Explanation: 2 does not exist in nums so return -1
```

Constraints:

- `1 <= nums.length <= 10^4`
- `-10^4 < nums[i], target < 10^4`

13.5K | 212 | 180 Online

Code

Java | Auto

```java
            int mid = left + (right - left) / 2;

            if (nums[mid] == target) {
                return mid;
            } else if (nums[mid] < target) {
                left = mid + 1;
            } else {
                right = mid - 1;
            }
        }

        return -1;
    }
}
```

Saved | Ln 19, Col 2

Testcase | Test Result

Accepted Runtime: 0 ms

Case 1 | Case 2

Input

nums =
[-1,0,3,5,9,12]

target =
9

Problem List | Submit | 0 | 359:00:56 | Premium

Description | Accepted | Editorial | Solutions | Submissions

75. Sort Colors

Solved

Medium | Topics | Companies | Hint

Given an array `nums` with `n` objects colored red, white, or blue, sort them **in-place** so that objects of the same color are adjacent, with the colors in the order red, white, and blue.

We will use the integers `0`, `1`, and `2` to represent the color red, white, and blue, respectively.

You must solve this problem without using the library's sort function.

Example 1:

```
Input: nums = [2,0,2,1,1,0]
Output: [0,0,1,1,2,2]
```

Example 2:

```
Input: nums = [2,0,1]
Output: [0,1,2]
```

Constraints:

- `n == nums.length`
- `1 <= n <= 300`

21.6K | 659 | 180 Online

Code

Java | Auto

```java
            mid++;
        } else { // nums[mid] == 2
            swap(nums, mid, high);
            high--;
        }
    }
}

private void swap(int[] nums, int i, int j) {
    int temp = nums[i];
    nums[i] = nums[j];
    nums[j] = temp;
}
}
```

Saved | Ln 24, Col 2

Testcase | Test Result

Accepted Runtime: 0 ms

Case 1 | Case 2

Input

nums =
[2,0,2,1,1,0]

Output

Problem List | Submit | 0 | 359:00:56 | Premium

Description | Accepted | Editorial | Solutions | Submissions

121. Best Time to Buy and Sell Stock

Solved

Easy | Topics | Companies

You are given an array `prices` where `prices[i]` is the price of a given stock on the ith day.

You want to maximize your profit by choosing a **single day** to buy one stock and choosing a **different day in the future** to sell that stock.

Return *the maximum profit you can achieve from this transaction.* If you cannot achieve any profit, return `0`.

Example 1:

```
Input: prices = [7,1,5,3,6,4]
Output: 5
Explanation: Buy on day 2 (price = 1) and sell on day 5 (price = 6), profit = 6-1
= 5.
Note that buying on day 2 and selling on day 1 is not allowed because you must
buy before you sell.
```

Example 2:

```
Input: prices = [7,6,4,3,1]
Output: 0
Explanation: In this case, no transactions are done and the max profit = 0.
```

35.6K | 790 | 519 Online

Code

Java | Auto

```java
class Solution {
    public int maxProfit(int[] prices) {
        int minPrice = Integer.MAX_VALUE;
        int maxProfit = 0;

        for (int price : prices) {
            if (price < minPrice) {
                minPrice = price; // better buying price
            } else {
                maxProfit = Math.max(maxProfit, price - minPrice);
            }
        }

        return maxProfit;
    }
```

Saved | Ln 16, Col 2

Testcase | Test Result

Accepted Runtime: 0 ms

Case 1 | Case 2

Input

prices =
[7,1,5,3,6,4]

Output

Problem List

Submit

Premium

Description | Accepted | Editorial | Solutions | Submissions

387. First Unique Character in a String

Solved

Easy | Topics | Companies

Given a string `s`, find the **first** non-repeating character in it and return its index. If it **does not** exist, return `-1`.

Example 1:

> **Input:** `s = "leetcode"`
>
> **Output:** `0`
>
> **Explanation:**
>
> The character `'l'` at index 0 is the first character that does not occur at any other index.

Example 2:

> **Input:** `s = "loveleetcode"`
>
> **Output:** 2

Example 3:

> **Input:** `s = "aabb"`
>
> **Output:** -1

9.8K | 141 | 101 Online

Code

Java | Auto

```java
        for (char c : s.toCharArray()) {
            freq[c - 'a']++;
        }

        // Step 2: Find first unique character
        for (int i = 0; i < s.length(); i++) {
            if (freq[s.charAt(i) - 'a'] == 1) {
                return i;
            }
        }

        return -1;
    }
}
```

Saved

Ln 19, Col 2

Testcase | Test Result

Accepted Runtime: 0 ms

Case 1 | Case 2 | Case 3

Input

s =
"leetcode"

Output

Move Zeroes - LeetCode | Move Zeroes Solution

https://leetcode.com/problems/move-zeroes/description/

Problem List | Submit | 359:00:56 | Premium

Description | Accepted | Editorial | Solutions | Submissions

283. Move Zeroes

Solved

Easy | Topics | Companies | Hint

Given an integer array `nums`, move all `0`'s to the end of it while maintaining the relative order of the non-zero elements.

Note that you must do this in-place without making a copy of the array.

Example 1:

```
Input: nums = [0,1,0,3,12]
Output: [1,3,12,0,0]
```

Example 2:

```
Input: nums = [0]
Output: [0]
```

Constraints:

- $1 \le nums.length \le 10^5$
- $-2^{31} \le nums[i] \le 2^{31} - 1$

19.4K | 402 | 234 Online

Code

Java | Auto

```java
class Solution {
    public void moveZeroes(int[] nums) {
        int j = 0; // position for next non-zero

        // Move non-zero elements forward
        for (int i = 0; i < nums.length; i++) {
            if (nums[i] != 0) {
                nums[j] = nums[i];
                j++;
            }
        }

        // Fill remaining with zeros
        while (j < nums.length) {
```

Saved | Upgrade to Cloud Saving | Ln 19, Col 2

Testcase | Test Result

Accepted Runtime: 0 ms

Case 1 | Case 2

Input

nums =
[0,1,0,3,12]

Output

Move Zeroes Solution | Reverse String - LeetCode

https://leetcode.com/problems/reverse-string/description/

Problem List | Submit | 359:00:56 | Premium

Description | Accepted | Editorial | Solutions | Submissions

344. Reverse String

Solved

Easy | Topics | Companies | Hint

Write a function that reverses a string. The input string is given as an array of characters `s`.

You must do this by modifying the input array in-place with `O(1)` extra memory.

Example 1:

```
Input: s = ["h","e","l","l","o"]
Output: ["o","l","l","e","h"]
```

Example 2:

```
Input: s = ["H","a","n","n","a","h"]
Output: ["h","a","n","n","a","H"]
```

Constraints:

- `1 <= s.length <= 10^5`
- `s[i]` is a printable ascii character.

9.6K | 310 | 85 Online

Code

Java | Auto

```java
class Solution {
    public void reverseString(char[] s) {
        int left = 0;
        int right = s.length - 1;

        while (left < right) {
            char temp = s[left];
            s[left] = s[right];
            s[right] = temp;

            left++;
            right--;
        }
    }
```

Saved | Ln 15, Col 2

Testcase | Test Result

Accepted Runtime: 0 ms

Case 1 | Case 2

Input

s =
["h","e","l","l","o"]

Output