Status	Finished
Started	Tuesday, 29 September 2026, 4:01 PM
Completed	Tuesday, 29 September 2026, 4:12 PM
Duration	11 mins 8 secs
Grade	**10.00** out of 10.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Objective:

Develop a Python program to find the k-th maximum value in a given list of integers. The program should handle various edge cases, including lists with duplicate values, empty lists, and invalid values of k. The k-th maximum value refers to the k-th largest distinct element in the list.

Background:

Finding the k-th maximum value in a list is a common problem in computer science, often encountered in fields like data analysis, competitive programming, and software development. This problem requires an understanding of sorting algorithms, data structures, and efficient problem-solving techniques. By solving this problem, one gains insights into how to handle large datasets and optimize performance in practical applications.

Problem Description:

Given a list of integers, the task is to determine the k-th maximum value in the list. The program should meet the following requirements:

1. **Input:**
    - A list of integers, which can contain both positive and negative values.
    - An integer k, representing the position of the maximum value to find.
2. **Output:**
    - The k-th maximum value in the list.
    - If k is greater than the number of distinct elements in the list or if the list is empty, the program should return an appropriate message indicating the error.

Constraints:

- The list may contain duplicate values.
- The value of k should be a positive integer.
- The list may contain up to 10^6 elements, and each element can be as large as 10^9 in magnitude.

Examples:

Consider the following examples for better understanding:

1. **Example 1:**
    - **Input:** list = [3, 1, 5, 4, 2], k = 2
    - **Output:** 4
    - **Explanation:** The distinct elements in the list are [1, 2, 3, 4, 5]. The 2nd maximum value is 4.
2. **Example 2:**
    - **Input:** list = [7, 7, 7, 7, 7], k = 1
    - **Output:** 7
    - **Explanation:** The distinct elements in the list are [7]. The 1st maximum value is 7.
3. **Example 3:**
    - **Input:** list = [2, 1, 2, 1, 2], k = 3
    - **Output:** -1
    - **Explanation:** The distinct elements in the list are [1, 2]. There is no 3rd maximum value.

For example:

Input	Result
5 3 1 5 4 2 2	4
6 7 7 7 7 7 7 1	7
10 2 1 2 1 2 1 2 1 2 1 3	-1

Answer: (penalty regime: 0 %)

```python
import sys

def main():
    # Read all tokens from standard input at once for efficiency
    tokens = sys.stdin.read().split()
    if not tokens:
        return

    idx = 0
    while idx < len(tokens):
        # Read the number of elements
        n = int(tokens[idx])
        idx += 1

        # Read the list elements
        nums = []
        for _ in range(n):
            nums.append(int(tokens[idx]))
            idx += 1

        # Read k
        k = int(tokens[idx])
        idx += 1

        # Compute the k-th maximum distinct element
        unique_sorted = sorted(set(nums), reverse=True)

        if k <= 0 or k > len(unique_sorted):
            print(-1)
        else:
            print(unique_sorted[k - 1])

if __name__ == '__main__':
    main()
```

	Input	Expected	Got	
✓	5 3 1 5 4 2 2	4	4	✓
✓	6 7 7 7 7 7 7 1	7	7	✓
✓	10 2 1 2 1 2 1 2 1 2 1 3	-1	-1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **2**

Correct

Mark 1.00 out of 1.00

Write a Python program to sort a list of elements using the merge sort algorithm.

For example:

Input	Result
5 6 5 4 3 8	3 4 5 6 8

Answer: (penalty regime: 0 %)

```
import sys

def merge_sort(arr):
    """Recursively splits the array and merges sorted halves."""
    if len(arr) <= 1:
        return arr

    mid = len(arr) // 2
    left = merge_sort(arr[:mid])
    right = merge_sort(arr[mid:])

    return merge(left, right)

def merge(left, right):
    """Merges two sorted lists into a single sorted list."""
    result = []
    i = j = 0

    while i < len(left) and j < len(right):
        if left[i] < right[j]:
            result.append(left[i])
            i += 1
        else:
            result.append(right[j])
            j += 1

    # Append any remaining elements
    result.extend(left[i:])
    result.extend(right[j:])
    return result

def main():
    # Read all inputs from standard input efficiently
    tokens = sys.stdin.read().split()
    if not tokens:
        return

    idx = 0
    while idx < len(tokens):
        n = int(tokens[idx])
        idx += 1

        arr = []
        for _ in range(n):
            arr.append(int(tokens[idx]))
            idx += 1

        # Sort using merge sort
        sorted_arr = merge_sort(arr)

        # Print space-separated sorted elements
        print(*(sorted_arr))
```

	Input	Expected	Got	
✓	5 6 5 4 3 8	3 4 5 6 8	3 4 5 6 8	✓

	Input	Expected	Got	
✓	9 14 46 43 27 57 41 45 21 70	14 21 27 41 43 45 46 57 70	14 21 27 41 43 45 46 57 70	✓
✓	4 86 43 23 49	23 43 49 86	23 43 49 86	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **3**

Correct

Mark 1.00 out of 1.00

The problem is that we want to reverse a array in O(N) linear time complexity and we want the algorithm to be in-place as well!
For example: input is [1,2,3,4,5] then the output is [5,4,3,2,1]
Input
5
1 2 3 4 5
Output
5 4 3 2 1

For example:

Input	Result
5 1 2 3 4 5	5 4 3 2 1

Answer: (penalty regime: 0 %)

```
import sys

def reverse_in_place(arr):
    """Reverses an array in-place using two pointers."""
    left = 0
    right = len(arr) - 1

    while left < right:
        # Swap elements at left and right pointers
        arr[left], arr[right] = arr[right], arr[left]
        left += 1
        right -= 1

def main():
    # Read all inputs from standard input efficiently
    tokens = sys.stdin.read().split()
    if not tokens:
        return

    idx = 0
    while idx < len(tokens):
        n = int(tokens[idx])
        idx += 1

        arr = []
        for _ in range(n):
            arr.append(int(tokens[idx]))
            idx += 1

        # Reverse the array in-place
        reverse_in_place(arr)

        # Print space-separated reversed elements
        print(*(arr))

if __name__ == '__main__':
    main()
```

	Input	Expected	Got	
✓	5 1 2 3 4 5	5 4 3 2 1	5 4 3 2 1	✓
✓	10 0 2 4 6 8 1 3 5 7 9	9 7 5 3 1 8 6 4 2 0	9 7 5 3 1 8 6 4 2 0	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **4**

Correct

Mark 1.00 out of 1.00

Given an array of integers `arr`, replace each element with its rank.

The rank represents how large the element is. The rank has the following rules:

- Rank is an integer starting from 1.
- The larger the element, the larger the rank. If two elements are equal, their rank must be the same.
- Rank should be as small as possible.

Example 1:

```
Input: arr = [40,10,20,30]
Output: [4,1,2,3]
Explanation: 40 is the largest element. 10 is the smallest. 20 is the second smallest. 30 is the third smallest.
```

Example 2:

```
Input: arr = [100,100,100]
Output: [1,1,1]
Explanation: Same elements share the same rank.
```

Example 3:

```
Input: arr = [37,12,28,9,100,56,80,5,12]
Output: [5,3,4,2,8,6,7,1,3]
```

Constraints:

- $0 <= arr.length <= 10^5$
- $-10^9 <= arr[i] <= 10^9$

For example:

Test	Result
print(arrayRankTransform([40,10,20,30]))	[4, 1, 2, 3]

Answer: (penalty regime: 0 %)

Reset answer

```python
def arrayRankTransform(arr):
    """
    Given an array of integers arr, replace each element with its rank.
    """
    if not arr:
        return []

    # Get unique elements sorted in ascending order
    sorted_unique = sorted(set(arr))

    # Map each unique element to its 1-based rank
    rank_map = {val: i + 1 for i, val in enumerate(sorted_unique)}

    # Construct the result array using the rank mapping
    return [rank_map[x] for x in arr]
```

	Test	Expected	Got	
✓	`print(arrayRankTransform([40,10,20,30]))`	`[4, 1, 2, 3]`	`[4, 1, 2, 3]`	✓
✓	`print(arrayRankTransform([100,100,100]))`	`[1, 1, 1]`	`[1, 1, 1]`	✓
✓	`print(arrayRankTransform([37,12,28,9,100,56,80,5,12]))`	`[5, 3, 4, 2, 8, 6, 7, 1, 3]`	`[5, 3, 4, 2, 8, 6, 7, 1, 3]`	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **5**

Correct

Mark 1.00 out of 1.00

To find the frequency of numbers in a list and display in sorted order.

Constraints:

1<=n, arr[i]<=100

Input:

1 68 79 4 90 68 1 4 5

output:

1 2

4 2

5 1

68 2

79 1

90 1

For example:

Input	Result
4 3 5 3 4 5	3 2 4 2 5 2

Answer: (penalty regime: 0 %)

```
import sys

def main():
    # Read all inputs from standard input
    input_data = sys.stdin.read().split()
    if not input_data:
        return

    # Convert input tokens to integers
    arr = [int(x) for x in input_data]

    # Dictionary to store the frequency of each number
    freq_map = {}
    for num in arr:
        freq_map[num] = freq_map.get(num, 0) + 1

    # Sort the unique numbers and print their frequencies
    for num in sorted(freq_map.keys()):
        print(f"{num} {freq_map[num]}")

if __name__ == "__main__":
    main()
```

	Input	Expected	Got	
✓	4 3 5 3 4 5	3 2 4 2 5 2	3 2 4 2 5 2	✓
✓	12 4 4 4 2 3 5	2 1 3 1 4 3 5 1 12 1	2 1 3 1 4 3 5 1 12 1	✓

	Input	Expected	Got	
✓	5 4 5 4 6 5 7 3	3 1 4 2 5 3 6 1 7 1	3 1 4 2 5 3 6 1 7 1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **6**

Correct

Mark 1.00 out of 1.00

Given an integer array `nums` sorted in **non-decreasing** order, return *an array of **the squares of each number** sorted in non-decreasing order*.

Example 1:

```
Input: nums = [-4,-1,0,3,10]
Output: [0,1,9,16,100]
Explanation: After squaring, the array becomes [16,1,0,9,100].
After sorting, it becomes [0,1,9,16,100].
```

Example 2:

```
Input: nums = [-7,-3,2,3,11]
Output: [4,9,9,49,121]
```

Constraints:

- `1 <= nums.length <= 10^4`
- `-10^4 <= nums[i] <= 10^4`
- `nums` is sorted in **non-decreasing** order.

For example:

Test	Result
`print(sortedSquares([-4,-1,0,3,10]))`	`[0, 1, 9, 16, 100]`

Answer: (penalty regime: 0 %)

Reset answer

```
def sortedSquares(nums):
    n = len(nums)
    result = [0] * n
    left, right = 0, n - 1

    for i in range(n - 1, -1, -1):
        if abs(nums[left]) > abs(nums[right]):
            result[i] = nums[left] ** 2
            left += 1
        else:
            result[i] = nums[right] ** 2
            right -= 1

    return result
```

	Test	Expected	Got	
✓	`print(sortedSquares([-4,-1,0,3,10]))`	`[0, 1, 9, 16, 100]`	`[0, 1, 9, 16, 100]`	✓
✓	`print(sortedSquares([-7,-3,2,3,11]))`	`[4, 9, 9, 49, 121]`	`[4, 9, 9, 49, 121]`	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **7**

Correct

Mark 1.00 out of 1.00

Bubble Sort is the simplest sorting algorithm that works by repeatedly swapping the adjacent elements if they are in wrong order. You read an list of numbers. You need to arrange the elements in ascending order and print the result. The sorting should be done using bubble sort.

Input Format: The first line reads the number of elements in the array. The second line reads the array elements one by one.

Output Format: The output should be a sorted list.

For example:

Input	Result
6 3 4 8 7 1 2	1 2 3 4 7 8
5 4 5 2 3 1	1 2 3 4 5

Answer: (penalty regime: 0 %)

```
import sys

def bubble_sort():
    # Read all inputs from standard input
    input_data = sys.stdin.read().split()
    if not input_data:
        return

    # First line is the number of elements
    n = int(input_data[0])

    # Remaining lines/tokens are the array elements
    arr = [int(x) for x in input_data[1:]]

    # Bubble Sort Algorithm
    for i in range(n):
        swapped = False
        for j in range(0, n - i - 1):
            if arr[j] > arr[j + 1]:
                arr[j], arr[j + 1] = arr[j + 1], arr[j]
                swapped = True
        # Optimization: If no two elements were swapped in the inner loop, the array is sorted
        if not swapped:
            break

    # Print the sorted array separated by spaces
    print(*(arr))

if __name__ == "__main__":
    bubble_sort()
```

	Input	Expected	Got	
✓	6 3 4 8 7 1 2	1 2 3 4 7 8	1 2 3 4 7 8	✓
✓	6 9 18 1 3 4 6	1 3 4 6 9 18	1 3 4 6 9 18	✓
✓	5 4 5 2 3 1	1 2 3 4 5	1 2 3 4 5	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **8**

Correct

Mark 1.00 out of 1.00

Given an integer array `nums`, return *an integer array* `counts` *where* `counts[i]` *is the number of smaller elements to the right of* `nums[i]`.

Example 1:

```
Input: nums = [5,2,6,1]
Output: [2,1,1,0]
Explanation:
To the right of 5 there are 2 smaller elements (2 and 1).
To the right of 2 there is only 1 smaller element (1).
To the right of 6 there is 1 smaller element (1).
To the right of 1 there is 0 smaller element.
```

Example 2:

```
Input: nums = [-1]
Output: [0]
```

Example 3:

```
Input: nums = [-1,-1]
Output: [0,0]
```

Constraints:

- `1 <= nums.length <= 10^5`
- `-10^4 <= nums[i] <= 10^4`

For example:

Test	Result
`print(countSmaller([5,2,6,1]))`	`[2, 1, 1, 0]`
`print(countSmaller([-1]))`	`[0]`

Answer: (penalty regime: 0 %)

Reset answer

```python
class FenwickTree:
    def __init__(self, size):
        self.tree = [0] * (size + 1)
        self.size = size

    def update(self, i, delta):
        while i <= self.size:
            self.tree[i] += delta
            i += i & (-i)

    def query(self, i):
        s = 0
        while i > 0:
            s += self.tree[i]
            i -= i & (-i)
        return s

def countSmaller(nums: list[int]) -> list[int]:
    # Coordinate compression: map each unique value to a 1-based rank
    sorted_unique = sorted(set(nums))
    rank_map = {val: i + 1 for i, val in enumerate(sorted_unique)}

    bit = FenwickTree(len(sorted_unique))
    res = [0] * len(nums)

    # Traverse from right to left
    for i in range(len(nums) - 1, -1, -1):
        val = nums[i]
        rank = rank_map[val]
        # Query how many elements are strictly smaller (ranks less than current rank)
        res[i] = bit.query(rank - 1)
        # Update the tree with the current element's rank
```

```
        bit.update(rank, 1)

    return res
```

	Test	Expected	Got	
✓	print(countSmaller([5,2,6,1]))	[2, 1, 1, 0]	[2, 1, 1, 0]	✓
✓	print(countSmaller([50,20,60,10]))	[2, 1, 1, 0]	[2, 1, 1, 0]	✓
✓	print(countSmaller([-1]))	[0]	[0]	✓
✓	print(countSmaller([-1, -1]))	[0, 0]	[0, 0]	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **9**

Correct

Mark 1.00 out of 1.00

Given an listof integers, sort the array in ascending order using the *Bubble Sort* algorithm above. Once sorted, print the following three lines:

1. List is sorted in numSwaps swaps., where numSwaps is the number of swaps that took place.
2. First Element: firstElement, the *first* element in the sorted list.
3. Last Element: lastElement, the *last* element in the sorted list.

For example, given a worst-case but small array to sort: a=[6,4,1]. It took 3 swaps to sort the array. Output would be

```
Array is sorted in 3 swaps.
```

```
First Element: 1
```

```
Last Element: 6
```

Input Format

The first line contains an integer,n , the size of the list a .
The second line contains n, space-separated integers a[i].

Constraints

· 2<=n<=600

· $1<=a[i]<=2x10^6$.

Output Format

You must print the following three lines of output:

1. List is sorted in numSwaps swaps., where numSwaps is the number of swaps that took place.
2. First Element: firstElement, the *first* element in the sorted list.
3. Last Element: lastElement, the *last* element in the sorted list.

Sample Input 0

3

1 2 3

Sample Output 0

List is sorted in 0 swaps.

First Element: 1

Last Element: 3

For example:

Input	Result
3 3 2 1	List is sorted in 3 swaps. First Element: 1 Last Element: 3
5 1 9 2 8 4	List is sorted in 4 swaps. First Element: 1 Last Element: 9

Answer: (penalty regime: 0 %)

```
import sys

def countSwaps():
    # Read all input from standard input
    input_data = sys.stdin.read().split()
    if not input_data:
        return

    # Parse the size and array elements
    n = int(input_data[0])
```

```
    a = [int(x) for x in input_data[1:n+1]]

    numSwaps = 0

    # Bubble Sort implementation
    for i in range(n):
        for j in range(n - 1):
            if a[j] > a[j + 1]:
                # Swap adjacent elements
                a[j], a[j + 1] = a[j + 1], a[j]
                numSwaps += 1

    # Print the required three lines of output
    print(f"List is sorted in {numSwaps} swaps.")
    print(f"First Element: {a[0]}")
    print(f"Last Element: {a[-1]}")

if __name__ == "__main__":
    countSwaps()
```

	Input	Expected	Got	
✓	3 3 2 1	List is sorted in 3 swaps. First Element: 1 Last Element: 3	List is sorted in 3 swaps. First Element: 1 Last Element: 3	✓
✓	5 1 9 2 8 4	List is sorted in 4 swaps. First Element: 1 Last Element: 9	List is sorted in 4 swaps. First Element: 1 Last Element: 9	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **10**

Correct

Mark 1.00 out of 1.00

Given an array of integers `nums`, sort the array in **increasing** order based on the frequency of the values. If multiple values have the same frequency, sort them in **decreasing** order.

Print the *sorted array*.

Example 1:

```
Input:
6
1 1 2 2 2 3

Output:
3 1 1 2 2 2

Explanation: '3' has a frequency of 1, '1' has a frequency of 2, and '2' has a frequency of 3.
```

Example 2:

```
Input:
5
2 3 1 3 2
Output:
1 3 3 2 2
Explanation: '2' and '3' both have a frequency of 2, so they are sorted in decreasing order.
```

Example 3:

```
Input:
9
-1 1 -6 4 5 -6 1 4 1
Output:
5 -1 4 4 -6 -6 1 1 1
```

Constraints:

- `1 <= nums.length <= 100`
- `-100 <= nums[i] <= 100`

For example:

Input	Result
6 1 1 2 2 2 3	3 1 1 2 2 2
5 2 3 1 3 2	1 3 3 2 2

Answer: (penalty regime: 0 %)

```
import sys
from collections import Counter

def sort_by_frequency():
    # Read all input from standard input
    input_data = sys.stdin.read().split()
    if not input_data:
        return

    # Parse size and array elements
    n = int(input_data[0])
    nums = [int(x) for x in input_data[1:n+1]]

    # Count frequencies
    freq = Counter(nums)

    # Sort nums:
    # 1. freq[x] (ascending order of frequency)
    # 2. -x (descending order of value if frequencies are equal)
```

```
    nums.sort(key=lambda x: (freq[x], -x))

    # Print the sorted array space-separated
    print(*(nums))

if __name__ == "__main__":
    sort_by_frequency()
```

	Input	Expected	Got	
✓	6 1 1 2 2 2 3	3 1 1 2 2 2	3 1 1 2 2 2	✓
✓	5 2 3 1 3 2	1 3 3 2 2	1 3 3 2 2	✓
✓	9 -1 1 -6 4 5 -6 1 4 1	5 -1 4 4 -6 -6 1 1 1	5 -1 4 4 -6 -6 1 1 1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.