



Argon ONE V5 M.2 Case for Raspberry Pi 5

SKU: ARG-ONE-V5 · Product Datasheet

Product Identity

Model No. / MPN	A24-005-AR-V5-NVME-S
UPC / EAN	5065019946164
Dimensions (cm)	10.00 x 4.00 x 16.50 cm
Weight (kg)	0.355
Category	ONE v5
HTS code	8473.30.5100

Compatibility

Raspberry Pi 5

Overview

Premium aluminium case for Raspberry Pi 5 with integrated M.2 NVMe PCIe storage support via the PCIe FPC connector. Features passive aluminium heatsink body, programmable power button, and repositioned full-size HDMI and USB-C ports. Compatible with Raspberry Pi 5 only.

Key Features

- Full-size HDMI ports (2x)
- PWM-controlled 30mm fan
- Programmable power button with safe shutdown
- 40-pin GPIO passthrough header
- All ports rear-facing for clean cable management

Specifications

active_cooling	30mm PWM blower fan, software-controlled
audio	3.5mm combo jack
audio_dac_chip	HS100B
audio_port	1× 3.5mm combo (audio out + mic in), Rear
case_material	Injected aluminum alloy top and injected ABS plastic bottom
case_material_bottom	Injected ABS plastic
case_material_top	Injected aluminum alloy
compatible_board	Raspberry Pi 5 only
cooling_fan	Blower type 30mm PWM
dac_chip	HS100B
dimensions	161 × 99 × 44 mm
ethernet	1× Gigabit
ethernet_port	Yes

ethernet_ports	1× Gigabit (passthrough), Rear
fan	40mm PWM, software-controlled
fan_type	Blower type
front_usb_2_ports	2
gpio	40-pin passthrough header with magnetic cover
gpio_access	Full GPIO Access with Magnetic cover
gpio_header	40-pin Passthrough header with magnetic cover, Top
hdmi	2x full-size HDMI
hdmi_output	2× full-size HDMI
hdmi_ports	2 Regular HDMI
m2_nvme_expansion_options	SINGLE M.2 NVMe PCIe Expansion Board, DUAL M.2 NVMe PCIe Expansion Board
material	Aluminum alloy
nvm_heatsink	Argon THRML M.2 NVMe heatsink with blue silicon thermal pads
nvme_heatsink	Argon THRML M.2 NVMe heatsink included
oled_module	1.8 inch OLED Module
optional_ups	Argon PWR UPS for Argon ONE V5 27W PD
passive_cooling	Aluminum alloy case body acts as heatsink
pcie_connector	U-shaped (included in box)
pcie_expansion	Raspberry Pi 5 native PCIe Gen2 ×1
pcie_standard	Raspberry Pi 5 native PCIe Gen2 ×1
pi5_bluetooth	Bluetooth 5.0 / BLE
pi5_gpu	VideoCore VII, OpenGL ES 3.1, Vulkan 1.2
pi5_power_minimum	5V 3A (15W)
pi5_power_recommended	5V 5A (27W)
pi5_processor	Broadcom BCM2712, 2.4 GHz quad-core 64-bit Arm Cortex-A76
pi5_ram_options	2GB, 4GB, 8GB, or 16GB LPDDR4X-4267
pi5_wifi	Dual-band 802.11ac (2.4 GHz / 5 GHz)
power_button	Programmable, supports safe shutdown
power_input	USB-C
product_name	Argon ONE V5 M.2 Case for Raspberry Pi 5
recommended_power_supply	Argon PWR GaN 27W Power Delivery
sku	ARG-ONE-V5
supported_m2_sizes	2230, 2242, 2260, 2280
tagline	A premium aluminum case for Raspberry Pi 5, combining active cooling, full-size HDMI output, flexible NVMe storage expansion, and a clean all-rear port layout.
thermal_interface	Silicon thermal pads (CPU, RP1, PMIC, RAM) + blue silicon thermal pads for M.2 drives
usb_2_0	2× Type-A, front-facing

usb_2_0_ports	2x front
usb_3_0	2× Type-A, rear-facing
usb_3_0_ports	2x
usb_hub_chip	FE1.1S
zigbee_chip	CC2562P

Document Control

Document version	v9
Product revision	rev 9
Generated	2026-07-24 03:34 UTC
Content hash	e80a322a0524
Revision record	datasheets/ARG-ONE-V5/version-log.json (document_version = 9)

Full revision history for this datasheet is recorded in **version-log.json** — see the entry where *document_version* = 9.