



ARG-ONE-V5-NVME

SKU: ARG-ONE-V5-NVME · Product Datasheet

Product Identity

Model No. / MPN	—
UPC / EAN	—
Dimensions (cm)	—
Weight (kg)	—
Category	—
HTS code	—

Compatibility

Raspberry Pi 5

Overview

Aluminum Raspberry Pi 5 case with M.2 NVMe SSD slot via PCIe for maximum storage performance.

Key Features

- M.2 NVMe SSD slot (PCIe, 2230/2242/2280)
- Full-size HDMI ports (2x)
- PWM-controlled fan
- Programmable power button
- 40-pin GPIO passthrough header

Specifications

active_cooling	30mm blower-type PWM fan, software-controlled via Raspberry Pi OS
audio	3.5mm audio out + mic in, powered by HS100B DAC Chip
audio_dac	HS100B - DAC Chip
audio_dac_chip	HS100B
audio_features	3.5mm audio out and mic in functionality
audio_out	3.5mm
case_material	Injected aluminum alloy top and injected ABS plastic bottom
case_material_bottom	Injected ABS plastic
case_material_top	Injected aluminum alloy
compatibility	Raspberry Pi 5 only
compatible_case	Argon ONE V5
compatible_raspberry_pi	Raspberry Pi 5
compatible_sbc	Raspberry Pi 5 only
cooling_active	Blower-type 30mm PWM fan, software-controlled via Raspberry Pi OS
cooling_passive	Case material design

cooling_system	Blower type 30mm PWM actively controlled by the Raspberry Pi OS
dimensions	110mmx90mm
dual_drive_gen2_chip	ASM1182e chip
dual_drive_gen3_chip	ASM2806 chip
dual_gen2_chipset	ASM1182e
dual_gen2_ports	1 PCIe x1 Gen2 upstream port to 2 PCIe x 1 Gen2 downstream ports
ethernet	Gigabit Ethernet
ethernet_port	1
fan	Blower type 30mm PWM
fan_control	actively controlled by the Raspberry Pi OS
flat_head_screws	8 pcs Flat head 2.5x6
front_usb_2_0_ports	2
front_usb_2_ports	2
gen_2_pcie_switch_chip	ASM1182e
gen_3_pcie_switch_chip	ASM2806
gpio	Full 40-pin passthrough header with magnetic cover
gpio_access	Full GPIO Access with Magnetic cover
gpio_pins	first 8 GPIO pins
hdmi	2x full-size HDMI
hdmi_conversion	Converted the micro HDMI of the RPi 5 to Regular HDMI
hdmi_ports	2 Regular HDMI
included_screws_flat	8 pcs flat head (2.5x6 mm)
included_screws_round	4 pcs round head (2.5x8 mm)
m2_form_factors_supported	2230, 2242, 2260, 2280
m2_nvme_options	SINGLE M.2 NVMe PCIe Expansion Board, DUAL M.2 NVMe PCIe Expansion Board
m2_slot	M.2 NVMe PCIe, 2230/2242/2280
material	Aluminum alloy
mic_in	3.5mm
not_included	Raspberry Pi 5, SD card, M.2 NVMe SSD drives
nvme_board_variants	Single (Gen 2), Dual Gen 2, Quad Gen 2, Dual Gen 3, Quad Gen 3
nvme_form_factors	2230, 2242, 2260, 2280
nvme_heatsink	THRML M.2 NVMe heatsink included
nvme_m2_sizes_supported	2230, 2242, 2260, 2280
nvme_thermal_pads	Blue silicon thermal pads applied to drives
oled_dimensions	55mmx90mm
oled_module	1.8 inch OLED Module
oled_module_gpio_pins	First 8 GPIO pins

oled_module_size	1.8 inch
passive_cooling	Aluminum alloy case body; aluminum THRML heatsinks on NVMe bottom
power_button	Programmable; supports safe shutdown
power_input	USB-C
product	Argon Industrial V5 OLED Module
product_name	Argon Industrial V5 ZigBEE Module
quad_drive_gen2_chip	ASM1182e chip
quad_drive_gen3_chip	ASM2806 chip
quad_gen3_chipset	ASM2806
round_head_screws	4 pcs Round head 2.5x8
screws_flat_head	8 pcs Flat head 2.5x6
screws_round_head	4 pcs Round head 2.5x8
single_board_chipset	RPI 5 Native 1 PCIe Gen2
single_drive_variant	RPI 5 native 1× PCIe Gen2
sku	ARG-ONE-V5-NVME
ssd_capacity_options	128 GB, 256 GB
supplemental_power	Black NVMe power cable required for multi-drive boards
thermal_pad_locations	CPU, RP1, RAM, PMIC
usb_2_0_ports	2
usb_3_0_ports	2
usb_hub_chip	FE1.1S - USB Hub Chip
zigbee_chip	CC2562P
zigbee_compatibility	Fully compatible with Home Assistant Operating System
zigbee_module_chip	CC2562P chip
zigbee_module_port	Internal 6-pin USB port

Document Control

Document version	v5
Product revision	rev 5
Generated	2026-07-24 03:35 UTC
Content hash	c078bf2ec5e0
Revision record	datasheets/ARG-ONE-V5-NVME/version-log.json (document_version = 5)

Full revision history for this datasheet is recorded in **version-log.json** — see the entry where *document_version* = 5.