



ARG-ONE-V5-NVME

SKU: ARG-ONE-V5-NVME · Product Datasheet

Product Identity

Model No. / MPN	A24-005-AR-V5-NVME-S
UPC / EAN	5065019946164
Dimensions (cm)	10.00 x 4.00 x 16.50 cm
Weight (kg)	0.355
Category	ONE v5
HTS code	8473.30.5100

Compatibility

Raspberry Pi 5

Overview

Aluminum Raspberry Pi 5 case with M.2 NVMe SSD slot via PCIe for maximum storage performance.

Key Features

- M.2 NVMe SSD slot (PCIe, 2230/2242/2280)
- Full-size HDMI ports (2x)
- PWM-controlled fan
- Programmable power button
- 40-pin GPIO passthrough header

Specifications

active_cooling	30mm blower-type PWM fan, software-controlled via Raspberry Pi OS
audio	3.5mm audio out + mic in, powered by HS100B DAC Chip
audio_dac	HS100B - DAC Chip
audio_dac_chip	HS100B
audio_ports	3.5mm audio out and mic in
case_material	Injected aluminum alloy top and injected ABS plastic bottom
case_material_bottom	Injected ABS plastic
case_material_top	Injected aluminum alloy
compatibility	Raspberry Pi 5 only
compatible_case	Argon ONE V5
compatible_raspberry_pi	Raspberry Pi 5
compatible_sbc	Raspberry Pi 5 only
cooling_active	Blower type 30mm PWM actively controlled by the Raspberry Pi OS
cooling_passive	Case material design
cpu_thermal_pads	Silicon thermal pads included

dimensions	110mmx90mm
dual_gen2_chip	ASM1182e chip
dual_gen3_chip	ASM2806 chip
ethernet	Gigabit Ethernet
fan	Blower type 30mm PWM
fan_control	actively controlled by the Raspberry Pi OS
fan_size	30mm
flat_head_screws	8 pcs Flat head 2.5x6
front_usb_2_0_ports	2× USB 2.0
front_usb_2_ports	2
gen_2_pcie_switch_chip	ASM1182e
gen_3_pcie_switch_chip	ASM2806
gpio	Full 40-pin passthrough header with magnetic cover
gpio_access	Full GPIO Access with Magnetic cover
gpio_pins	first 8 GPIO pins
hdmi	2x full-size HDMI
hdmi_ports	2 Regular HDMI
included_flat_head_screws	8 pcs (2.5×6 mm)
included_round_head_screws	4 pcs (2.5×8 mm)
m2_form_factors_supported	2230, 2242, 2260, 2280
m2_slot	M.2 NVMe PCIe, 2230/2242/2280
material	Aluminum alloy
not_included	Raspberry Pi 5, SD card, M.2 NVMe SSD drives
nvme_board_variants	Single (Gen 2), Dual Gen 2, Quad Gen 2, Dual Gen 3, Quad Gen 3
nvme_form_factors	2230, 2242, 2260, 2280
nvme_gen_2_chip	ASM1182e
nvme_gen_3_chip	ASM2806
nvme_heatsink	THRML M.2 NVMe heatsink included
nvme_options	Single, Dual, or Quad M.2 NVMe PCIe drives
nvme_size_compatibility	2230, 2242, 2260, 2280
nvme_thermal_pads	Blue silicon thermal pads applied to drives
oled_display_info	IP address, storage, CPU, and memory status
oled_gpio_pins	First 8 GPIO pins
oled_module	1.8 inch OLED Module
oled_module_size	1.8 inch
passive_cooling	Aluminum alloy case body; aluminum THRML heatsinks on NVMe bottom
power_button	Programmable; supports safe shutdown
power_input	USB-C; recommended 27W PD

product_name	Argon Industrial V5 ZigBEE Module
quad_gen2_chip	ASM1182e chip
quad_gen3_chip	ASM2806 chip
recommended_power_supply	Argon PWR GaN 27W Power Delivery
recommended_psu	27W Power Delivery
recommended_ups	Argon PWR UPS for Argon ONE V5 27W PD
round_head_screws	4 pcs Round head 2.5x8
screws_flat_head	8 pcs Flat head 2.5x6
screws_round_head	4 pcs Round head 2.5x8
single_drive_variant	RPI 5 native 1× PCIe Gen2
sku	ARG-ONE-V5-NVME
ssd_options	128 GB and 256 GB M.2 NVMe SSD
supplemental_power	Black NVMe power cable required for multi-drive boards
usb_2_0_front	2× USB 2.0 ports via FE1.1S USB Hub Chip
usb_2_0_ports	2 Front USB 2.0 ports
usb_3_0	2× USB 3.0 ports
usb_3_0_ports	2× USB 3.0
usb_hub_chip	FE1.1S
zigbee_chip	CC2562P
zigbee_compatibility	Fully compatible with Home Assistant OS
zigbee_module	Argon Industria V5 with CC2562P chip
zigbee_port	Internal 6-pin USB port
zigbee_port_conflict	Disables leftmost front USB port if installed

Document Control

Document version	v6
Product revision	rev 6
Generated	2026-07-24 05:11 UTC
Content hash	4fc88df8393b
Revision record	datasheets/ARG-ONE-V5-NVME/version-log.json (document_version = 6)

Full revision history for this datasheet is recorded in **version-log.json** — see the entry where *document_version* = 6.