



Argon ONE V5 M.2 Case for Raspberry Pi 5

SKU: ARG-ONE-V5 · Product Datasheet

Product Identity

Model No. / MPN	A24-005-AR-V5-NVME-S
UPC / EAN	5065019946164
Dimensions (cm)	10.00 x 4.00 x 16.50 cm
Weight (kg)	0.355
Category	ONE v5
HTS code	8473.30.5100

Compatibility

Raspberry Pi 5

Overview

Premium aluminium case for Raspberry Pi 5 with integrated M.2 NVMe PCIe storage support via the PCIe FPC connector. Features passive aluminium heatsink body, programmable power button, and repositioned full-size HDMI and USB-C ports. Compatible with Raspberry Pi 5 only.

Key Features

- Full-size HDMI ports (2x)
- PWM-controlled 30mm fan
- Programmable power button with safe shutdown
- 40-pin GPIO passthrough header
- All ports rear-facing for clean cable management

Specifications

active_cooling	30mm PWM blower fan, software-controlled
assembly_time	15–20 minutes
audio	3.5mm combo jack
audio_dac	HS100B - DAC Chip
audio_jack	1× 3.5mm combo (audio out + mic in), rear
audio_out	3.5mm audio out
case_material	Injected aluminum alloy and injected ABS plastic bottom
case_material_bottom	Injected ABS plastic
case_material_top	Injected aluminum alloy
compatible_board	Raspberry Pi 5 only
cooling_fan	30mm PWM blower fan, software-controlled
dac_chip	HS100B
dimensions	161 × 99 × 44 mm

ethernet	1× Gigabit
ethernet_ports	1× Gigabit (passthrough), rear
fan	Blower type 30mm PWM
fan_control	actively controlled by the Raspberry Pi OS
fan_type	Blower type
front_usb_2_0_ports	2
gpio	Full GPIO Access with Magnetic cover
gpio_header	40-pin passthrough with magnetic cover, top
hdmi	2x full-size HDMI
hdmi_conversion	Converted the micro HDMI of the RPi 5 to Regular HDMI
hdmi_output	2× full-size HDMI
hdmi_ports	2x Regular HDMI
m2_nvme_support	OPTIONS: SINGLE M.2 NVMe PCIe Expansion Board, DUAL M.2 NVMe PCIe Expansion Board
material	Aluminum alloy
mic_in	3.5mm mic in
nvme_heatsink	Argon THRML M.2 NVMe heatsink included
oled_module_size	1.8 inch OLED Module
passive_cooling	Aluminum alloy case body acts as heatsink
pcie_connector	U-shaped (included in box)
pcie_expansion	Raspberry Pi 5 native PCIe Gen2 ×1
pcie_standard	Raspberry Pi 5 native PCIe Gen2 ×1
power_button	Programmable, supports safe shutdown
power_input	1× USB-C, rear
power_supply_recommended	Argon PWR GaN 27W Power Delivery
product_name	Argon ONE V5 M.2 Case for Raspberry Pi 5
recommended_power_supply	Argon PWR GaN 27W Power Delivery
sku	ARG-ONE-V5
supported_m2_sizes	2230, 2242, 2260, 2280
thermal_interface	Silicon thermal pads (CPU, RP1, PMIC, RAM) + blue silicon thermal pads for M.2 drives
ups_option	Argon PWR UPS for Argon ONE V5 27W PD
ups_recommended	Argon PWR UPS for Argon ONE V5 27W PD
usb_2_0	2× Type-A, front-facing
usb_2_0_ports	2× Type-A, front-facing
usb_3_0	2× Type-A, rear-facing
usb_3_0_ports	2× Type-A, rear-facing
usb_hub_chip	FE1.1S - USB Hub Chip
zigbee_chip	CC2562P

Document Control

Document version	v8
Product revision	rev 8
Generated	2026-07-24 02:38 UTC
Content hash	511598a2acd2
Revision record	datasheets/ARG-ONE-V5/version-log.json (document_version = 8)

Full revision history for this datasheet is recorded in **version-log.json** — see the entry where *document_version* = 8.