



Argon ONE V5 Case for Raspberry Pi 5

SKU: ARG-ONE-V5 · Product Datasheet

Product Identity

Model No. / MPN	A24-005-AR-V5-NVME-S
UPC / EAN	5065019946164
Dimensions (cm)	10.00 x 4.00 x 16.50 cm
Weight (kg)	0.355
Category	ONE v5
HTS code	8473.30.5100

Compatibility

Raspberry Pi 5

Overview

Premium aluminium case for Raspberry Pi 5 with integrated M.2 NVMe PCIe storage support via the PCIe FPC connector. Features passive aluminium heatsink body, programmable power button, and repositioned full-size HDMI and USB-C ports. Compatible with Raspberry Pi 5 only.

Key Features

- Full-size HDMI ports (2x)
- PWM-controlled 30mm fan
- Programmable power button with safe shutdown
- 40-pin GPIO passthrough header
- All ports rear-facing for clean cable management
- Front 2x USB A
- Front 3.5mm Audio IN/OUT

Specifications

active_cooling	30mm PWM blower fan, software-controlled
audio	3.5mm combo jack — audio out + mic in (via HS100B DAC Chip)
audio_dac	HS100B - DAC Chip
audio_jack	1× 3.5mm combo (audio out + mic in), rear
audio_out	3.5mm audio out
case_material	Injected aluminum alloy top and injected ABS plastic bottom
case_material_bottom	Injected ABS plastic
case_material_top	Injected aluminum alloy
compatible_board	Raspberry Pi 5 only
cooling_fan	30mm PWM blower fan, software-controlled
cooling_type	Blower type 30mm PWM actively controlled by the Raspberry Pi OS
dac_chip	HS100B

dimensions	161 × 99 × 44 mm
ethernet	1× Gigabit (passthrough from Raspberry Pi 5)
ethernet_ports	1× Gigabit (passthrough), rear
fan	PWM 30mm Fan
fan_type	Blower type
front_usb_2_0_ports	2
gpio	40-pin passthrough header with magnetic cover
gpio_access	Full GPIO Access with Magnetic cover
gpio_header	40-pin passthrough with magnetic cover, top
hdmi	2x full-size HDMI
hdmi_conversion	Converted the micro HDMI of the RPi 5 to Regular HDMI
hdmi_location	Rear
hdmi_output	2× full-size HDMI (converted from Pi 5 micro-HDMI)
hdmi_ports	2 Regular HDMI
m2_nvme_expansion	OPTIONS: SINGLE M.2 NVMe PCIe Expansion Board, DUAL M.2 NVMe PCIe Expansion Board
material	Aluminum alloy
mic_in	3.5mm mic in
nvme_heatsink	Argon THRML M.2 NVMe heatsink included
oled_module	1.8 inch OLED Module
optional_ups	Argon PWR UPS for Argon ONE V5 27W PD
passive_cooling	Aluminum alloy case body acts as heatsink
pcie_connector	U-shaped (included in box)
pcie_expansion	Raspberry Pi 5 native PCIe Gen2 ×1
pcie_standard	Raspberry Pi 5 native PCIe Gen2 ×1
pi5_power_minimum	5V 3A (15W)
pi5_power_recommended	5V 5A (27W)
power_button	Programmable, supports safe shutdown
power_input	1× USB-C, rear
product_name	Argon ONE V5 M.2 Case for Raspberry Pi 5
recommended_power_supply	Argon PWR GaN 27W Power Delivery
recommended_ups	Argon PWR UPS for Argon ONE V5 27W PD
sku	ARG-ONE-V5
supported_m2_sizes	2230, 2242, 2260, 2280
thermal_interface	Silicon thermal pads (CPU, RP1, PMIC, RAM) + blue silicon thermal pads for M.2 drives
ups_option	Argon PWR UPS for Argon ONE V5 27W PD
usb_2_0	2× Type-A, front-facing (via FE1.1S USB Hub Chip)
usb_2_0_ports	2× Type-A, front-facing

usb_3_0	2× Type-A, rear-facing (passthrough from Pi 5)
usb_3_0_ports	2× Type-A, rear-facing
usb_hub_chip	FE1.1S - USB Hub Chip
zigbee_chip	CC2562P Zigbee Chip for Home Assistant

Document Control

Document version	v10
Product revision	rev 10
Generated	2026-07-28 03:47 UTC
Content hash	033f2ae4358b
Revision record	datasheets/ARG-ONE-V5/version-log.json (document_version = 10)

Full revision history for this datasheet is recorded in **version-log.json** — see the entry where *document_version* = 10.