



Argon ONE V5 M.2 Case for Raspberry Pi 5

SKU: ARG-ONE-V5 · Product Datasheet

Product Identity

Model No. / MPN	A24-005-AR-V5-NVME-S
UPC / EAN	5065019946164
Dimensions (cm)	10.00 x 4.00 x 16.50 cm
Weight (kg)	0.355
Category	ONE v5
HTS code	8473.30.5100

Compatibility

Raspberry Pi 5

Overview

Premium aluminium case for Raspberry Pi 5 with integrated M.2 NVMe PCIe storage support via the PCIe FPC connector. Features passive aluminium heatsink body, programmable power button, and repositioned full-size HDMI and USB-C ports. Compatible with Raspberry Pi 5 only.

Key Features

- Full-size HDMI ports (2x)
- PWM-controlled 30mm fan
- Programmable power button with safe shutdown
- 40-pin GPIO passthrough header
- All ports rear-facing for clean cable management
- 2 Front USB
- 1 Front 3.5 mm audio IN/OUT
- Blower-type 30mm PWM fan for superior airflow
- Integrated HS100B DAC for 3.5mm audio out and mic in
- Integrated FE1.1S USB hub chip (2 additional front USB 2.0 ports)
- Silicon thermal pads for CPU, RP1, PMIC, RAM, and M.2 drives
- Argon THRML M.2 NVMe heatsink included
- Supports M.2 NVMe sizes 2230, 2242, 2260, 2280
- Optional M.2 NVMe expansion boards (single, dual, quad configurations)
- Optional Argon Industria V5 OLED Module (1.8-inch display)
- Optional Argon Industria V5 ZigBee Module for Home Assistant
- USB 3.0 Type-A ports (2x rear-facing)
- USB 2.0 Type-A ports (2x front-facing)
- Gigabit Ethernet passthrough
- 3.5mm combo audio jack (audio out + mic in)
- Aluminum alloy top with ABS plastic bottom
- Magnetic GPIO cover included

Specifications

audio	3.5mm combo jack (audio out + mic in via HS100B DAC)
audio_chip	HS100B - DAC Chip

audio_ports	3.5mm audio out and mic in
case_bottom_material	ABS plastic
case_material	Injected aluminum alloy top and injected ABS plastic bottom
case_top_material	Injected aluminum alloy
dimensions	161 x 99 x 44mm
ethernet	1x Gigabit (passthrough)
fan	Blower type 30mm PWM
fan_control	Actively controlled by the Raspberry Pi OS
fan_type	30mm PWM blower
gpio	40-pin passthrough header
gpio_access	Full GPIO Access with Magnetic cover
hdmi	2x full-size HDMI
hdmi_ports	2 Regular HDMI
m2_cooling	Argon THRML M.2 NVMe heatsink
m2_nvme_options	SINGLE M.2 NVMe PCIe Expansion Board or DUAL M.2 NVMe PCIe Expansion Board
m2_sizes_supported	2230, 2242, 2260, 2280
material	Aluminum alloy
oled_module	1.8 inch OLED Module
pcie_standard	Gen2 x1 (native Raspberry Pi 5)
power_button	Programmable, supports safe shutdown
power_input	USB-C
recommended_power_supply	27W PD
screws_included	8 pcs Flat head 2.5x6 screws, 4 pcs Round head 2.5x8 screws
thermal_interface	Silicon thermal pads + Argon THRML M.2 heatsink
usb_2_0	2x Type-A (front-facing via FE1.1S hub chip)
usb_3_0	2x Type-A (rear-facing)
usb_front_ports	2 Front USB 2.0 ports
usb_hub_chip	FE1.1S - USB Hub Chip
zigbee_chip	CC2562P

Document Control

Document version	v7
Product revision	rev 7
Generated	2026-07-24 02:34 UTC
Content hash	87a79b414351
Revision record	datasheets/ARG-ONE-V5/version-log.json (document_version = 7)

Full revision history for this datasheet is recorded in **version-log.json** — see the entry where *document_version* = 7.