

Introduction to Neural Networks and Deep Learning

Recurrent Neural Networks

Andres Mendez-Vazquez

March 8, 2021

Outline

1

Introduction

- History
- State-Space Model
- Back to the RNN Equations
- Introducing the Cost Function
- Other Cost Functions

2

Training a Vanilla RNN Model

- The Final RNN Model
- Back-Propagation Through Time (BPTT)
- Deriving $\frac{\partial L(t)}{\partial V_{os}}$
- Vanishing and Exploding Gradients
 - The Analysis of the Exploding and Vanishing Gradient
- Signal Propagation
 - The Stability Frontier
- Truncated BPTT
- Initialization
 - Hidden State

3

Modern Recurrent Architectures

- Now, Long Short Term Memory (LSTM)
 - What about the Output?
- What about Gated Recurrent Units (GRU) units?

4

Deeper Architectures with RNN's

- Introduction
- Deep Architectures for Better Learning
- Deep Input-to-Hidden Function
- Deep Transition Architectures
- Conclusions

Outline

1

Introduction

History

- State-Space Model
- Back to the RNN Equations
- Introducing the Cost Function
- Other Cost Functions

2

Training a Vanilla RNN Model

- The Final RNN Model
- Back-Propagation Through Time (BPTT)
- Deriving $\frac{\partial L(t)}{\partial V_{os}}$
- Vanishing and Exploding Gradients
 - The Analysis of the Exploding and Vanishing Gradient
- Signal Propagation
 - The Stability Frontier
- Truncated BPTT
- Initialization
 - Hidden State

3

Modern Recurrent Architectures

- Now, Long Short Term Memory (LSTM)
 - What about the Output?
- What about Gated Recurrent Units (GRU) units?

4

Deeper Architectures with RNN's

- Introduction
- Deep Architectures for Better Learning
- Deep Input-to-Hidden Function
- Deep Transition Architectures
- Conclusions

In 1987 Robinson and Fallside [2]

At Cambridge University Engineering Department

- They proposed a new type of neural network based on Linear Control Theory

They took the work of Jacobs, 1974 on dynamic nets [1]

$$s_{t+1} = As_t + Bx_t$$

$$y_t = Cs_t$$

In 1987 Robinson and Fallside [2]

At Cambridge University Engineering Department

- They proposed a new type of neural network based on Linear Control Theory


They took the work of Jacobs, 1974 on dynamic nets [1]

$$s_{t+1} = As_t + Bx_t$$

$$y_t = Cs_t$$

Example of this unit

We have



Furthermore

Jordan Proposed a simple recurrent network

$$\mathbf{h}_t = \sigma_h (W_{sd}\mathbf{x}_t + U_{ss}\mathbf{h}_{t-1} + \mathbf{b}_h)$$

$$\mathbf{y}_t = \sigma_s (V_{os}\mathbf{h}_t + \mathbf{b}_o)$$

Furthermore

Jordan Proposed a simple recurrent network

$$\mathbf{h}_t = \sigma_h (W_{sd}\mathbf{x}_t + U_{ss}\mathbf{h}_{t-1} + \mathbf{b}_h)$$
$$\mathbf{y}_t = \sigma_s (V_{os}\mathbf{h}_t + \mathbf{b}_o)$$

Where

- 1 \mathbf{x}_t is an input of dimension d .
- 2 \mathbf{h}_t is a hidden state layer of dimension h .
- 3 \mathbf{y}_t is the output vector of dimension s .
- 4 W, U, V parameter matrices.
- 5 \mathbf{b}_h and \mathbf{b}_o bias for the linear part.
- 6 σ_h and σ_s are activation functions.

Furthermore

Jordan Proposed a simple recurrent network

$$\mathbf{h}_t = \sigma_h (W_{sd}\mathbf{x}_t + U_{ss}\mathbf{h}_{t-1} + \mathbf{b}_h)$$
$$\mathbf{y}_t = \sigma_s (V_{os}\mathbf{h}_t + \mathbf{b}_o)$$

Where

- ① \mathbf{x}_t is an input of dimension d .
- ② \mathbf{h}_t is a hidden state layer of dimension h .
- ③ \mathbf{y}_t is the output vector of dimension s .
- ④ W, U, V parameter matrices.
- ⑤ \mathbf{b}_h and \mathbf{b}_o bias for the linear part.
- ⑥ σ_h and σ_s are activation functions.

Furthermore

Jordan Proposed a simple recurrent network

$$\mathbf{h}_t = \sigma_h (W_{sd}\mathbf{x}_t + U_{ss}\mathbf{h}_{t-1} + \mathbf{b}_h)$$
$$\mathbf{y}_t = \sigma_s (V_{os}\mathbf{h}_t + \mathbf{b}_o)$$

Where

- 1 \mathbf{x}_t is an input of dimension d .
- 2 \mathbf{h}_t is a hidden state layer of dimension h .
- 3 \mathbf{y}_t is the output vector of dimension s .

4 W, U, V parameter matrices.

5 \mathbf{b}_h and \mathbf{b}_o bias for the linear part.

6 σ_h and σ_s are activation functions.

Furthermore

Jordan Proposed a simple recurrent network

$$\begin{aligned}\mathbf{h}_t &= \sigma_h (W_{sd}\mathbf{x}_t + U_{ss}\mathbf{h}_{t-1} + \mathbf{b}_h) \\ \mathbf{y}_t &= \sigma_s (V_{os}\mathbf{h}_t + \mathbf{b}_o)\end{aligned}$$

Where

- 1 \mathbf{x}_t is an input of dimension d .
- 2 \mathbf{h}_t is a hidden state layer of dimension h .
- 3 \mathbf{y}_t is the output vector of dimension s .
- 4 W, U, V parameter matrices.

• \mathbf{b}_h and \mathbf{b}_o bias for the linear part.

• σ_h and σ_s are activation functions.

Furthermore

Jordan Proposed a simple recurrent network

$$\begin{aligned}\mathbf{h}_t &= \sigma_h (W_{sd}\mathbf{x}_t + U_{ss}\mathbf{h}_{t-1} + \mathbf{b}_h) \\ \mathbf{y}_t &= \sigma_s (V_{os}\mathbf{h}_t + \mathbf{b}_o)\end{aligned}$$

Where

- 1 \mathbf{x}_t is an input of dimension d .
- 2 \mathbf{h}_t is a hidden state layer of dimension h .
- 3 \mathbf{y}_t is the output vector of dimension s .
- 4 W, U, V parameter matrices.
- 5 b_h and b_o bias for the linear part.

σ_h and σ_s are activation functions.

Furthermore

Jordan Proposed a simple recurrent network


$$\begin{aligned} \mathbf{h}_t &= \sigma_h (W_{sd}\mathbf{x}_t + U_{ss}\mathbf{h}_{t-1} + \mathbf{b}_h) \\ \mathbf{y}_t &= \sigma_s (V_{os}\mathbf{h}_t + \mathbf{b}_o) \end{aligned}$$

Where

- 1 \mathbf{x}_t is an input of dimension d .
- 2 \mathbf{h}_t is a hidden state layer of dimension h .
- 3 \mathbf{y}_t is the output vector of dimension s .
- 4 W, U, V parameter matrices.
- 5 b_h and b_o bias for the linear part.
- 6 σ_h and σ_s are activation functions.

Graphically

We have



What were they used for?

Robinson and Fallside

- As with Hidden Markov Models, they were proposed for Speech Coding


They proposed the following architecture

What were they used for?

Robinson and Fallside

- As with Hidden Markov Models, they were proposed for Speech Coding

They proposed the following architecture



Outline

1

Introduction

- History
- **State-Space Model**
- Back to the RNN Equations
- Introducing the Cost Function
- Other Cost Functions

2

Training a Vanilla RNN Model

- The Final RNN Model
- Back-Propagation Through Time (BPTT)
- Deriving $\frac{\partial L(t)}{\partial V_{os}}$
- Vanishing and Exploding Gradients
 - The Analysis of the Exploding and Vanishing Gradient
- Signal Propagation
 - The Stability Frontier
- Truncated BPTT
- Initialization
 - Hidden State

3

Modern Recurrent Architectures

- Now, Long Short Term Memory (LSTM)
 - What about the Output?
- What about Gated Recurrent Units (GRU) units?

4

Deeper Architectures with RNN's

- Introduction
- Deep Architectures for Better Learning
- Deep Input-to-Hidden Function
- Deep Transition Architectures
- Conclusions

Based on the State-Space Model

Basically, a linear system

- Based in a state-determined system model

Definition

- A mathematical description of the system in terms of a minimum set of variables $x_i(t)$, $i = 1, \dots, n$, together with knowledge of those variables at an initial time t_0 and the system inputs for time $t \geq t_0$, are sufficient to predict the future system state and outputs for all time $t > t_0$.

Based on the State-Space Model

Basically, a linear system


- Based in a state-determined system model

Definition

- A mathematical description of the system in terms of a minimum set of variables $x_i(t)$, $i = 1, \dots, n$, together with knowledge of those variables at an initial time t_0 and the system inputs for time $t \geq t_0$, are sufficient to predict the future system state and outputs for all time $t > t_0$.

Therefore

We have a system as a block



This can be expressed as a state equations

$$\dot{s}_1 = f_1(x, s, t)$$


$$\dot{s}_2 = f_2(x, s, t)$$

$$\dots = \dots$$

$$\dot{s}_n = f_n(x, s, t)$$

Therefore

We have a system as a block



This can be expressed as a state equations

$$\dot{s}_1 = f_1(\mathbf{x}, \mathbf{s}, t)$$

$$\dot{s}_2 = f_2(\mathbf{x}, \mathbf{s}, t)$$

$$\dots = \dots$$

$$\dot{s}_n = f_n(\mathbf{x}, \mathbf{s}, t)$$

Using Vector Notation

Assuming that we have a linear system and time invariant

- Time-Invariant $\bowtie x(t + \delta)$ directly equates $y(t + \delta)$, for example

$$\alpha x(t + \delta) + \beta = y(t + \delta)$$

Therefore, using this idea

$$\dot{s}_i = a_{i1}x_1(t) + \dots + a_{id}x_d(t) + b_{i1}s_1(t) + \dots + b_{in}s_n(t)$$

Or in Matrix form

$$\dot{y}(t) = Ax(t) + Bs(t)$$

Using Vector Notation

Assuming that we have a linear system and time invariant

- Time-Invariant $\bowtie x(t + \delta)$ directly equates $y(t + \delta)$, for example

$$\alpha x(t + \delta) + \beta = y(t + \delta)$$

Therefore, using this idea

$$\dot{s}_i = a_{i1}x_1(t) + \dots + a_{id}x_d(t) + b_{i1}s_1(t) + \dots + b_{in}s_n(t)$$

Or in Matrix form

$$\dot{y}(t) = Ax(t) + Bs(t)$$

Using Vector Notation

Assuming that we have a linear system and time invariant

- Time-Invariant $\bowtie x(t + \delta)$ directly equates $y(t + \delta)$, for example

$$\alpha x(t + \delta) + \beta = y(t + \delta)$$

Therefore, using this idea

$$\dot{s}_i = a_{i1}x_1(t) + \dots + a_{id}x_d(t) + b_{i1}s_1(t) + \dots + b_{in}s_n(t)$$

Or in Matrix form

$$\mathbf{y}(t) = \mathbf{A}\mathbf{x}(t) + \mathbf{B}\mathbf{s}(t)$$

Then, the discretized version

We introduce an update for the state part

$$\begin{aligned} \mathbf{y}(t) &= \mathbf{A}\mathbf{x}(t) + \mathbf{B}\mathbf{s}(t) \\ \dot{\mathbf{s}}(t) &= \mathbf{C}\mathbf{s}(t) \end{aligned}$$

On our discrete step equations

$$\begin{aligned} \mathbf{y}(t) &= \mathbf{A}\mathbf{x}(t) + \mathbf{B}\mathbf{s}(t) \\ \mathbf{s}(t+1) &= \mathbf{C}\mathbf{s}(t) \end{aligned}$$

Then, the discretized version

We introduce an update for the state part

$$\begin{aligned}\mathbf{y}(t) &= \mathbf{A}\mathbf{x}(t) + \mathbf{B}\mathbf{s}(t) \\ \dot{\mathbf{s}}(t) &= \mathbf{C}\mathbf{s}(t)\end{aligned}$$

Or our discrete step equations

$$\begin{aligned}\mathbf{y}(t) &= \mathbf{A}\mathbf{x}(t) + \mathbf{B}\mathbf{s}(t) \\ \mathbf{s}(t+1) &= \mathbf{C}\mathbf{s}(t)\end{aligned}$$

Outline

1

Introduction

- History
- State-Space Model
- **Back to the RNN Equations**
- Introducing the Cost Function
- Other Cost Functions

2

Training a Vanilla RNN Model

- The Final RNN Model
- Back-Propagation Through Time (BPTT)
- Deriving $\frac{\partial L(t)}{\partial V_{os}}$
- Vanishing and Exploding Gradients
 - The Analysis of the Exploding and Vanishing Gradient
- Signal Propagation
 - The Stability Frontier
- Truncated BPTT
- Initialization
 - Hidden State

3

Modern Recurrent Architectures

- Now, Long Short Term Memory (LSTM)
 - What about the Output?
- What about Gated Recurrent Units (GRU) units?

4

Deeper Architectures with RNN's

- Introduction
- Deep Architectures for Better Learning
- Deep Input-to-Hidden Function
- Deep Transition Architectures
- Conclusions

The Elman Network

In Elman's Equations

$$\mathbf{h}_t = \sigma_h (W_{sd}\mathbf{x}_t + U_{ss}\mathbf{h}_{t-1} + \mathbf{b}_h)$$

$$\mathbf{y}_t = \sigma_y (V_{os}\mathbf{h}_t + \mathbf{b}_y)$$

We noticed something different from the linear recurrent system

- The use of activation functions to introduce the concept of non-linearity

The Elman Network

In Elman's Equations

$$\mathbf{h}_t = \sigma_h (W_{sd}\mathbf{x}_t + U_{ss}\mathbf{h}_{t-1} + \mathbf{b}_h)$$

$$\mathbf{y}_t = \sigma_y (V_{os}\mathbf{h}_t + \mathbf{b}_y)$$

We noticed something different from the linear recurrent system

- The use of activation functions to introduce the concept of non-linearity

Explanation

We have the following

- 1 The input \mathbf{x}_t is coded by W_{sd}

$$W_{sd}\mathbf{x}_t$$

- 2 An state is generated by using the codified version of the input plus a previous state \mathbf{h}_{t-1}

$$\mathbf{h}_t = \sigma_h(W_{sd}\mathbf{x}_t + U_{ss}\mathbf{h}_{t-1} + \mathbf{b}_h)$$

- 3 The output is generated using the new state \mathbf{h}_t

$$\mathbf{y}_t = \sigma_y(V_{os}\mathbf{h}_t + \mathbf{b}_y)$$

Explanation

We have the following

- 1 The input \mathbf{x}_t is coded by W_{sd}

$$W_{sd}\mathbf{x}_t$$

- 2 An state is generated by using the codified version of the input plus a previous state \mathbf{h}_{t-1}

$$\mathbf{h}_t = \sigma_h (W_{sd}\mathbf{x}_t + U_{ss}\mathbf{h}_{t-1} + \mathbf{b}_h)$$

- 3 The output is generated using the new state \mathbf{h}_t

$$\mathbf{y}_t = \sigma_y (V_{os}\mathbf{h}_t + \mathbf{b}_y)$$

Explanation

We have the following

- 1 The input \mathbf{x}_t is coded by W_{sd}

$$W_{sd}\mathbf{x}_t$$

- 2 An state is generated by using the codified version of the input plus a previous state \mathbf{h}_{t-1}

$$\mathbf{h}_t = \sigma_h (W_{sd}\mathbf{x}_t + U_{ss}\mathbf{h}_{t-1} + \mathbf{b}_h)$$

- 3 The output is generated using the new state \mathbf{h}_t

$$\mathbf{y}_t = \sigma_y (V_{os}\mathbf{h}_t + \mathbf{b}_y)$$

Outline

1

Introduction

- History
- State-Space Model
- Back to the RNN Equations
- **Introducing the Cost Function**
- Other Cost Functions

2

Training a Vanilla RNN Model

- The Final RNN Model
- Back-Propagation Through Time (BPTT)
- Deriving $\frac{\partial L(t)}{\partial V_{os}}$
- Vanishing and Exploding Gradients
 - The Analysis of the Exploding and Vanishing Gradient
- Signal Propagation
 - The Stability Frontier
- Truncated BPTT
- Initialization
 - Hidden State

3

Modern Recurrent Architectures

- Now, Long Short Term Memory (LSTM)
 - What about the Output?
- What about Gated Recurrent Units (GRU) units?

4

Deeper Architectures with RNN's

- Introduction
- Deep Architectures for Better Learning
- Deep Input-to-Hidden Function
- Deep Transition Architectures
- Conclusions

We need to introduce the concept of cost function

Which as always

- It needs to comply with two properties

The cost function L must be able to be written as an average

$$L = \frac{1}{N} \sum_{x \in \mathcal{X}} C_x$$

over the cost individual cost functions C_x

This allow to apply different optimization techniques as

- Minibatch
- Stochastic Gradient Descent
- etc

We need to introduce the concept of cost function

Which as always

- It needs to comply with two properties

The cost function L must be able to be written as an average

$$L = \frac{1}{N} \sum_{x \in \mathcal{X}} C_x$$

over the cost individual cost functions C_x

This allow to apply different optimization techniques as

- Minbatch
- Stochastic Gradient Descent
- etc

We need to introduce the concept of cost function

Which as always

- It needs to comply with two properties

The cost function L must be able to be written as an average

$$L = \frac{1}{N} \sum_{x \in \mathcal{X}} C_x$$

over the cost individual cost functions C_x

This allow to apply different optimization techniques as

- Minbatch
- Stochastic Gradient Descent
- etc

Furthermore

Non dependency

- The cost function L must not be dependent on any activation values of a neural network besides the output values.

If we cannot assure this

- If not Backpropagation becomes too unstable or too complex to solve. For example

$$L = \frac{1}{N} \sum_{t=0}^N [y_t + h_t - z_t]^2$$

- This gives two entry points to the network.

Furthermore

Non dependency

- The cost function L must not be dependent on any activation values of a neural network besides the output values.

If we cannot assure this

- If not Backpropagation becomes too unstable or too complex to solve. For example

$$L = \frac{1}{N} \sum_{t=0}^N [y_t + h_t - z_t]^2$$

- ▶ This gives two entry points to the network.

A List of Cost Functions

The Average Quadratic Cost

$$L = \frac{1}{N} \sum_{t=0}^N [y_t - z_t]^2$$

- Where y_t is the output of the network and z_t is the ground truth of the output.

Here, we are interpolating functions


A List of Cost Functions

The Average Quadratic Cost

$$L = \frac{1}{N} \sum_{t=0}^N [y_t - z_t]^2$$

- Where y_t is the output of the network and z_t is the ground truth of the output.

Here, we are interpolating functions



Cross-Entropy cost

First, the Loss Function

$$L = - \sum_{i=1}^C z_i \log(y_i)$$

- Where y_i is the output and z_i is the ground truth for the class estimation.

Why log-likelihood

- We can imagine a sequence of class probabilities y_1, y_2, \dots, y_m and the likelihood of the data and the model

$$P[\text{data}|\text{model}] = y_1^{k_1} y_2^{k_2} \dots y_m^{k_n}$$

Cross-Entropy cost

First, the Loss Function

$$L = - \sum_{i=1}^C z_i \log(y_i)$$

- Where y_i is the output and z_i is the ground truth for the class estimation.

Why $y_i \log(z_i)$?

- We can imagine a sequence of class probabilities y_1, y_2, \dots, y_m and the likelihood of the data and the model

$$P[data|model] = y_1^{k_1} y_2^{k_2} \dots y_m^{k_n}$$

Then

Taking the logarithm and multiplying by -1

$$-\log P[\text{data}|\text{model}] = -\sum_{i=1}^C k_i \log y_i$$

Then, dividing by the total number of samples

$$-\frac{1}{N} \log P[\text{data}|\text{model}] = -\sum_{i=1}^C \frac{k_i}{N} \log y_i = -\sum_{i=1}^C z_i \log y_i$$

Then

Taking the logarithm and multiplying by -1

$$-\log P[data|model] = -\sum_{i=1}^C k_i \log y_i$$

Then, dividing by the total number of samples

$$-\frac{1}{N} \log P[data|model] = -\sum_{i=1}^C \frac{k_i}{N} \log y_i = -\sum_{i=1}^C z_i \log y_i$$

Then

In information theory, The Kraft–McMillan theorem

- It establishes that any directly decodable coding scheme for coding a message to identify one value $x_i \in \{x_1, x_2, \dots, x_n\}$

It can be seen as representing an implicit probability distribution over the values x_i

$$q(x_i) = \left(\frac{1}{2}\right)^{l_i}$$

- Where l_i is the length of the code for x_i

Then

In information theory, The Kraft–McMillan theorem

- It establishes that any directly decodable coding scheme for coding a message to identify one value $x_i \in \{x_1, x_2, \dots, x_n\}$

It can be seen as representing an implicit probability distribution over $\{x_1, x_2, \dots, x_n\}$

$$q(x_i) = \left(\frac{1}{2}\right)^{l_i}$$

- Where l_i is the length of the code for x_i

We have that

- Cross entropy can be interpreted as the expected message-length per datum when a wrong distribution q is assumed while the data actually follows a distribution p .

The expected message-length under the true distribution p is

$$\begin{aligned} E_p[l] &= -E_p \left[\frac{\ln q(x)}{\ln 2} \right] \\ &= -E_p [\log_2 q(x)] \\ &= -\sum_{x_i} p(x_i) \log_2 q(x) \\ &= H(p, q) \end{aligned}$$

We have that

- Cross entropy can be interpreted as the expected message-length per datum when a wrong distribution q is assumed while the data actually follows a distribution p .

The expected message-length under the true distribution p is

$$\begin{aligned} E_p[l] &= -E_p \left[\frac{\ln q(x)}{\ln 2} \right] \\ &= -E_p [\log_2 q(x)] \\ &= - \sum_{x_i} p(x_i) \log_2 q(x) \\ &= H(p, q) \end{aligned}$$

Special Case

A special case is the binary class problem, $C = 2$

- Based on the fact that $z_1 + z_2 = 1$ and $y_1 + y_2 = 1$

$$L = - \sum_{i=1}^2 z_i \log(y_i) = -z_1 \log(y_1) - (1 - z_1) \log(1 - y_1)$$

A problem of this

- It could be possible to have a $y_1 = 0$

Special Case

A special case is the binary class problem, $C = 2$

- Based on the fact that $z_1 + z_2 = 1$ and $y_1 + y_2 = 1$


$$L = - \sum_{i=1}^2 z_i \log(y_i) = -z_1 \log(y_1) - (1 - z_1) \log(1 - y_1)$$

A problem of this

- It could be possible to have a $y_1 = 0$

Dealing with this problem

We can use an activation function in front of it



Another Interpretation

The Loss can be expressed as

$$L = \begin{cases} -\log(f(y_1)) & \text{if } z_1 = 1 \\ -\log(1 - f(y_1)) & \text{if } z_1 = 0 \end{cases}$$

Where

- It means that the class $C_1 = C_i$ is positive for this sample.

Another Interpretation

The Loss can be expressed as

$$L = \begin{cases} -\log(f(y_1)) & \text{if } z_1 = 1 \\ -\log(1 - f(y_1)) & \text{if } z_1 = 0 \end{cases}$$

Where $z_1 = 1$

- It means that the class $C_1 = C_i$ is positive for this sample.

The Gradient of the Binary Cross Entropy

We make a derivative with respect to y_i

$$\frac{\partial L}{\partial y_1} = z_1 (f(y_1) - 1) + (1 - z_1) f(y_1)$$

In the case of the Multiclass Problem

We use two things, a softmax

$$f(y_i) = \frac{\exp\{y_i\}}{\sum_{j=1}^C \exp\{y_j\}}$$

As to the multiclass for the Linear Models

- The labels are one-hot, so only the positive class C_p keeps its term in the loss.

Therefore:

- There is only one element of the Target vector z that is not zero, $z_i = z_p$.

In the case of the Multiclass Problem

We use two things, a softmax

$$f(y_i) = \frac{\exp\{y_i\}}{\sum_{j=1}^C \exp\{y_j\}}$$

As in the multiclass for the Linear Models

- The labels are one-hot, so only the positive class C_p keeps its term in the loss.

Therefore:

- There is only one element of the Target vector z that is not zero,
 $z_i = z_p$.

In the case of the Multiclass Problem

We use two things, a softmax

$$f(y_i) = \frac{\exp\{y_i\}}{\sum_{j=1}^C \exp\{y_j\}}$$

As in the multiclass for the Linear Models

- The labels are one-hot, so only the positive class C_p keeps its term in the loss.

Therefore

- There is only one element of the Target vector z that is not zero, $z_i = z_p$.

We can then simplify

The cost function becomes

$$L = -\sum_{i=1}^C z_i \log(f(y_i)) = -\log\left(\frac{\exp\{y_p\}}{\sum_{j=1}^C \exp\{y_p\}}\right)$$

Outline

1

Introduction

- History
- State-Space Model
- Back to the RNN Equations
- Introducing the Cost Function
- **Other Cost Functions**

2

Training a Vanilla RNN Model

- The Final RNN Model
- Back-Propagation Through Time (BPTT)
- Deriving $\frac{\partial L(t)}{\partial V_{os}}$
- Vanishing and Exploding Gradients
 - The Analysis of the Exploding and Vanishing Gradient
- Signal Propagation
 - The Stability Frontier
- Truncated BPTT
- Initialization
 - Hidden State

3

Modern Recurrent Architectures

- Now, Long Short Term Memory (LSTM)
 - What about the Output?
- What about Gated Recurrent Units (GRU) units?

4

Deeper Architectures with RNN's

- Introduction
- Deep Architectures for Better Learning
- Deep Input-to-Hidden Function
- Deep Transition Architectures
- Conclusions

Other Cost Functions

Exponential Cost with hyper-parameter τ

$$L = \tau \exp \left[\frac{1}{\tau} \sum_{i=1}^N (y_i - z_i)^2 \right]$$

Hellinger Distance

$$L = \frac{1}{2} \sum_{i=1}^N (\sqrt{y_i} - \sqrt{z_i})^2$$

- Here the values need to be at the interval $[0, 1]$.

Other Cost Functions

Exponential Cost with hyper-parameter τ

$$L = \tau \exp \left[\frac{1}{\tau} \sum_{i=1}^N (y_i - z_i)^2 \right]$$

Hellinger Distance

$$L = \frac{1}{2} \sum_{i=1}^N (\sqrt{y_i} - \sqrt{z_i})^2$$

- Here the values need to be at the interval $[0, 1]$.

Other Cost Functions

Given Kullback-Leibler Divergence

$$D_{KL}(P \parallel Q) = \sum_i P(i) \ln \frac{P(i)}{Q(i)}$$

The Final Cost Function

$$L = \sum_j \hat{y}_j \log \frac{\hat{y}_j}{y_j^{pred}}$$

Other Cost Functions

Given Kullback-Leibler Divergence

$$D_{KL}(P \parallel Q) = \sum_i P(i) \ln \frac{P(i)}{Q(i)}$$

The Final Cost function

$$L = \sum_j \hat{y}_j \log \frac{\hat{y}_j}{y_j^{pred}}$$

Outline

1

Introduction

- History
- State-Space Model
- Back to the RNN Equations
- Introducing the Cost Function
- Other Cost Functions

2

Training a Vanilla RNN Model

- **The Final RNN Model**
- Back-Propagation Through Time (BPTT)
- Deriving $\frac{\partial L(t)}{\partial V_{os}}$
- Vanishing and Exploding Gradients
 - The Analysis of the Exploding and Vanishing Gradient
- Signal Propagation
 - The Stability Frontier
- Truncated BPTT
- Initialization
 - Hidden State

3

Modern Recurrent Architectures

- Now, Long Short Term Memory (LSTM)
 - What about the Output?
- What about Gated Recurrent Units (GRU) units?

4

Deeper Architectures with RNN's

- Introduction
- Deep Architectures for Better Learning
- Deep Input-to-Hidden Function
- Deep Transition Architectures
- Conclusions

We have the following

Architecture with Quadratic Error

$$\mathbf{h}_t = \sigma_h (W_{sd}\mathbf{x}_t + U_{ss}\mathbf{h}_{t-1} + \mathbf{b}_h)$$

$$\mathbf{y}_t = \sigma_y (V_{os}\mathbf{h}_t + \mathbf{b}_y)$$

$$L = \frac{1}{2} \sum_{t=0}^N [y_t - z_t]^2$$

Something Notable

- How do we train something with a recurrence forcing a dependence over time?

We have the following

Architecture with Quadratic Error

$$\mathbf{h}_t = \sigma_h (W_{sd}\mathbf{x}_t + U_{ss}\mathbf{h}_{t-1} + \mathbf{b}_h)$$

$$\mathbf{y}_t = \sigma_y (V_{os}\mathbf{h}_t + \mathbf{b}_y)$$

$$L = \frac{1}{2} \sum_{t=0}^N [y_t - z_t]^2$$

Something Notable

- How do we train something with a recurrence forcing a dependence over time?

Outline

1

Introduction

- History
- State-Space Model
- Back to the RNN Equations
- Introducing the Cost Function
- Other Cost Functions

2

Training a Vanilla RNN Model

- The Final RNN Model
- **Back-Propagation Through Time (BPTT)**
- Deriving $\frac{\partial L(t)}{\partial V_{os}}$
- Vanishing and Exploding Gradients
 - The Analysis of the Exploding and Vanishing Gradient
- Signal Propagation
 - The Stability Frontier
- Truncated BPTT
- Initialization
 - Hidden State

3

Modern Recurrent Architectures

- Now, Long Short Term Memory (LSTM)
 - What about the Output?
- What about Gated Recurrent Units (GRU) units?

4

Deeper Architectures with RNN's

- Introduction
- Deep Architectures for Better Learning
- Deep Input-to-Hidden Function
- Deep Transition Architectures
- Conclusions

Now, given the dependency over time

We can use the classic unfolding of the network [3, 4] by assuming

- W , U , V , b_h and b_o do not change under the unfolding

Unfolding?

- Assume that there are not bias correcting terms, only, W , U and V .

Now, given the dependency over time

We can use the classic unfolding of the network [3, 4] by assuming

- W , U , V , b_h and b_o do not change under the unfolding

Unfolding?

- Assume that there are not bias correcting terms, only, W , U and V .

Then

Given an observation sequence $\mathbf{x} = \{x_1, x_2, \dots, x_T\}$

- where $x_i \in \mathbb{R}$, and their corresponding label $y = \{y_1, y_2, \dots, y_T\}$

We remove the bias to simplify our derivations.

$$h_t = \sigma_h (W_{sd} \mathbf{x}_t + U_{ss} h_{t-1})$$

$$y_t = \sigma_y (V_{os} h_t)$$

$$L = \frac{1}{2} \sum_{t=0}^T [z_t - y_t]^2$$

Then

Given an observation sequence $\mathbf{x} = \{x_1, x_2, \dots, x_T\}$

- where $x_i \in \mathbb{R}$, and their corresponding label $y = \{y_1, y_2, \dots, y_T\}$

We remove the bias to simplify our derivations


$$\mathbf{h}_t = \sigma_h (W_{sd}\mathbf{x}_t + U_{ss}\mathbf{h}_{t-1})$$

$$y_t = \sigma_y (V_{os}\mathbf{h}_t)$$

$$L = \frac{1}{2} \sum_{t=0}^T [z_t - y_t]^2$$

Unfolding

We can then see the unfolding of the recurrence



Outline

1

Introduction

- History
- State-Space Model
- Back to the RNN Equations
- Introducing the Cost Function
- Other Cost Functions

2

Training a Vanilla RNN Model

- The Final RNN Model
- Back-Propagation Through Time (BPTT)
- Deriving $\frac{\partial L(t)}{\partial V_{os}}$
 - Vanishing and Exploding Gradients
 - The Analysis of the Exploding and Vanishing Gradient
 - Signal Propagation
 - The Stability Frontier
 - Truncated BPTT
 - Initialization
 - Hidden State

3

Modern Recurrent Architectures

- Now, Long Short Term Memory (LSTM)
 - What about the Output?
- What about Gated Recurrent Units (GRU) units?

4

Deeper Architectures with RNN's

- Introduction
- Deep Architectures for Better Learning
- Deep Input-to-Hidden Function
- Deep Transition Architectures
- Conclusions

This allows

To simplify the backpropagation process

$$\begin{aligned}\frac{\partial L}{\partial V_{os}} &= \frac{1}{2} \sum_{t=0}^T \frac{\partial L}{\partial y_t} \times \frac{\partial y_t}{\partial V_{os}} \\ &= \frac{1}{2} \sum_{t=0}^T \frac{\partial L}{\partial y_t} \times \frac{\partial y_t}{\partial net_o} \times \frac{\partial net_o}{\partial V_{os}} \\ &= - \sum_{t=0}^T [z_t - y_t] \times \frac{\partial y_t}{\partial net_o} \times \frac{\partial net_o}{\partial V_{os}}\end{aligned}$$

• Where $net_o^t = V_{os} h_t$

This allows

To simplify the backpropagation process

$$\begin{aligned}\frac{\partial L}{\partial V_{os}} &= \frac{1}{2} \sum_{t=0}^T \frac{\partial L}{\partial y_t} \times \frac{\partial y_t}{\partial V_{os}} \\ &= \frac{1}{2} \sum_{t=0}^T \frac{\partial L}{\partial y_t} \times \frac{\partial y_t}{\partial net_o} \times \frac{\partial net_o}{\partial V_{os}} \\ &= - \sum_{t=0}^T [z_t - y_t] \times \frac{\partial y_t}{\partial net_o} \times \frac{\partial net_o}{\partial V_{os}}\end{aligned}$$

• Where $net_o^t = V_{os} h_t$

This allows

To simplify the backpropagation process

$$\begin{aligned}\frac{\partial L}{\partial V_{os}} &= \frac{1}{2} \sum_{t=0}^T \frac{\partial L}{\partial y_t} \times \frac{\partial y_t}{\partial V_{os}} \\ &= \frac{1}{2} \sum_{t=0}^T \frac{\partial L}{\partial y_t} \times \frac{\partial y_t}{\partial net_o} \times \frac{\partial net_o}{\partial V_{os}} \\ &= - \sum_{t=0}^T [z_t - y_t] \times \frac{\partial y_t}{\partial net_o} \times \frac{\partial net_o}{\partial V_{os}}\end{aligned}$$

- Where $net_o^t = V_{os} h_t$

Now, we have

We have that

$$\frac{\partial y_t}{\partial net_o} = \begin{pmatrix} \frac{\partial y_{t1}}{\partial net_{o1}} & \frac{\partial y_{t2}}{\partial net_{o1}} & \dots & \frac{\partial y_{to}}{\partial net_{o1}} \\ \frac{\partial y_{t1}}{\partial net_{o2}} & \frac{\partial y_{t2}}{\partial net_{o2}} & \dots & \frac{\partial y_{to}}{\partial net_{o2}} \\ \vdots & \vdots & \ddots & \vdots \\ \frac{\partial y_{t1}}{\partial net_{oo}} & \frac{\partial y_{t2}}{\partial net_{oo}} & \dots & \frac{\partial y_{to}}{\partial net_{oo}} \end{pmatrix}$$

Simplify!!!

Now, we have that if $i = j$

$$\frac{\partial y_{ti}}{\partial \text{net}_{oi}} = \sigma'(\text{net}_{oi})$$

And for the rest, we have

$$\frac{\partial y_{ti}}{\partial \text{net}_{oi}} = 0$$

Simplify!!!

Now, we have that if $i = j$

$$\frac{\partial y_{ti}}{\partial \text{net}_{oi}} = \sigma'(\text{net}_{oi})$$

And for the rest, we have $i \neq j$

$$\frac{\partial y_{ti}}{\partial \text{net}_{oi}} = 0$$

Finally

We have that

$$\frac{\partial y_t}{\partial net_o} = \begin{pmatrix} \sigma'_o(net_{o1}) & 0 & \cdots & 0 \\ 0 & \sigma'_o(net_{o2}) & \cdots & 0 \\ \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \cdots & \sigma'_o(net_{oo}) \end{pmatrix} = A$$

Now, $\frac{\partial net_o}{\partial V_{os}}$

First we have a component i

$$net_{oi} = \sum_{j=1}^s V_{ij} h_j$$

What happen when we derive with respect to the matrix?

$$\frac{\partial net_o}{\partial V_{os}} = \begin{bmatrix} \frac{\partial net_o}{\partial V_{11}} & \frac{\partial net_o}{\partial V_{12}} & \dots & \frac{\partial net_o}{\partial V_{1s}} \\ \frac{\partial net_o}{\partial V_{21}} & \frac{\partial net_o}{\partial V_{22}} & \dots & \frac{\partial net_o}{\partial V_{2s}} \\ \vdots & \vdots & \ddots & \vdots \\ \frac{\partial net_o}{\partial V_{o1}} & \frac{\partial net_o}{\partial V_{o2}} & \dots & \frac{\partial net_o}{\partial V_{os}} \end{bmatrix}$$

Actually

- A Tensor with three dimensions...

Now, $\frac{\partial net_o}{\partial V_{os}}$

First we have a component i

$$net_{oi} = \sum_{j=1}^s V_{ij} h_j$$

What happen when we derive with respect to the matrix?

$$\frac{\partial net_o}{\partial V_{os}} = \begin{bmatrix} \frac{\partial net_o}{\partial V_{11}} & \frac{\partial net_o}{\partial V_{12}} & \dots & \frac{\partial net_o}{\partial V_{1s}} \\ \frac{\partial net_o}{\partial V_{21}} & \frac{\partial net_o}{\partial V_{22}} & \dots & \frac{\partial net_o}{\partial V_{2s}} \\ \vdots & \vdots & \ddots & \vdots \\ \frac{\partial net_o}{\partial V_{o1}} & \frac{\partial net_o}{\partial V_{o2}} & \dots & \frac{\partial net_o}{\partial V_{os}} \end{bmatrix}$$

Actually

- A Tensor with three dimensions...

Now, $\frac{\partial net_o}{\partial V_{os}}$

First we have a component i

$$net_{oi} = \sum_{j=1}^s V_{ij} h_j$$

What happen when we derive with respect to the matrix?

$$\frac{\partial net_o}{\partial V_{os}} = \begin{bmatrix} \frac{\partial net_o}{\partial V_{11}} & \frac{\partial net_o}{\partial V_{12}} & \dots & \frac{\partial net_o}{\partial V_{1s}} \\ \frac{\partial net_o}{\partial V_{21}} & \frac{\partial net_o}{\partial V_{22}} & \dots & \frac{\partial net_o}{\partial V_{2s}} \\ \vdots & \vdots & \ddots & \vdots \\ \frac{\partial net_o}{\partial V_{o1}} & \frac{\partial net_o}{\partial V_{o2}} & \dots & \frac{\partial net_o}{\partial V_{os}} \end{bmatrix}$$

Actually

- A Tensor with three dimensions...

But something quite nice

Each of the components of net_o

- It has the previous structure

$$net_{oi} = \sum_{k=1}^s V_{ik} h_k$$

Then if the V_{jk} does not intervene on it

$$\frac{\partial net_{oi}}{\partial V_{jk}} = 0$$

Additionally if it intervenes

$$\frac{\partial net_{oi}}{\partial V_{jk}} = h_k$$

But something quite nice

Each of the components of net_o

- It has the previous structure

$$net_{oi} = \sum_{k=1}^s V_{ik} h_k$$

Then if the V_{jk} does not intervene on it

$$\frac{\partial net_{oi}}{\partial V_{jk}} = 0$$

Additionally if it intervenes

$$\frac{\partial net_{oi}}{\partial V_{jk}} = h_k$$

But something quite nice

Each of the components of net_o

- It has the previous structure

$$net_{oi} = \sum_{k=1}^s V_{ik} h_k$$

Then if the V_{jk} does not intervene on it

$$\frac{\partial net_{oi}}{\partial V_{jk}} = 0$$

Additionally if it intervenes

$$\frac{\partial net_{oi}}{\partial V_{jk}} = h_k$$

Therefore

It is possible to collapse the tensor into a 2D Matrix

- Given that the other information is redundant, ad we can rewrite the tensor as

$$F_{ijk} = \frac{\partial net_{oi}}{\partial V_{jk}}$$

Then we have that

$$F_{ijk} = G_{ij} \Leftarrow \text{Better Storage!!!}$$

Therefore

It is possible to collapse the tensor into a 2D Matrix

- Given that the other information is redundant, ad we can rewrite the tensor as

$$F_{ijk} = \frac{\partial net_{oi}}{\partial V_{jk}}$$

Then, we have that

$$F_{ijk} = G_{ij} \Leftarrow \text{Better Storage!!!}$$

Therefore, given that a matrix is a tensor also

We have that two tensors, $net^{o \times o}$ and $F^{o \times s \times o}$ [5]

- We will use the contracted product of two tensors which is a generalization of the tensor-vector and tensor-matrix multiplications

Definition

- Given two tensors $A^{o \times o}$ and $B^{o \times s \times o}$

$$\langle A, B \rangle (k, j) = \sum_{i=1}^o A_{i,k} G_{i,j} = A_{i,i} G_{i,j} = \sigma'(net_{oi}) h_j$$

Therefore, given that a matrix is a tensor also

We have that two tensors, $net^{o \times o}$ and $F^{o \times s \times o}$ [5]

- We will use the contracted product of two tensors which is a generalization of the tensor-vector and tensor-matrix multiplications

Definition

- Given two tensors $A^{o \times o}$ and $B^{o \times s \times o}$

$$\langle A, B \rangle (k, j) = \sum_{i=1}^o A_{i,k} G_{i,j} = A_{i,i} G_{i,j} = \sigma' (net_{oi}) h_j$$

Now, the term $\frac{\partial L}{\partial U_{ss}}$

Assuming our change in time step $t \rightarrow t + 1$ and given

$$\mathbf{h}_t = \sigma_h(W_{sd}\mathbf{x}_t + U_{ss}\mathbf{h}_{t-1})$$

Therefore we have

$$\frac{\partial L(t+1)}{\partial U_{ss}} = \frac{\partial L(t+1)}{\partial y_{t+1}} \times \frac{\partial y_{t+1}}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial U_{ss}}$$

Therefore

- We can think on this as a Markovian Backpropagation

Now, the term $\frac{\partial L}{\partial U_{ss}}$

Assuming our change in time step $t \rightarrow t + 1$ and given

$$\mathbf{h}_t = \sigma_h(W_{sd}\mathbf{x}_t + U_{ss}\mathbf{h}_{t-1})$$

Therefore we have

$$\frac{\partial L(t+1)}{\partial U_{ss}} = \frac{\partial L(t+1)}{\partial y_{t+1}} \times \frac{\partial y_{t+1}}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial U_{ss}}$$

Therefore

- We can think on this as a Markovian Backpropagation

Now, the term $\frac{\partial L}{\partial U_{ss}}$

Assuming our change in time step $t \rightarrow t + 1$ and given

$$\mathbf{h}_t = \sigma_h (W_{sd}\mathbf{x}_t + U_{ss}\mathbf{h}_{t-1})$$

Therefore we have

$$\frac{\partial L(t+1)}{\partial U_{ss}} = \frac{\partial L(t+1)}{\partial y_{t+1}} \times \frac{\partial y_{t+1}}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial U_{ss}}$$

Therefore

- We can think on this as a Markovian Backpropagation

What if we go further

From $t - 1 \rightarrow t + 1$

$$\frac{\partial L(t+1)}{\partial U_{ss}} = \frac{\partial L(t+1)}{\partial y_{t+1}} \times \frac{\partial y_{t+1}}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial h_t} \times \frac{\partial h_t}{\partial U_{ss}}$$

Now, the trick if we consider all the possible derivatives from 0 to t

- We have:

$$\frac{\partial L(t+1)}{\partial U_{ss}} = \sum_{i=0}^T \frac{\partial L(t+1)}{\partial y_{t+1}} \times \frac{\partial y_{t+1}}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial h_t} \times \frac{\partial h_t}{\partial U_{ss}}$$

However:

- How do we calculate $\frac{\partial h_{t+1}}{\partial h_k}$?

What if we go further

From $t - 1 \rightarrow t + 1$

$$\frac{\partial L(t+1)}{\partial U_{ss}} = \frac{\partial L(t+1)}{\partial y_{t+1}} \times \frac{\partial y_{t+1}}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial h_t} \times \frac{\partial h_t}{\partial U_{ss}}$$

Now, the trick if we consider all the possible derivatives from 0 to T

- We have:

$$\frac{\partial L(t+1)}{\partial U_{ss}} = \sum_{t=0}^T \frac{\partial L(t+1)}{\partial y_{t+1}} \times \frac{\partial y_{t+1}}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial h_t} \times \frac{\partial h_t}{\partial U_{ss}}$$

However:

- How do we calculate $\frac{\partial h_{t+1}}{\partial h_k}$?

What if we go further

From $t - 1 \rightarrow t + 1$

$$\frac{\partial L(t+1)}{\partial U_{ss}} = \frac{\partial L(t+1)}{\partial y_{t+1}} \times \frac{\partial y_{t+1}}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial h_t} \times \frac{\partial h_t}{\partial U_{ss}}$$

Now, the trick if we consider all the possible derivatives from 0 to T

- We have:

$$\frac{\partial L(t+1)}{\partial U_{ss}} = \sum_{t=0}^T \frac{\partial L(t+1)}{\partial y_{t+1}} \times \frac{\partial y_{t+1}}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial h_t} \times \frac{\partial h_t}{\partial U_{ss}}$$

However

- How do we calculate $\frac{\partial h_{t+1}}{\partial h_k}$?

We have a proposal

Given the product of functions

$$\frac{\partial h_{t+1}}{\partial h_k} = \frac{\partial h_{k+1}}{\partial h_k} \times \frac{\partial h_{k+2}}{\partial h_{k+1}} \times \dots \times \frac{\partial h_{t+1}}{\partial h_t}$$

Here we know that

$$\frac{\partial h_{i+1}}{\partial h_i} = \frac{\partial h_{i+1}}{\partial net_s} \times \frac{\partial net_s}{\partial h_i}$$

We have a proposal

Given the product of functions

$$\frac{\partial h_{t+1}}{\partial h_k} = \frac{\partial h_{k+1}}{\partial h_k} \times \frac{\partial h_{k+2}}{\partial h_{k+1}} \times \dots \times \frac{\partial h_{t+1}}{\partial h_t}$$

Here, we know that

$$\frac{\partial h_{i+1}}{\partial h_i} = \frac{\partial h_{i+1}}{\partial net_s} \times \frac{\partial net_s}{\partial h_i}$$

We have that

We have given $\mathbf{h}_{i+1} = \sigma_h (W_{sd}\mathbf{x}_i + U_{ss}\mathbf{h}_i)$ and $net_h = W_{sd}\mathbf{x}_i + U_{ss}\mathbf{h}_i$

$$\frac{\partial \mathbf{h}_{i+1}}{\partial net_s} = \begin{pmatrix} \sigma'_h(net_{h1}) & 0 & \cdots & 0 \\ 0 & \sigma'_h(net_{h2}) & \cdots & 0 \\ \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \cdots & \sigma'_h(net_{hs}) \end{pmatrix} = D_{i+1}$$

Finally, we have that

$$\frac{\partial net_s}{\partial h_i} = U_{ss}$$

We have that

We have given $\mathbf{h}_{i+1} = \sigma_h (W_{sd}\mathbf{x}_i + U_{ss}\mathbf{h}_i)$ and $net_h = W_{sd}\mathbf{x}_i + U_{ss}\mathbf{h}_i$

$$\frac{\partial \mathbf{h}_{i+1}}{\partial net_s} = \begin{pmatrix} \sigma'_h(net_{h1}) & 0 & \cdots & 0 \\ 0 & \sigma'_h(net_{h2}) & \cdots & 0 \\ \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \cdots & \sigma'_h(net_{hs}) \end{pmatrix} = D_{i+1}$$

Finally, we have that

$$\frac{\partial net_s}{\partial h_i} = U_{ss}$$

Then

We can aggregate over all the time

$$\frac{\partial L}{\partial U_{ss}} = \sum_{k=1}^t \frac{\partial L(t+1)}{\partial y_{t+1}} \times \frac{\partial y_{t+1}}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial h_k} \times \frac{\partial h_t}{\partial U_{ss}}$$

Now, we need to derive the L with respect to h_{t+1}

$$\frac{\partial L(t+1)}{\partial W_{sd}} = \frac{\partial L(t+1)}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial W_{sd}}$$

Then

We can aggregate over all the time

$$\frac{\partial L}{\partial U_{ss}} = \sum_{k=1}^t \frac{\partial L(t+1)}{\partial y_{t+1}} \times \frac{\partial y_{t+1}}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial h_k} \times \frac{\partial h_t}{\partial U_{ss}}$$

Now, we need to derive the L with respect to W_{sd}

$$\frac{\partial L(t+1)}{\partial W_{sd}} = \frac{\partial L(t+1)}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial W_{sd}}$$

Now

Because h_t and x_{t+1} , we need to back-propagate to h_t

$$\begin{aligned}\frac{\partial L(t+1)}{\partial W_{sd}} &= \frac{\partial L(t+1)}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial W_{sd}} + \frac{\partial L(t+1)}{\partial h_t} \times \frac{\partial h_t}{\partial W_{sd}} \\ &= \frac{\partial L(t+1)}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial W_{sd}} + \frac{\partial L(t+1)}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial h_t} \times \frac{\partial h_t}{\partial W_{sd}}\end{aligned}$$

Then summing over all the contributions from t to 0

$$\frac{\partial L(t+1)}{\partial W_{sd}} = \sum_{k=1}^{t+1} \frac{\partial L(t+1)}{\partial y_{t+1}} \times \frac{\partial y_{t+1}}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial h_k} \times \frac{\partial h_t}{\partial W_{sd}}$$

Finally summing over all the time

$$\frac{\partial L}{\partial W_{sd}} = \sum_{k=1}^{t+1} \frac{\partial L(t+1)}{\partial y_{t+1}} \times \frac{\partial y_{t+1}}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial h_k} \times \frac{\partial h_t}{\partial W_{sd}}$$

Now

Because h_t and x_{t+1} , we need to back-propagate to h_t

$$\begin{aligned}\frac{\partial L(t+1)}{\partial W_{sd}} &= \frac{\partial L(t+1)}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial W_{sd}} + \frac{\partial L(t+1)}{\partial h_t} \times \frac{\partial h_t}{\partial W_{sd}} \\ &= \frac{\partial L(t+1)}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial W_{sd}} + \frac{\partial L(t+1)}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial h_t} \times \frac{\partial h_t}{\partial W_{sd}}\end{aligned}$$

Then summing over all the contributions from t to 0

$$\frac{\partial L(t+1)}{\partial W_{sd}} = \sum_{k=1}^{t+1} \frac{\partial L(t+1)}{\partial y_{t+1}} \times \frac{\partial y_{t+1}}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial h_k} \times \frac{\partial h_t}{\partial W_{sd}}$$

Finally, summing over all the time

$$\frac{\partial L}{\partial W_{sd}} = \sum_{k=1}^{t+1} \frac{\partial L(t+1)}{\partial y_{t+1}} \times \frac{\partial y_{t+1}}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial h_k} \times \frac{\partial h_t}{\partial W_{sd}}$$

Now

Because h_t and x_{t+1} , we need to back-propagate to h_t

$$\begin{aligned}\frac{\partial L(t+1)}{\partial W_{sd}} &= \frac{\partial L(t+1)}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial W_{sd}} + \frac{\partial L(t+1)}{\partial h_t} \times \frac{\partial h_t}{\partial W_{sd}} \\ &= \frac{\partial L(t+1)}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial W_{sd}} + \frac{\partial L(t+1)}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial h_t} \times \frac{\partial h_t}{\partial W_{sd}}\end{aligned}$$

Then summing over all the contributions from t to 0

$$\frac{\partial L(t+1)}{\partial W_{sd}} = \sum_{k=1}^{t+1} \frac{\partial L(t+1)}{\partial y_{t+1}} \times \frac{\partial y_{t+1}}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial h_k} \times \frac{\partial h_t}{\partial W_{sd}}$$

Finally, summing over all the time

$$\frac{\partial L}{\partial W_{sd}} = \sum_{k=1}^{t+1} \frac{\partial L(t+1)}{\partial y_{t+1}} \times \frac{\partial y_{t+1}}{\partial h_{t+1}} \times \frac{\partial h_{t+1}}{\partial h_k} \times \frac{\partial h_t}{\partial W_{sd}}$$

Outline

1

Introduction

- History
- State-Space Model
- Back to the RNN Equations
- Introducing the Cost Function
- Other Cost Functions

2

Training a Vanilla RNN Model

- The Final RNN Model
- Back-Propagation Through Time (BPTT)
- Deriving $\frac{\partial L(t)}{\partial V_{os}}$
- **Vanishing and Exploding Gradients**
 - The Analysis of the Exploding and Vanishing Gradient
- Signal Propagation
 - The Stability Frontier
- Truncated BPTT
- Initialization
 - Hidden State

3

Modern Recurrent Architectures

- Now, Long Short Term Memory (LSTM)
 - What about the Output?
- What about Gated Recurrent Units (GRU) units?

4

Deeper Architectures with RNN's

- Introduction
- Deep Architectures for Better Learning
- Deep Input-to-Hidden Function
- Deep Transition Architectures
- Conclusions

Vanishing Gradients

We have a problem

$$\frac{\partial h_{k+1}}{\partial h_k} \times \frac{\partial h_{k+2}}{\partial h_{k+1}} \times \dots \times \frac{\partial h_{t+1}}{\partial h_t}$$

you finish with a vanishing gradient using

- This is problematic!!!

Vanishing Gradients

We have a problem

$$\frac{\partial h_{k+1}}{\partial h_k} \times \frac{\partial h_{k+2}}{\partial h_{k+1}} \times \dots \times \frac{\partial h_{t+1}}{\partial h_t}$$

You finish with a vanishing gradient using $\sigma = \frac{1}{1+\exp\{-x\}}$

- This is problematic!!!

Given

Given the commutativity of the product

- You could put together the derivative of the sigmoid's

$$f(x) = \frac{ds(x)}{dx} = \frac{e^{-x}}{(1 + e^{-x})^2}$$

Therefore, deriving again

$$\frac{df(x)}{dx} = -\frac{e^{-x}}{(1 + e^{-x})^2} + \frac{2(e^{-x})^2}{(1 + e^{-x})^3}$$

After making $f'(x) = 0$

- We have the maximum is at $x = 0$

Given

Given the commutativity of the product

- You could put together the derivative of the sigmoid's

$$f(x) = \frac{ds(x)}{dx} = \frac{e^{-x}}{(1 + e^{-x})^2}$$

Therefore, deriving again

$$\frac{df(x)}{dx} = -\frac{e^{-x}}{(1 + e^{-x})^2} + \frac{2(e^{-x})^2}{(1 + e^{-x})^3}$$

After making $x = 0$

- We have the maximum is at $x = 0$

Given

Given the commutativity of the product

- You could put together the derivative of the sigmoid's

$$f(x) = \frac{ds(x)}{dx} = \frac{e^{-x}}{(1 + e^{-x})^2}$$

Therefore, deriving again

$$\frac{df(x)}{dx} = -\frac{e^{-x}}{(1 + e^{-x})^2} + \frac{2(e^{-x})^2}{(1 + e^{-x})^3}$$

After making $\frac{df(x)}{dx} = 0$

- We have the maximum is at $x = 0$

Therefore

The maximum for the derivative of the sigmoid

- $f'(0) = 0.25$

Therefore, Given a Deep Network

- We could finish with

$$\lim_{k \rightarrow \infty} \left(\frac{ds(x)}{dx} \right)^k = \lim_{k \rightarrow \infty} (0.25)^k \rightarrow 0$$

A Vanishing Derivative or Vanishing Gradient

- Making quite difficult to do train a deeper network using this activation function for Deep Learning and even in Shallow Learning

Therefore

The maximum for the derivative of the sigmoid

- $f'(0) = 0.25$

Therefore, Given a **Deep** Network

- We could finish with

$$\lim_{k \rightarrow \infty} \left(\frac{ds(x)}{dx} \right)^k = \lim_{k \rightarrow \infty} (0.25)^k \rightarrow 0$$

A Vanishing Derivative or Vanishing Gradient

- Making quite difficult to do train a deeper network using this activation function for Deep Learning and even in Shallow Learning

Therefore

The maximum for the derivative of the sigmoid

- $f'(0) = 0.25$

Therefore, Given a **Deep** Network

- We could finish with

$$\lim_{k \rightarrow \infty} \left(\frac{ds(x)}{dx} \right)^k = \lim_{k \rightarrow \infty} (0.25)^k \rightarrow 0$$

A Vanishing Derivative or Vanishing Gradient

- Making quite difficult to do train a deeper network using this activation function for Deep Learning and even in Shallow Learning

For the case of vanishing gradient, we have that

Rearranging terms in $\frac{\partial h_{k+1}}{\partial h_k} \times \frac{\partial h_{k+2}}{\partial h_{k+1}} \times \dots \times \frac{\partial h_{t+1}}{\partial h_t}$

- We have

$$\left[\prod_{k=0}^T \frac{\partial h_{k+1}}{\partial net_s} \right] [U_{ss}]^{T+1}$$

Then, given the sigmoid

$$\prod_{k=0}^T \frac{\partial h_{k+1}}{\partial net_s} = \begin{bmatrix} \prod_{k=0}^T \sigma'_h(net_{h1}^k) & 0 & \dots & 0 \\ 0 & \prod_{k=0}^T \sigma'_h(net_{h2}^k) & \dots & 0 \\ \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \dots & \prod_{k=0}^T \sigma'_h(net_{hs}^k) \end{bmatrix}$$

For the case of vanishing gradient, we have that

Rearranging terms in $\frac{\partial h_{k+1}}{\partial h_k} \times \frac{\partial h_{k+2}}{\partial h_{k+1}} \times \dots \times \frac{\partial h_{t+1}}{\partial h_t}$

- We have

$$\left[\prod_{k=0}^T \frac{\partial h_{k+1}}{\partial net_s} \right] [U_{ss}]^{T+1}$$

Then, given the sigmoid

$$\prod_{k=0}^T \frac{\partial h_{k+1}}{\partial net_s} = \begin{bmatrix} \prod_{k=0}^T \sigma'_h (net_{h1}^k) & 0 & \dots & 0 \\ 0 & \prod_{k=0}^T \sigma'_h (net_{h2}^k) & \dots & 0 \\ \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \dots & \prod_{k=0}^T \sigma'_h (net_{hs}^k) \end{bmatrix}$$

It is clear

That you have the phenomena of vanishing gradient

- Do we have a way to fixing this?

Yes

- The use of new activation functions.

It is clear

That you have the phenomena of vanishing gradient

- Do we have a way to fixing this?

Yes

- The use of new activation functions.

For example, the ReLu activation function

The need to introduce a new function

$$f(x) = x^+ = \max(0, x)$$

It is called ReLu or Rectifier

With a smooth approximation (Softplus function)

$$f(x) = \frac{\ln(1 + e^{kx})}{k}$$

For example, the ReLu activation function

The need to introduce a new function

$$f(x) = x^+ = \max(0, x)$$

It is called ReLu or Rectifier

With a smooth approximation (Softplus function)

$$f(x) = \frac{\ln(1 + e^{kx})}{k}$$

Outline

1

Introduction

- History
- State-Space Model
- Back to the RNN Equations
- Introducing the Cost Function
- Other Cost Functions

2

Training a Vanilla RNN Model

- The Final RNN Model
- Back-Propagation Through Time (BPTT)
- Deriving $\frac{\partial L(t)}{\partial V_{os}}$
- Vanishing and Exploding Gradients
 - The Analysis of the Exploding and Vanishing Gradient
- Signal Propagation
 - The Stability Frontier
- Truncated BPTT
- Initialization
 - Hidden State

3

Modern Recurrent Architectures

- Now, Long Short Term Memory (LSTM)
 - What about the Output?
- What about Gated Recurrent Units (GRU) units?

4

Deeper Architectures with RNN's

- Introduction
- Deep Architectures for Better Learning
- Deep Input-to-Hidden Function
- Deep Transition Architectures
- Conclusions

However

Here the gradient can explode

- Thus, the need to control the gradient...

Therefore we will use the following analysis [8]

- “The Emergence of Spectral Universality in Deep Networks” by
Jeffrey Pennington, Samuel S. Schoenholz, Surya Ganguli

However

Here the gradient can explode

- Thus, the need to control the gradient...

Therefore, we will use the following analysis [6]

- “The Emergence of Spectral Universality in Deep Networks” by Jeffrey Pennington, Samuel S. Schoenholz, Surya Ganguli

We have

The following dynamic

$$\mathbf{h}_t = \sigma_h(s_t), \mathbf{s}_t = W_{sd}\mathbf{x}_t + U_{ss}\mathbf{h}_{t-1} + b_h$$

Then, we have the following Jacobian

$$J = \frac{\partial \mathbf{h}_T}{\partial \mathbf{h}_0} = \prod_{t=1}^L D_t U_{ss}$$

We have

The following dynamic

$$\mathbf{h}_t = \sigma_h(s_t), \mathbf{s}_t = W_{sd}\mathbf{x}_t + U_{ss}\mathbf{h}_{t-1} + b_h$$

Then, we have the following Jacobian

$$J = \frac{\partial h_T}{\partial h_0} = \prod_{t=1}^L D_t U_{SS}$$

Here, we have

Where as we saw it D_t is a diagonal matrix

- With entries $D_{ij}^t = \sigma' \left(s_i^l \right) \delta_{ij}$
 - ▶ Here δ_{ij} is the Kronecker delta function

J is an input-output Jacobian

- This Jacobian J is a matrix of dimension $s \times s$ therefore,

It is closely related to the backpropagation operator

- Mapping output errors to weight matrices at a given layer,
 - ▶ in the sense that if the former is well-conditioned, then the latter tends to be well-conditioned for all weight layers.

Here, we have

Where as we saw it D_t is a diagonal matrix

- With entries $D_{ij}^t = \sigma' \left(s_i^l \right) \delta_{ij}$
 - ▶ Here δ_{ij} is the Kronecker delta function

J is an input-output Jacobian

- This Jacobian J is a matrix of dimension $s \times s$ therefore,

It is closely related to the backpropagation operator

- Mapping output errors to weight matrices at a given layer,
 - ▶ in the sense that if the former is well-conditioned, then the latter tends to be well-conditioned for all weight layers.

Here, we have

Where as we saw it D_t is a diagonal matrix

- With entries $D_{ij}^t = \sigma' \left(s_i^l \right) \delta_{ij}$
 - ▶ Here δ_{ij} is the Kronecker delta function

J is an input-output Jacobian

- This Jacobian J is a matrix of dimension $s \times s$ therefore,

It is closely related to the backpropagation operator

- Mapping output errors to weight matrices at a given layer,
 - ▶ in the sense that if the former is well-conditioned, then the latter tends to be well-conditioned for all weight layers.

Actually

Given this matrix J

- We have that if we can analyze the set of eigenvalues (Spectrum)

We can try to get a way

- To stabilize our training

Actually

Given this matrix J


- We have that if we can analyze the set of eigenvalues (Spectrum)

We can try to get a way

- To stabilize our training

A Trick

An RNN can be seen as a deep neural network



Remember the structure of the layer

The following dynamic

$$\mathbf{h}_t = \sigma_h(s_t), \mathbf{s}_t = W_{sd}\mathbf{x}_t + U_{ss}\mathbf{h}_{t-1} + b_h$$

Therefore, we have that

$$s_{it} = \sum_j W_{ij}x_j^t + \sum_k U_{ik}h_k^{t-1} + b_i$$

We assume the following about the temporal layer weights

$$[U_{ss}, W_{sd}] \sim N\left(0, \frac{\rho_w^2}{N}\right), b_h \sim N(0, \rho_b^2)$$

- Here $N = s$ the state dimension.

Remember the structure of the layer

The following dynamic

$$\mathbf{h}_t = \sigma_h(s_t), \mathbf{s}_t = W_{sd}\mathbf{x}_t + U_{ss}\mathbf{h}_{t-1} + b_h$$

Therefore, we have that

$$s_{it} = \sum_j W_{ij}x_j^t + \sum_k U_{ik}h_k^{t-1} + b_i$$

We assume the following about the temporal layer weights

$$[U_{ss}, W_{sd}] \sim N\left(0, \frac{\rho_w^2}{N}\right), b_h \sim N(0, \rho_b^2)$$

- Here $N = s$ the state dimension.

Remember the structure of the layer

The following dynamic

$$\mathbf{h}_t = \sigma_h(s_t), \mathbf{s}_t = W_{sd}\mathbf{x}_t + U_{ss}\mathbf{h}_{t-1} + b_h$$

Therefore, we have that

$$s_{it} = \sum_j W_{ij}x_j^t + \sum_k U_{ik}h_k^{t-1} + b_i$$

We assume the following about the temporal layer weights

$$[U_{ss}, W_{sd}] \sim N\left(0, \frac{\rho_w^2}{N}\right), b_h \sim N(0, \rho_b^2)$$

- Here $N = s$ the state dimension.

Outline

1

Introduction

- History
- State-Space Model
- Back to the RNN Equations
- Introducing the Cost Function
- Other Cost Functions

2

Training a Vanilla RNN Model

- The Final RNN Model
- Back-Propagation Through Time (BPTT)
- Deriving $\frac{\partial L(t)}{\partial V_{os}}$
- Vanishing and Exploding Gradients
 - The Analysis of the Exploding and Vanishing Gradient

● Signal Propagation

- The Stability Frontier
- Truncated BPTT
- Initialization
 - Hidden State

3

Modern Recurrent Architectures

- Now, Long Short Term Memory (LSTM)
 - What about the Output?
- What about Gated Recurrent Units (GRU) units?

4

Deeper Architectures with RNN's

- Introduction
- Deep Architectures for Better Learning
- Deep Input-to-Hidden Function
- Deep Transition Architectures
- Conclusions

Therefore, we have

In [7, 8]

- In these works, it has been shown that the propagation of a distribution through the N multiple layers, when N is large:
 - ▶ It tends to a Gaussian Distribution

With Zero Mean and Variance q^t

$$q^t = \text{Var} \left[q^{t-1} | \rho_w, \rho_b \right] = \rho_w^2 \int D h \sigma_h \left(\sqrt{q^{t-1}} h \right)^2 + \rho_b^2$$

- where ρ_w and ρ_b are standard deviations for $[W_{sd} U_{ss}]$ and b_h respectively.

Therefore, we have

In [7, 8]

- In these works, it has been shown that the propagation of a distribution through the N multiple layers, when N is large:
 - ▶ It tends to a Gaussian Distribution

With Zero Mean and Variance q^t

$$q^t = Var \left[q^{t-1} | \rho_w, \rho_b \right] = \rho_w^2 \int Dh \sigma_h \left(\sqrt{q^{t-1}} h \right)^2 + \rho_b^2$$

- where ρ_w and ρ_b are standard deviations for $[W_{sd}U_{ss}]$ and b_h respectively.

Where

We have an initial condition

$$q^1 = \frac{\rho_w^2}{N} \sum_{i=1}^N \left(x_i^0\right)^2 + \rho_b^2$$

And for Dh

$$Dh = \frac{dh}{\sqrt{2\pi}} \exp\left\{-\frac{h^2}{2}\right\}$$

- The standard normal distribution

Where

We have an initial condition

$$q^1 = \frac{\rho_w^2}{N} \sum_{i=1}^N \left(x_i^0\right)^2 + \rho_b^2$$

And for Dh

$$Dh = \frac{dh}{\sqrt{2\pi}} \exp \left\{ -\frac{h^2}{2} \right\}$$

- The standard normal distribution

We have two conditions

We have that if $q^1 = q^*$

- Then, the dynamics start at the fixed point and the distribution of D_t is independent of t .

Even, when $q^1 \neq q^*$

- A few layers is often sufficient to approximately converge to the fixed point

Therefore:

- As such, when L is large, it is often a good approximation to assume that $q^1 = q^*$ for all t when computing the spectrum of J

We have two conditions

We have that if $q^1 = q^*$

- Then, the dynamics start at the fixed point and the distribution of D_t is independent of t .

Even, when $q^1 \neq q^*$

- A few layers is often sufficient to approximately converge to the fixed point

Therefore:

- As such, when L is large, it is often a good approximation to assume that $q^1 = q^*$ for all t when computing the spectrum of J

We have two conditions

We have that if $q^1 = q^*$

- Then, the dynamics start at the fixed point and the distribution of D_t is independent of t .

Even, when $q^1 \neq q^*$

- A few layers is often sufficient to approximately converge to the fixed point

Therefore

- As such, when L is large, it is often a good approximation to assume that $q^1 = q^*$ for all t when computing the spectrum of J

Outline

1

Introduction

- History
- State-Space Model
- Back to the RNN Equations
- Introducing the Cost Function
- Other Cost Functions

2

Training a Vanilla RNN Model

- The Final RNN Model
- Back-Propagation Through Time (BPTT)
- Deriving $\frac{\partial L(t)}{\partial V_{os}}$
- Vanishing and Exploding Gradients
 - The Analysis of the Exploding and Vanishing Gradient
- **Signal Propagation**
 - **The Stability Frontier**
- Truncated BPTT
- Initialization
 - Hidden State

3

Modern Recurrent Architectures

- Now, Long Short Term Memory (LSTM)
 - What about the Output?
- What about Gated Recurrent Units (GRU) units?

4

Deeper Architectures with RNN's

- Introduction
- Deep Architectures for Better Learning
- Deep Input-to-Hidden Function
- Deep Transition Architectures
- Conclusions

Now, assume that

Now, consider the evolution of a single input through the network x_{it}

- Since the weights and biases are independent with zero mean

$$E[s_{it}] = 0$$

The second moment of the Gaussian random variable (Actually the Covariance)

$$E[s_{it}s_{jt}] = q^t \delta_{ij}$$

Now, assume that

Now, consider the evolution of a single input through the network x_{it}

- Since the weights and biases are independent with zero mean

$$E[s_{it}] = 0$$

The second moment of the Gaussian random variable (Actually the Covariance)

$$E[s_{it}s_{jt}] = q^t \delta_{ij}$$

Where the second moment

Of a Gaussian Distribution is

$$\int_{-\infty}^{\infty} s^2 \frac{1}{\sqrt{2\pi}\sigma} \exp \left\{ -\frac{(s - \mu)^2}{2\sigma^2} \right\} ds$$

Here we have

Here q^t is the variance of the pre-activations in the t^{th} layer due to an input \mathbf{x}_t

$$q^t = \frac{\rho_w^2}{\sqrt{2\pi}} \int \sigma_h^2 \left(\sqrt{q^{t-1}} s_{it-1} \right) \exp \left\{ -\frac{1}{2} s_{it}^2 \right\} ds_{it} + \rho_b^2$$

They describe the pass through the recursion of the RNN

- For any choice of ρ_w^2 and ρ_b^2 and a bounded ϕ the previous equation converges to a specific fix point.

This recursion has a fixed point

$$q^* = \frac{\rho_w^2}{\sqrt{2\pi}} \int \sigma_h^2 \left(\sqrt{q^*} s_{it-1} \right) \exp \left\{ -\frac{1}{2} s_{it}^2 \right\} ds_{it} + \rho_b^2$$

Here we have

Here q^t is the variance of the pre-activations in the t^{th} layer due to an input \mathbf{x}_t

$$q^t = \frac{\rho_w^2}{\sqrt{2\pi}} \int \sigma_h^2 \left(\sqrt{q^{t-1}} s_{it-1} \right) \exp \left\{ -\frac{1}{2} s_{it}^2 \right\} ds_{it} + \rho_b^2$$

They describe the pass through the recursion of the RNN

- For any choice of ρ_w^2 and ρ_b^2 and a bounded ϕ the previous equation converges to a specific fix point.

This recursion has a fixed point

$$q^* = \frac{\rho_w^2}{\sqrt{2\pi}} \int \sigma_h^2 \left(\sqrt{q^*} s_{it-1} \right) \exp \left\{ -\frac{1}{2} s_{it}^2 \right\} ds_{it} + \rho_b^2$$

Here we have

Here q^t is the variance of the pre-activations in the t^{th} layer due to an input \mathbf{x}_t

$$q^t = \frac{\rho_w^2}{\sqrt{2\pi}} \int \sigma_h^2 \left(\sqrt{q^{t-1}} \mathbf{s}_{it-1} \right) \exp \left\{ -\frac{1}{2} \mathbf{s}_{it}^2 \right\} d\mathbf{s}_{it} + \rho_b^2$$

They describe the pass through the recursion of the RNN

- For any choice of ρ_w^2 and ρ_b^2 and a bounded ϕ the previous equation converges to a specific fix point.

This recursion has a fixed point

$$q^* = \frac{\rho_w^2}{\sqrt{2\pi}} \int \sigma_h^2 \left(\sqrt{q^*} \mathbf{s}_{it-1} \right) \exp \left\{ -\frac{1}{2} \mathbf{s}_{it}^2 \right\} d\mathbf{s}_{it} + \rho_b^2$$

A Fixed Point

Definition

- In mathematics, a fixed point of a function is an element of the function's domain that is mapped to itself by the function.


Example

A Fixed Point

Definition

- In mathematics, a fixed point of a function is an element of the function's domain that is mapped to itself by the function.

Example



Therefore

We have that

- If the input x_0 is chosen so that $q^1 = q^*$ the dynamics start at the fixed point and the distribution of D_t is independent of t .

Not only that:

- $q^1 \neq q^*$ a few layers is often sufficient to approximately converge to a fixed point.

So when L is large:

- So it is a good approximation to assume $q^L = q^*$.

Therefore

We have that

- If the input x_0 is chosen so that $q^1 = q^*$ the dynamics start at the fixed point and the distribution of D_t is independent of t .

Not only that

- $q^1 \neq q^*$ a few layers is often sufficient to approximately converge to a fixed point.

So when n is large

- So it is a good approximation to assume $q^l = q^*$.

Therefore

We have that

- If the input x_0 is chosen so that $q^1 = q^*$ the dynamics start at the fixed point and the distribution of D_t is independent of t .

Not only that

- $q^1 \neq q^*$ a few layers is often sufficient to approximately converge to a fixed point.

So when t is large

- So it is a good approximation to assume $q^t = q^*$.

Additionally

The independence of the weights and biases implies

- The covariance between different pre-activations in the same layer will be given by

$$E[z_{it;a}z_{jt;b}] = q_{ab}^t \delta_{ij}$$

Therefore

$$q_{ab}^t = \rho_w^2 \int \sigma_h(u_1) \sigma_h(u_2) Dz_1 Dz_2 + \rho_b^2$$

- Where $Dz = \frac{1}{\sqrt{2\pi}} \int \exp\{-\frac{1}{2}s^2\} ds$
- $u_1 = \sqrt{q_{aa}^{t-1}}$
- $u_2 = \sqrt{q_{bb}^{t-1}} \left[c_{ab}^{t-1} s_1 + \sqrt{1 - (c_{ab}^{t-1})^2} s_2 \right]$
- $c_{ab}^t = \frac{q_{ab}^t}{\sqrt{q_{aa}^t q_{bb}^t}}$

Additionally

The independence of the weights and biases implies

- The covariance between different pre-activations in the same layer will be given by

$$E [z_{it;a} z_{jt;b}] = q_{ab}^t \delta_{ij}$$

Therefore

$$q_{ab}^t = \rho_w^2 \int \sigma_h(u_1) \sigma_h(u_2) Dz_1 Dz_2 + \rho_b^2$$

- Where $Dz = \frac{1}{\sqrt{2\pi}} \int \exp \left\{ -\frac{1}{2} s^2 \right\} ds$
- $u_1 = \sqrt{q_{aa}^{t-1}}$
- $u_2 = \sqrt{q_{bb}^{t-1}} \left[c_{ab}^{t-1} s_1 + \sqrt{1 - (c_{ab}^{t-1})^2} z_2 \right]$
- $c_{ab}^t = \frac{q_{ab}^t}{\sqrt{q_{aa}^t q_{bb}^t}}$

Therefore

Therefore, we can look at the variance of the Jacobian Matrix elements

$$\chi = \frac{1}{N} \left\langle \text{Tr} \left[(D_t U_{SS})^T D_t U_{SS} \right] \right\rangle = \sigma_w^2 \int [\sigma'_h (\sqrt{q^*} \mathbf{s}_{it})]^2 \exp \left\{ -\frac{1}{2} \mathbf{s}_{it}^2 \right\} d\mathbf{s}_{it}$$

Then

$\chi(\rho_w, \rho_b)$

- It separates (ρ_w, ρ_b) plane into two regions.

When

- Forward signal propagation expands and folds space in a chaotic manner and gradients explode

When

- Forward signal propagation contracts in an ordered manner and gradients exponentially vanishes

Then

$\chi(\rho_w, \rho_b)$

- It separates (ρ_w, ρ_b) plane into two regions.

When $\chi > 1$

- Forward signal propagation expands and folds space in a chaotic manner and gradients explode

When

- Forward signal propagation contracts in an ordered manner and gradients exponentially vanishes

Then

$\chi(\rho_w, \rho_b)$

- It separates (ρ_w, ρ_b) plane into two regions.

When $\chi > 1$


- Forward signal propagation expands and folds space in a chaotic manner and gradients explode

When $\chi < 1$

- Forward signal propagation contracts in an ordered manner and gradients exponentially vanishes

This Regions establish the stability of the network

We have the following



Therefore

It is clear that

- When we choose same $\rho_b = \rho_w$ we have a convergence of the network

Having other values

- It requires a careful choosing of the values

Therefore

It is clear that

- When we choose same $\rho_b = \rho_w$ we have a convergence of the network

Having other values

- It requires a careful choosing of the values

Outline

1

Introduction

- History
- State-Space Model
- Back to the RNN Equations
- Introducing the Cost Function
- Other Cost Functions

2

Training a Vanilla RNN Model

- The Final RNN Model
- Back-Propagation Through Time (BPTT)
- Deriving $\frac{\partial L(t)}{\partial V_{os}}$
- Vanishing and Exploding Gradients
 - The Analysis of the Exploding and Vanishing Gradient
- Signal Propagation
 - The Stability Frontier
- **Truncated BPTT**
- Initialization
 - Hidden State

3

Modern Recurrent Architectures

- Now, Long Short Term Memory (LSTM)
 - What about the Output?
- What about Gated Recurrent Units (GRU) units?

4

Deeper Architectures with RNN's

- Introduction
- Deep Architectures for Better Learning
- Deep Input-to-Hidden Function
- Deep Transition Architectures
- Conclusions

Another Problem

Although, the Vanishing and Exploding Gradients

- They are a problem for the RNN's

If we use the full BPTT

- We confront limitations on the amount of Memory and Hardware available

Thus a popular strategy

- It is the Truncated BPTT [9, 10]

Another Problem

Although, the Vanishing and Exploding Gradients

- They are a problem for the RNN's

If we use the full BPTT

- We confront limitations on the amount of Memory and Hardware available

There is a popular strategy

- It is the Truncated BPTT [9, 10]

Another Problem

Although, the Vanishing and Exploding Gradients

- They are a problem for the RNN's

If we use the full BPTT

- We confront limitations on the amount of Memory and Hardware available

Thus a popular strategy

- It is the Truncated BPTT [9, 10]

Therefore

They proposed using a truncation on the BPTT

- To solve the problem with the Vanishing and Exploding Gradient

What is Truncated BPTT?

- In general, this should be regarded as a heuristic technique for simplifying the computation.
 - Which it is a good approximation true gradient

Therefore

They proposed using a truncation on the BPTT

- To solve the problem with the Vanishing and Exploding Gradient

What is Truncated BPTT?

- In general, this should be regarded as a heuristic technique for simplifying the computation.
 - ▶ Which it is a good approximation true gradient

The Algorithm

Truncated BPTT

- 1 for $t = 1$ to T do:
- 2 Run the RNN for one step, computing h_t and y_t
- 3 if t divides k_1 then
- 4 Run BPTT from t to $t - k_2$

Something Notable

- It was first used by Elman [11]
- Also Mikolov et al. [12] used the TBPTT to train RNN on word-level language modeling.

The Algorithm

Truncated BPTT

- 1 for $t = 1$ to T do:
- 2 Run the RNN for one step, computing h_t and y_t
- 3 if t divides k_1 then
- 4 Run BPTT from t to $t - k_2$

Something Notable

- 1 It was first used by Elman [11]
- 2 Also Mikolov et al. [12] used the TBPTT to train RNN on word-level language modeling.

Outline

1

Introduction

- History
- State-Space Model
- Back to the RNN Equations
- Introducing the Cost Function
- Other Cost Functions

2

Training a Vanilla RNN Model

- The Final RNN Model
- Back-Propagation Through Time (BPTT)
- Deriving $\frac{\partial L(t)}{\partial V_{os}}$
- Vanishing and Exploding Gradients
 - The Analysis of the Exploding and Vanishing Gradient
- Signal Propagation
 - The Stability Frontier
- Truncated BPTT
- Initialization**
 - Hidden State

3

Modern Recurrent Architectures

- Now, Long Short Term Memory (LSTM)
 - What about the Output?
- What about Gated Recurrent Units (GRU) units?

4

Deeper Architectures with RNN's

- Introduction
- Deep Architectures for Better Learning
- Deep Input-to-Hidden Function
- Deep Transition Architectures
- Conclusions

Outline

1

Introduction

- History
- State-Space Model
- Back to the RNN Equations
- Introducing the Cost Function
- Other Cost Functions

2

Training a Vanilla RNN Model

- The Final RNN Model
- Back-Propagation Through Time (BPTT)
- Deriving $\frac{\partial L(t)}{\partial V_{os}}$
- Vanishing and Exploding Gradients
 - The Analysis of the Exploding and Vanishing Gradient
- Signal Propagation
 - The Stability Frontier
- Truncated BPTT
- Initialization
 - Hidden State

3

Modern Recurrent Architectures

- Now, Long Short Term Memory (LSTM)
 - What about the Output?
- What about Gated Recurrent Units (GRU) units?

4

Deeper Architectures with RNN's

- Introduction
- Deep Architectures for Better Learning
- Deep Input-to-Hidden Function
- Deep Transition Architectures
- Conclusions

Initialization of the Hidden State

This is the classic problem in RNN

- How to initialize the h_s hidden state?

There are two main methods

- Initialize h_s to the zero vector.
- Adaptive noisy initialization of h_s
- Find the steady state

Initialization of the Hidden State

This is the classic problem in RNN

- How to initialize the h_s hidden state?

There are two main methods

- 1 Initialize h_s to the zero vector.
- 2 Adaptive noisy initialization of h_s
- 3 Find the steady state

The Simplest One

We can simply initialize h_s

- To a zero state

Quite simple and easy to apply

- However do we have something better?

The Simplest One

We can simply initialize h_s

- To a zero state

Quite simple and easy to apply

- However do we have something better?

Adaptive noisy initialization

It is proposed by Zimmermann et al. [13]

- They proposed to use the residual error once the back-propagation was done for h_0

This is done

- By disturbing h_0 with a noise term Θ which follows the distribution of the residual error.

Adaptive noisy initialization

It is proposed by Zimmermann et al. [13]


- They proposed to use the residual error once the back-propagation was done for h_0

This is done

- By disturbing h_0 with a noise term Θ which follows the distribution of the residual error.

Adaptive Noise

The network tries to stabilize the output



Example of this initializations

Source <https://r2rt.com/non-zero-initial-states-for-recurrent-neural-networks.html>



What about the Weight Parameters?

We could simply initialize them to zero

- Denger Will Robinson!!!

A simple example with the following feed-forward architecture

$$w = \sigma_1(W_{hi}x)$$

$$y = \sigma_2(W_{oh}w)$$

$$L = \frac{1}{2} [y - z]^2$$

What about the Weight Parameters?

We could simply initialize them to zero

- Denger Will Robinson!!!

A simple example with the following feed-forward architecture

$$\mathbf{w} = \sigma_1 (W_{hi} \mathbf{x})$$

$$\mathbf{y} = \sigma_2 (W_{oh} \mathbf{w})$$

$$L = \frac{1}{2} [\mathbf{y} - \mathbf{z}]^2$$

Therefore

We have by back-propagation

$$\Delta W_{ho} = [\sigma'_2(W_{oh}\sigma_1(W_{hi}\mathbf{x}_1)) - z] \sigma'_2(W_{oh}\sigma_1(W_{hi}\mathbf{x})) W_{oh}\sigma'_1(W_{hi}\mathbf{x}) \mathbf{x}$$

Therefore

$$\Delta W_{ho} = 0$$

Therefore

We have by back-propagation

$$\Delta W_{ho} = [\sigma'_2(W_{oh}\sigma_1(W_{hi}\mathbf{x}_1)) - z] \sigma'_2(W_{oh}\sigma_1(W_{hi}\mathbf{x})) W_{oh}\sigma'_1(W_{hi}\mathbf{x}) \mathbf{x}$$

Therefore

$$\Delta W_{ho} = 0$$

Therefore

Not a good idea

- What else we can do?

We have heuristics as the Gaussian initialization

$$w_{ij} \sim N(0, \sigma^2)$$

Therefore

Not a good idea


- What else we can do?

We have heuristics as the Gaussian initialization

$$w_{ij} \sim N(0, \sigma^2)$$

Do you remember?

We have the following



Furthermore

We have heuristics

- For Relu — We multiply the randomly generated values of W by:

$$\sqrt{\frac{2}{size^{l-1}}}$$

For tanh — The heuristic is called Xavier initialization

$$\sqrt{\frac{2}{size^{l-1} + size^l}}$$

Other common one

$$\sqrt{\frac{2}{size^{l-1} + size^l}}$$

Furthermore

We have heuristics

- For Relu — We multiply the randomly generated values of W by:

$$\sqrt{\frac{2}{size^{l-1}}}$$

For tanh — The heuristic is called Xavier initialization

$$\sqrt{\frac{2}{size^{l-1} + size^l}}$$

Other common one

$$\sqrt{\frac{2}{size^{l-1} + size^l}}$$

Furthermore

We have heuristics

- For Relu — We multiply the randomly generated values of W by:

$$\sqrt{\frac{2}{size^{l-1}}}$$

For tanh — The heuristic is called Xavier initialization

$$\sqrt{\frac{2}{size^{l-1}}}$$

Other common one

$$\sqrt{\frac{2}{size^{l-1} + size^l}}$$

Outline

1

Introduction

- History
- State-Space Model
- Back to the RNN Equations
- Introducing the Cost Function
- Other Cost Functions

2

Training a Vanilla RNN Model

- The Final RNN Model
- Back-Propagation Through Time (BPTT)
- Deriving $\frac{\partial L(t)}{\partial V_{os}}$
- Vanishing and Exploding Gradients
 - The Analysis of the Exploding and Vanishing Gradient
- Signal Propagation
 - The Stability Frontier
- Truncated BPTT
- Initialization
 - Hidden State

3

Modern Recurrent Architectures

- Now, Long Short Term Memory (LSTM)
 - What about the Output?
- What about Gated Recurrent Units (GRU) units?

4

Deeper Architectures with RNN's

- Introduction
- Deep Architectures for Better Learning
- Deep Input-to-Hidden Function
- Deep Transition Architectures
- Conclusions

History of LSTM

They were introduced by

- LSTM was proposed in 1997 by Sepp Hochreiter and Jürgen Schmidhuber [14]

An attempt to deal with the vanishing and exploding gradient

- By introducing Constant Error Carousel (CEC) units

Properties

- In 1999, Felix Gers and his advisor Jürgen Schmidhuber and Fred Cummins introduced the forget gate (also called “keep gate”) into LSTM architecture.
 - ▶ It enables the LSTM to reset its own state

History of LSTM

They were introduced by

- LSTM was proposed in 1997 by Sepp Hochreiter and Jürgen Schmidhuber [14]

An attempt to deal with the vanishing and exploding gradient

- By introducing Constant Error Carousel (CEC) units

Properties

- In 1999, Felix Gers and his advisor Jürgen Schmidhuber and Fred Cummins introduced the forget gate (also called “keep gate”) into LSTM architecture.
 - It enables the LSTM to reset its own state

History of LSTM

They were introduced by

- LSTM was proposed in 1997 by Sepp Hochreiter and Jürgen Schmidhuber [14]

An attempt to deal with the vanishing and exploding gradient

- By introducing Constant Error Carousel (CEC) units

Properties

- In 1999, Felix Gers and his advisor Jürgen Schmidhuber and Fred Cummins introduced the forget gate (also called “keep gate”) into LSTM architecture.
 - ▶ It enables the LSTM to reset its own state

Long Short Term Memory (LSTM)

We have the following Architecture (Component wise product \odot)

$$\mathbf{f}_t = \text{sig}[W_f \mathbf{x}_t + U_f \mathbf{h}_{t-1} + \mathbf{b}_f] \text{ (Forget Gate)}$$

$$\mathbf{i}_t = \text{sig}[W_i \mathbf{x}_t + U_i \mathbf{h}_{t-1} + \mathbf{b}_i] \text{ (Input/Update Gate)}$$

$$\mathbf{o}_t = \text{sig}[W_o \mathbf{x}_t + U_o \mathbf{h}_{t-1} + \mathbf{b}_o] \text{ (Output Gate)}$$

$$\hat{\mathbf{c}}_t = \tanh[W_c \mathbf{x}_t + U_c \mathbf{h}_{t-1} + \mathbf{b}_c] \text{ (Intermediate Cell Gate)}$$


$$\mathbf{c}_t = \mathbf{f}_t \odot \mathbf{c}_{t-1} + \mathbf{i}_t \odot \hat{\mathbf{c}}_t \text{ (Cell State Gate)}$$

$$\mathbf{h}_t = \mathbf{o}_t \odot \tanh(\mathbf{c}_t) \text{ (Hidden State)}$$

- Where σ is a sigmoid function.

Graphically

We have that



Here, Sepp Hochreiter and Jürgen Schmidhuber [14, 15] say

In the RNN

$$\mathbf{h}_t = \sigma_h (W_{sd}\mathbf{x}_t + U_{ss}\mathbf{h}_{t-1})$$

But, Here

$$\begin{aligned}c_t &= f_t \odot c_{t-1} + i_t \odot \hat{c}_t \text{ (Cell State Gate)} \\h_t &= o_t \odot \tanh(c_t)\end{aligned}$$

you need the forget term, the input term, and the intermediate cell

- To update the state

Here, Sepp Hochreiter and Jürgen Schmidhuber [14, 15] say

In the RNN

$$\mathbf{h}_t = \sigma_h (W_{sd}\mathbf{x}_t + U_{ss}\mathbf{h}_{t-1})$$

But Here

$$\mathbf{c}_t = \mathbf{f}_t \odot \mathbf{c}_{t-1} + \mathbf{i}_t \odot \hat{\mathbf{c}}_t \text{ (Cell State Gate)}$$

$$\mathbf{h}_t = \mathbf{o}_t \odot \tanh(\mathbf{c}_t)$$

you need the forget term, the input term, and the intermediate cell

- To update the state

Here, Sepp Hochreiter and Jürgen Schmidhuber [14, 15] say

In the RNN

$$\mathbf{h}_t = \sigma_h (W_{sd}\mathbf{x}_t + U_{ss}\mathbf{h}_{t-1})$$

But Here

$$\mathbf{c}_t = \mathbf{f}_t \odot \mathbf{c}_{t-1} + \mathbf{i}_t \odot \hat{\mathbf{c}}_t \text{ (Cell State Gate)}$$

$$\mathbf{h}_t = \mathbf{o}_t \odot \tanh(\mathbf{c}_t)$$

You need the forget term, the input term and the intermediate cell

- To update the state

You can see

Something Notable

- The cell keeps track of the dependencies between the elements in the input sequence and the state

The input gate

- It is in charge of how much of the input flows into the cell gate

$$i_t = \sigma [W_i x_t + U_i h_{t-1} + b_i]$$

You can see

Something Notable

- The cell keeps track of the dependencies between the elements in the input sequence and the state

The input gate

- It is in charge of how much of the input flows into the cell gate

$$\mathbf{i}_t = \sigma [W_i \mathbf{x}_t + U_i \mathbf{h}_{t-1} + \mathbf{b}_i]$$

What is the meaning?

We have that

- The sigmoid layer decides what values to update

They impact the term z_j or a_j

- Making possible to decide how to control the cell intermediate values

What is the meaning?

We have that

- The sigmoid layer decides what values to update

They impact the term $i_t \odot \hat{c}_t$

- Making possible to decide how to control the cell intermediate values

The forget gate

- How much of the previous cell gate time value remains in the cell at time t

$$\mathbf{f}_t = \sigma [W_f \mathbf{x}_t + U_f \mathbf{h}_{t-1} + \mathbf{b}_f]$$

Actually

- It uses previous state and input

Then the sigmoid actually can be interpreted as

- Sigmoid: value 0 and 1 – “completely forget” vs. “completely keep”

Now

The forget gate

- How much of the previous cell gate time value remains in the cell at time t

$$\mathbf{f}_t = \sigma [W_f \mathbf{x}_t + U_f \mathbf{h}_{t-1} + \mathbf{b}_f]$$

Actually

- It uses previous state and input

Then the sigmoid actually can be interpreted as

- Sigmoid: value 0 and 1 – “completely forget” vs. “completely keep”

Now

The forget gate

- How much of the previous cell gate time value remains in the cell at time t

$$\mathbf{f}_t = \sigma [W_f \mathbf{x}_t + U_f \mathbf{h}_{t-1} + \mathbf{b}_f]$$

Actually

- It uses previous state and input

Then the sigmoid actually can be interpreted as

- Sigmoid: value 0 and 1 – “completely forget” vs. “completely keep”

Furthermore

The output gate

- It controls the extent to which the value in the cell is used to compute the actual state

Which impacts the term $f(\mathbf{h}_{t-1}, \mathbf{x}_t)$

- Based on the previous cell state

Thus a type of control

- Between the previous cell state and the new cell state

Furthermore

The output gate

- It controls the extent to which the value in the cell is used to compute the actual state

Which impacts the term $f_t \odot c_{t-1}$

- Based on the previous cell state

Thus a type of control

- Between the previous cell state and the new cell state

Furthermore

The output gate

- It controls the extent to which the value in the cell is used to compute the actual state

Which impacts the term $f_t \odot c_{t-1}$

- Based on the previous cell state

Thus a type of control

- Between the previous cell state and the new cell state

Finally

We have the update of the cell as

$$\mathbf{c}_t = \mathbf{f}_t \odot \mathbf{c}_{t-1} + \mathbf{i}_t \odot \hat{\mathbf{c}}_t$$

Basically

- Apply forget operation to previous internal cell state.
- Add new candidate values, scaled by how much we decided to update

We can see as

- Drop old information and add new information about subject's gender.

Finally

We have the update of the cell as

$$\mathbf{c}_t = \mathbf{f}_t \odot \mathbf{c}_{t-1} + \mathbf{i}_t \odot \hat{\mathbf{c}}_t$$

Basically

- Apply forget operation to previous internal cell state.
- Add new candidate values, scaled by how much we decided to update

We can see as

- Drop old information and add new information about subject's gender.

Finally

We have the update of the cell as

$$\mathbf{c}_t = \mathbf{f}_t \odot \mathbf{c}_{t-1} + \mathbf{i}_t \odot \hat{\mathbf{c}}_t$$

Basically

- Apply forget operation to previous internal cell state.
- Add new candidate values, scaled by how much we decided to update

We can see as

- Drop old information and add new information about subject's gender.

Outline

1

Introduction

- History
- State-Space Model
- Back to the RNN Equations
- Introducing the Cost Function
- Other Cost Functions

2

Training a Vanilla RNN Model

- The Final RNN Model
- Back-Propagation Through Time (BPTT)
- Deriving $\frac{\partial L(t)}{\partial V_{os}}$
- Vanishing and Exploding Gradients
 - The Analysis of the Exploding and Vanishing Gradient
- Signal Propagation
 - The Stability Frontier
- Truncated BPTT
- Initialization
 - Hidden State

3

Modern Recurrent Architectures

- Now, Long Short Term Memory (LSTM)
 - What about the Output?
- What about Gated Recurrent Units (GRU) units?

4

Deeper Architectures with RNN's

- Introduction
- Deep Architectures for Better Learning
- Deep Input-to-Hidden Function
- Deep Transition Architectures
- Conclusions

Thus at the output layer and update state

We have

$$\mathbf{o}_t = \sigma [W_o \mathbf{x}_t + U_o \mathbf{h}_{t-1} + \mathbf{b}_o] \text{ (Output Gate)}$$

$$\mathbf{h}_t = \mathbf{o}_t \odot \tanh(\mathbf{c}_t) \text{ (Hidden State)}$$

Therefore, we have that

- Sigmoid layer: decide what linear combination of state/input to output

Additionally, we have that the tanh squashes the values between -1 and 1

- The output is used to filter a version of cell state!!!

Thus at the output layer and update state

We have

$$\mathbf{o}_t = \sigma [W_o \mathbf{x}_t + U_o \mathbf{h}_{t-1} + \mathbf{b}_o] \text{ (Output Gate)}$$

$$\mathbf{h}_t = \mathbf{o}_t \odot \tanh(\mathbf{c}_t) \text{ (Hidden State)}$$

Therefore, we have that

- Sigmoid layer: decide what linear combination of state/input to output

Additionally, we have that the \tanh squashes the values between -1 and 1

- The output is used to filter a version of cell state!!!

Thus at the output layer and update state

We have

$$\mathbf{o}_t = \sigma [W_o \mathbf{x}_t + U_o \mathbf{h}_{t-1} + \mathbf{b}_o] \text{ (Output Gate)}$$

$$\mathbf{h}_t = \mathbf{o}_t \odot \tanh(\mathbf{c}_t) \text{ (Hidden State)}$$

Therefore, we have that

- Sigmoid layer: decide what linear combination of state/input to output


Additionally, we have that the tanh squashes the values between -1 and 1

- The output is used to filter a version of cell state!!!

Something nice about LSTM

Quite nice

- Backpropagation from c_t to c_{t-1} requires only elementwise multiplication!



LSTM Remarks

First

- It maintains a separate cell state from what is outputted

Second

- Use gates to control the flow of information
 - ▶ Forget gate tries to get rid of irrelevant information
 - ▶ Selectively update cell state
 - ▶ Output gate returns a filtered version of the cell state

Third

- Backpropagation from c_t to c_{t-1} requires only elementwise multiplication!

LSTM Remarks

First

- It maintains a separate cell state from what is outputted

Second

- Use gates to control the flow of information
 - ▶ Forget gate tries to get rid of irrelevant information
 - ▶ Selectively update cell state
 - ▶ Output gate returns a filtered version of the cell state

Third

- Backpropagation from a_t to a_{t-1} requires only elementwise multiplication!

LSTM Remarks

First

- It maintains a separate cell state from what is outputted

Second

- Use gates to control the flow of information
 - ▶ Forget gate tries to get rid of irrelevant information
 - ▶ Selectively update cell state
 - ▶ Output gate returns a filtered version of the cell state

Third

- Backpropagation from c_t to c_{t-1} requires only elementwise multiplication!

Achievements

LSTM achieved record results in natural language text compression

- <http://www.mattmahoney.net/dc/text.html#1218>

Unconstrained connected handwriting recognition

- Graves, A., Liwicki, M., Fernández, S., Bertolami, R., Bunke, H., Schmidhuber, J. (May 2009). "A Novel Connectionist System for Unconstrained Handwriting Recognition". IEEE Transactions on Pattern Analysis and Machine Intelligence. 31 (5): 855–868

Finally

- Won the ICDAR handwriting competition (2009)

Achievements

LSTM achieved record results in natural language text compression

- <http://www.mattmahoney.net/dc/text.html#1218>

Unsegmented connected handwriting recognition

- Graves, A., Liwicki, M., Fernández, S., Bertolami, R.; Bunke, H., Schmidhuber, J. (May 2009). "A Novel Connectionist System for Unconstrained Handwriting Recognition". IEEE Transactions on Pattern Analysis and Machine Intelligence. 31 (5): 855–868

Results

- Won the ICDAR handwriting competition (2009)

Achievements

LSTM achieved record results in natural language text compression

- <http://www.mattmahoney.net/dc/text.html#1218>

Unsegmented connected handwriting recognition

- Graves, A., Liwicki, M., Fernández, S., Bertolami, R.; Bunke, H., Schmidhuber, J. (May 2009). "A Novel Connectionist System for Unconstrained Handwriting Recognition". IEEE Transactions on Pattern Analysis and Machine Intelligence. 31 (5): 855–868

Finally

- Won the ICDAR handwriting competition (2009)

Right now

Something Notable

- As of 2016, major technology companies including Google, Apple, and Microsoft were using LSTM as fundamental components in new products.

Outline

1

Introduction

- History
- State-Space Model
- Back to the RNN Equations
- Introducing the Cost Function
- Other Cost Functions

2

Training a Vanilla RNN Model

- The Final RNN Model
- Back-Propagation Through Time (BPTT)
- Deriving $\frac{\partial L(t)}{\partial V_{os}}$
- Vanishing and Exploding Gradients
 - The Analysis of the Exploding and Vanishing Gradient
- Signal Propagation
 - The Stability Frontier
- Truncated BPTT
- Initialization
 - Hidden State

3

Modern Recurrent Architectures

- Now, Long Short Term Memory (LSTM)
 - What about the Output?
- What about Gated Recurrent Units (GRU) units?

4

Deeper Architectures with RNN's

- Introduction
- Deep Architectures for Better Learning
- Deep Input-to-Hidden Function
- Deep Transition Architectures
- Conclusions

History

They were proposed as a simplification of the LSTM

- In 2014, Kyunghyun Cho et al. put forward a simplified variant called Gated recurrent unit (GRU)

Something Notable

- The GRU is like a long short-term memory (LSTM) with forget gate...
 - ▶ but has fewer parameters than LSTM, as it lacks an output gate

History

They were proposed as a simplification of the LSTM

- In 2014, Kyunghyun Cho et al. put forward a simplified variant called Gated recurrent unit (GRU)

Something Notable

- The GRU is like a long short-term memory (LSTM) with forget gate...
 - ▶ but has fewer parameters than LSTM, as it lacks an output gate

Gated Recurrent Units

Architecture

$$z_t = \sigma [W_z \mathbf{x}_t + U_z \mathbf{h}_{t-1} + \mathbf{b}_z] \text{ (Update Gate)}$$


$$r_t = \sigma [W_r \mathbf{x}_t + U_r \mathbf{h}_{t-1} + \mathbf{b}_r] \text{ (Reset Gate)}$$

$$\hat{\mathbf{h}}_t = \tanh [W_h \mathbf{x}_t + U_h r_t \odot \mathbf{h}_{t-1} + \mathbf{b}_h]$$

$$\mathbf{h}_t = (1 - z_t) \odot \mathbf{h}_{t-1} + z_t \odot \hat{\mathbf{h}}_t$$

Graphically, we have the architecture

GRU Architecture



Main Observations

There is a gate used to combine the state h_{t-1} ,

- The z_t gate that basically uses the information of the input and the previous state to decide how to update

$$h_t = (1 - z_t) \odot h_{t-1} + z_t \odot \hat{h}_t$$

The intermediate step \hat{h}_t

- A bounded version of the possible state h_t

Main Observations

There is a gate used to combine the state \mathbf{h}_{t-1} ,

- The z_t gate that basically uses the information of the input and the previous state to decide how to update

$$\mathbf{h}_t = (1 - z_t) \odot \mathbf{h}_{t-1} + z_t \odot \hat{\mathbf{h}}_t$$

The intermediate step $\hat{\mathbf{h}}_t$

- A bounded version of the possible state \mathbf{h}_t

Next

We have that a reset gate

$$\mathbf{r}_t = \sigma [W_r \mathbf{x}_t + U_r \mathbf{h}_{t-1} + \mathbf{b}_r]$$

- To update

$$\hat{\mathbf{h}}_t = \tanh [W_h \mathbf{x}_t + U_h \mathbf{r}_t \odot \mathbf{h}_{t-1} + \mathbf{b}_h]$$

However

It has been shown that

- As shown by Gail Weiss, Yoav Goldberg, Eran Yahav, the LSTM is "strictly stronger" than the GRU

LSTM can perform unbounded counting [16]

- The GRU cannot.
 - ▶ It simulates a counting machine used for theoretical CS

Denny Britz, Anne Goldie, Minh-Thang Luong, Quoc Le of Google Brain

- LSTM cells consistently outperform GRU cells in "the first large-scale analysis of architecture variations for Neural Machine Translation."

However

It has been shown that

- As shown by Gail Weiss, Yoav Goldberg, Eran Yahav, the LSTM is "strictly stronger" than the GRU

LSTM can perform unbounded counting[16]

- The GRU cannot.
 - ▶ It simulates a counting machine used for theoretical CS

Denny Britz, Anne Goldie, Minh-Thang Luong, Quoc Le of Google Brain

- LSTM cells consistently outperform GRU cells in "the first large-scale analysis of architecture variations for Neural Machine Translation"

However

It has been shown that

- As shown by Gail Weiss, Yoav Goldberg, Eran Yahav, the LSTM is "strictly stronger" than the GRU

LSTM can perform unbounded counting[16]

- The GRU cannot.
 - ▶ It simulates a counting machine used for theoretical CS

Denny Britz, Anna Goldie, Minh-Thang Luong, Quoc Le of Google Brain

- LSTM cells consistently outperform GRU cells in "the first large-scale analysis of architecture variations for Neural Machine Translation."

Outline

1

Introduction

- History
- State-Space Model
- Back to the RNN Equations
- Introducing the Cost Function
- Other Cost Functions

2

Training a Vanilla RNN Model

- The Final RNN Model
- Back-Propagation Through Time (BPTT)
- Deriving $\frac{\partial L(t)}{\partial V_{os}}$
- Vanishing and Exploding Gradients
 - The Analysis of the Exploding and Vanishing Gradient
- Signal Propagation
 - The Stability Frontier
- Truncated BPTT
- Initialization
 - Hidden State

3

Modern Recurrent Architectures

- Now, Long Short Term Memory (LSTM)
 - What about the Output?
- What about Gated Recurrent Units (GRU) units?

4

Deeper Architectures with RNN's

Introduction

- Deep Architectures for Better Learning
- Deep Input-to-Hidden Function
- Deep Transition Architectures
- Conclusions

Given that we want to do sequence modeling

Stock Options



Predict next phase

- Question: If I am a man ?
 - Prediction: you are homo sapiens

Given that we want to do sequence modeling

Stock Options




Predict next phrase

- Question: If I am a man ?
 - ▶ Prediction: you are homo sapiens

What do we have in this sequences of data?

Sequences have different lengths

- We need to handle variable-length sequences



Furthermore

We need to track long-term dependencies



Not only that

Maintain information about order

- “We have a mother living in Yucatan, Mexico”

Share information across the sequence

- Do you remember the state h_t ?

Not only that

Maintain information about order

- “We have a mother living in Yucatan, Mexico”

Share parameters across the sequence

- Do you remember the state h_t ?

However

There is a need to increase their power

- Given the amounts of data we have right now

Then there is a tendency to start using the Recurrent Neural Networks

- As cells to be stacked for bigger systems [17, 18]

This is based in the following idea [19]:

- Hypothesis, hierarchical model can be exponentially more efficient at representing some functions than a shallow one.

However

There is a need to increase their power

- Given the amounts of data we have right know

Then there is a tendency to start using the Recurrent Neural Networks

- As cells to be stacked for bigger systems [17, 18]

This is based on the following idea [19]

- Hypothesis, hierarchical model can be exponentially more efficient at representing some functions than a shallow one.

However

There is a need to increase their power

- Given the amounts of data we have right know

Then there is a tendency to start using the Recurrent Neural Networks

- As cells to be stacked for bigger systems [17, 18]

This is based in the following idea [19]

- Hypothesis, hierarchical model can be exponentially more efficient at representing some functions than a shallow one.

In the case of RNN's

Certain Transitions are not Deep

- They are only results of a **linear projection** followed by an element-wise nonlinearity.

They are

- Hidden-to-hidden $h_{t-1} \rightarrow h_t$
- Hidden-to-output $h_t \rightarrow y_t$
- Input-to-hidden $x_{t-1} \rightarrow h_t$

Meaning

- They are all shallow in the sense that there exists no intermediate, nonlinear hidden layer.

In the case of RNN's

Certain Transitions are not Deep

- They are only results of a **linear projection** followed by an element-wise nonlinearity.

They are

- Hidden-to-hidden $\mathbf{h}_{t-1} \rightarrow \mathbf{h}_t$
- Hidden-to-output $\mathbf{h}_t \rightarrow \mathbf{y}_t$
- Input-to-hidden $\mathbf{x}_{t-1} \rightarrow \mathbf{h}_t$

Meaning

- They are all shallow in the sense that there exists no intermediate, nonlinear hidden layer.

In the case of RNN's

Certain Transitions are not Deep

- They are only results of a **linear projection** followed by an element-wise nonlinearity.

They are

- Hidden-to-hidden $\mathbf{h}_{t-1} \rightarrow \mathbf{h}_t$
- Hidden-to-output $\mathbf{h}_t \rightarrow \mathbf{y}_t$
- Input-to-hidden $\mathbf{x}_{t-1} \rightarrow \mathbf{h}_t$

Meaning

- They are all shallow in the sense that there exists no intermediate, nonlinear hidden layer.

Outline

1

Introduction

- History
- State-Space Model
- Back to the RNN Equations
- Introducing the Cost Function
- Other Cost Functions

2

Training a Vanilla RNN Model

- The Final RNN Model
- Back-Propagation Through Time (BPTT)
- Deriving $\frac{\partial L(t)}{\partial V_{os}}$
- Vanishing and Exploding Gradients
 - The Analysis of the Exploding and Vanishing Gradient
- Signal Propagation
 - The Stability Frontier
- Truncated BPTT
- Initialization
 - Hidden State

3

Modern Recurrent Architectures

- Now, Long Short Term Memory (LSTM)
 - What about the Output?
- What about Gated Recurrent Units (GRU) units?

4

Deeper Architectures with RNN's

- Introduction
- **Deep Architectures for Better Learning**
- Deep Input-to-Hidden Function
- Deep Transition Architectures
- Conclusions

Gave the following Hypothesis

- In sampling algorithms (Markov Chains and MCMC techniques) suffer from a fundamental problem
 - ▶ Given unconnected or weakly connected regions of distributions

We have that

- it is difficult for the Markov chain to jump from one mode of the distribution to another, when these are separated by large low-density regions

This means that we have a slow mixing of samples

- In order to represent distributions

Gave the following Hypothesis

- In sampling algorithms (Markov Chains and MCMC techniques) suffer from a fundamental problem
 - ▶ Given unconnected or weakly connected regions of distributions

We have that

- it is difficult for the Markov chain to jump from one mode of the distribution to another, when these are separated by large low-density regions

This means that we have a slow mixing of samples

- In order to represent distributions

Gave the following Hypothesis

- In sampling algorithms (Markov Chains and MCMC techniques) suffer from a fundamental problem
 - ▶ Given unconnected or weakly connected regions of distributions

We have that


- it is difficult for the Markov chain to jump from one mode of the distribution to another, when these are separated by large low-density regions

This means that we have a slow mixing of samples

- In order to represent distributions

Example

A Big Problem



The Main Problem

We have that

- Slow mixing means that many consecutive samples tend to be correlated
 - ▶ They belong to the same mode of the mixture

What

- Jumping around in the MCMC method is quite slow and scarce

The Main Problem

We have that

- Slow mixing means that many consecutive samples tend to be correlated
 - ▶ They belong to the same mode of the mixture

Why?

- Jumping around in the MCMC method is quite slow and scarce

Implications in Learning Algorithms

Given that some form of sampling is at the core of many learning algorithms

- For example, to estimate the log-likelihood gradient

Therefore, at the beginning of learning

- Mixing is therefore initially easy

However, as the model improves

- its corresponding distribution sharpens and mixing becomes slower

Implications in Learning Algorithms

Given that some form of sampling is at the core of many learning algorithms

- For example, to estimate the log-likelihood gradient

Therefore, at the beginning of learning

- Mixing is therefore initially easy

However, as the model improves

- its corresponding distribution sharpens and mixing becomes slower

Implications in Learning Algorithms

Given that some form of sampling is at the core of many learning algorithms

- For example, to estimate the log-likelihood gradient

Therefore, at the beginning of learning


- Mixing is therefore initially easy

However as the model improves

- its corresponding distribution sharpens and mixing becomes slower

Basically

We have slow downs on the learning in shallow models



Outline

1

Introduction

- History
- State-Space Model
- Back to the RNN Equations
- Introducing the Cost Function
- Other Cost Functions

2

Training a Vanilla RNN Model

- The Final RNN Model
- Back-Propagation Through Time (BPTT)
- Deriving $\frac{\partial L(t)}{\partial V_{os}}$
- Vanishing and Exploding Gradients
 - The Analysis of the Exploding and Vanishing Gradient
- Signal Propagation
 - The Stability Frontier
- Truncated BPTT
- Initialization
 - Hidden State

3

Modern Recurrent Architectures

- Now, Long Short Term Memory (LSTM)
 - What about the Output?
- What about Gated Recurrent Units (GRU) units?

4

Deeper Architectures with RNN's

- Introduction
- Deep Architectures for Better Learning
- **Deep Input-to-Hidden Function**
- Deep Transition Architectures
- Conclusions

Therefore

We need to build deeper structures to reach more capabilities

- For example the vector representation of documents

Here a extra layer of representation can be used for doing representation

- For Example, Mikolov et al. [21]

Therefore

We need to build deeper structures to reach more capabilities


- For example the vector representation of documents

Here a extra layer of representation can be used for doing representation

- For Example, Mikolov et al. [21]

Basically a shallow network before the main architecture

An Encoder Layer before a GRU



The equations

They will look like

$$w_{t'}^{encoded} = \sigma [Aw_t + b_{w_t}]$$

$$x_t = \sigma [Bw_{t'}^{encoded} + b_{x_t}]$$

$$z_t = \sigma [W_z x_t + U_z h_{t-1} + b_z] \text{ (Update Gate)}$$

$$r_t = \sigma [W_z x_t + U_z h_{t-1} + b_z] \text{ (Reset Gate)}$$

$$\hat{h}_t = \tanh [W_h x_t + U_h r_t \odot h_{t-1} + b_h]$$

$$h_t = (1 - z_t) \odot h_{t-1} + z_t \odot \hat{h}_t$$

Outline

1

Introduction

- History
- State-Space Model
- Back to the RNN Equations
- Introducing the Cost Function
- Other Cost Functions

2

Training a Vanilla RNN Model

- The Final RNN Model
- Back-Propagation Through Time (BPTT)
- Deriving $\frac{\partial L(t)}{\partial V_{os}}$
- Vanishing and Exploding Gradients
 - The Analysis of the Exploding and Vanishing Gradient
- Signal Propagation
 - The Stability Frontier
- Truncated BPTT
- Initialization
 - Hidden State

3

Modern Recurrent Architectures

- Now, Long Short Term Memory (LSTM)
 - What about the Output?
- What about Gated Recurrent Units (GRU) units?

4

Deeper Architectures with RNN's

- Introduction
- Deep Architectures for Better Learning
- Deep Input-to-Hidden Function
- **Deep Transition Architectures**
- Conclusions

Deep Transition Architectures

In a deep transition RNN (DT-RNN)

- At each time step the next state is computed by the sequential application of multiple transition layers.

For example in Memristor system [22]

- They use GRU transitions blocks under independent trainable parameters

With a caveat:

- The hidden state output is used as the input state on the next one

Deep Transition Architectures

In a deep transition RNN (DT-RNN)

- At each time step the next state is computed by the sequential application of multiple transition layers.

For example in Nematus system [22]

- They use GRU transitions blocks under independent trainable parameters

With a Caveat

- The hidden state output is used as the input state on the next one

Deep Transition Architectures

In a deep transition RNN (DT-RNN)

- At each time step the next state is computed by the sequential application of multiple transition layers.

For example in Nematus system [22]

- They use GRU transitions blocks under independent trainable parameters

With a Caveat

- The hidden state output is used as the input state on the next one

For example, at the encoder phase

For the i^{th} source word in the forward direction, we have $\mathbf{h}_i = \mathbf{h}_{i,L_s}$

$$\mathbf{h}_{i,1} = GRU_1(\mathbf{x}_1, \mathbf{h}_{i-1,L_s})$$

$$\mathbf{h}_{i,k} = GRU_k(0, \mathbf{h}_{i,k-1}) \text{ for } 1 < k \leq L_s$$

The sequence word is reversed and you have a backward state then

$$\mathbf{c} \equiv [\vec{\mathbf{h}}_{i,L_s}, \overleftarrow{\mathbf{h}}_{i,L_s}]$$

For example, at the encoder phase

For the i^{th} source word in the forward direction, we have $\mathbf{h}_i = \mathbf{h}_{i,L_s}$

$$\mathbf{h}_{i,1} = GRU_1(\mathbf{x}_1, \mathbf{h}_{i-1,L_s})$$

$$\mathbf{h}_{i,k} = GRU_k(0, \mathbf{h}_{i,k-1}) \text{ for } 1 < k \leq L_s$$

The sequence word is reversed and you have a backward state then

$$C \equiv [\vec{\mathbf{h}}_{i,L_s}, \overleftarrow{\mathbf{h}}_{i,L_s}]$$

Then

Decoder phase uses the outputs from the previous GRU and something called attention (We will look at this latter)

$$\mathbf{s}_{j,1} = GRU_1(\mathbf{y}_{j-1}, \mathbf{s}_{j-1}, L_t)$$

$$\mathbf{s}_{j,2} = GRU_2(ATT, \mathbf{s}_{j-1}, L_t)$$

$$\mathbf{s}_{j,k} = GRU_k(0, L_t) \text{ for } 2 < k \leq L_t$$

Then, the target word state

- It is used by a feed-forward neural network to predict the current target network

Then

Decoder phase uses the outputs from the previous GRU and something called attention (We will look at this latter)

$$\mathbf{s}_{j,1} = GRU_1(\mathbf{y}_{j-1}, \mathbf{s}_{j-1}, L_t)$$

$$\mathbf{s}_{j,2} = GRU_2(ATT, \mathbf{s}_{j-1}, L_t)$$


$$\mathbf{s}_{j,k} = GRU_k(0, L_t) \text{ for } 2 < k \leq L_t$$

Then, the target word state $\mathbf{s}_j \equiv \mathbf{s}_{j,L_t}$

- It is used by a feed-forward neural network to predict the current target network

Deep Transition Decoder

We have the following depiction of the architecture



Outline

1

Introduction

- History
- State-Space Model
- Back to the RNN Equations
- Introducing the Cost Function
- Other Cost Functions

2

Training a Vanilla RNN Model

- The Final RNN Model
- Back-Propagation Through Time (BPTT)
- Deriving $\frac{\partial L(t)}{\partial V_{os}}$
- Vanishing and Exploding Gradients
 - The Analysis of the Exploding and Vanishing Gradient
- Signal Propagation
 - The Stability Frontier
- Truncated BPTT
- Initialization
 - Hidden State

3

Modern Recurrent Architectures

- Now, Long Short Term Memory (LSTM)
 - What about the Output?
- What about Gated Recurrent Units (GRU) units?

4

Deeper Architectures with RNN's

- Introduction
- Deep Architectures for Better Learning
- Deep Input-to-Hidden Function
- Deep Transition Architectures
- Conclusions

There are many other examples

Basically

- We are far from the classic methods as
 - 1 Autoregressive integrated moving average (ARMA)
 - 2 Auto Regressive Integrated Moving Average (ARIMA)
 - 3 etc

These RNN architectures are taking the prediction of time series

- To another level!!!

There are many other examples

Basically

- We are far from the classic methods as
 - ① Autoregressive integrated moving average (ARMA)
 - ② Auto Regressive Integrated Moving Average (ARIMA)
 - ③ etc

These RNN architectures are taking the prediction of time series

- To another level!!!

- [1] O. L. R. Jacobs, “Introduction to control theory,” 1974.
- [2] A. Robinson and F. Fallside, *The utility driven dynamic error propagation network*.
University of Cambridge Department of Engineering, 1987.
- [3] P. J. Werbos *et al.*, “Backpropagation through time: what it does and how to do it,” *Proceedings of the IEEE*, vol. 78, no. 10, pp. 1550–1560, 1990.
- [4] G. Chen, “A gentle tutorial of recurrent neural network with error backpropagation,” *arXiv preprint arXiv:1610.02583*, 2016.
- [5] B. W. Bader and T. G. Kolda, “Algorithm 862: Matlab tensor classes for fast algorithm prototyping,” *ACM Trans. Math. Softw.*, vol. 32, Dec. 2006.
- [6] J. Pennington, S. S. Schoenholz, and S. Ganguli, “The emergence of spectral universality in deep networks,” *arXiv preprint arXiv:1802.09979*, 2018.

- [7] B. Poole, S. Lahiri, M. Raghu, J. Sohl-Dickstein, and S. Ganguli, “Exponential expressivity in deep neural networks through transient chaos,” *arXiv preprint arXiv:1606.05340*, 2016.
- [8] S. S. Schoenholz, J. Gilmer, S. Ganguli, and J. Sohl-Dickstein, “Deep information propagation,” *arXiv preprint arXiv:1611.01232*, 2016.
- [9] R. J. Williams and D. Zipser, “Gradient-based learning algorithms for recurrent,” *Backpropagation: Theory, architectures, and applications*, vol. 433, 1995.
- [10] R. J. Williams and J. Peng, “An efficient gradient-based algorithm for on-line training of recurrent network trajectories,” *Neural computation*, vol. 2, no. 4, pp. 490–501, 1990.
- [11] J. L. Elman, “Finding structure in time,” *Cognitive science*, vol. 14, no. 2, pp. 179–211, 1990.

- [12] T. Mikolov, M. Karafiát, L. Burget, J. Černocký, and S. Khudanpur, “Recurrent neural network based language model,” in *Eleventh annual conference of the international speech communication association*, 2010.
- [13] H.-G. Zimmermann, C. Tietz, and R. Grothmann, “Forecasting with recurrent neural networks: 12 tricks,” in *Neural Networks: Tricks of the Trade*, pp. 687–707, Springer, 2012.
- [14] S. Hochreiter and J. Schmidhuber, “Long short-term memory,” *Neural computation*, vol. 9, no. 8, pp. 1735–1780, 1997.
- [15] F. A. Gers, J. Schmidhuber, and F. Cummins, “Learning to forget: Continual prediction with lstm,” 1999.
- [16] G. Weiss, Y. Goldberg, and E. Yahav, “On the practical computational power of finite precision rnns for language recognition,” *CoRR*, vol. abs/1805.04908, 2018.

- [17] R. Pascanu, C. Gulcehre, K. Cho, and Y. Bengio, “How to construct deep recurrent neural networks,” *arXiv preprint arXiv:1312.6026*, 2013.
- [18] A. V. M. Barone, J. Helcl, R. Sennrich, B. Haddow, and A. Birch, “Deep architectures for neural machine translation,” *arXiv preprint arXiv:1707.07631*, 2017.
- [19] Y. Bengio *et al.*, “Learning deep architectures for ai,” *Foundations and trends® in Machine Learning*, vol. 2, no. 1, pp. 1–127, 2009.
- [20] Y. Bengio, G. Mesnil, Y. Dauphin, and S. Rifai, “Better mixing via deep representations,” in *International conference on machine learning*, pp. 552–560, 2013.
- [21] T. Mikolov, K. Chen, G. Corrado, and J. Dean, “Efficient estimation of word representations in vector space,” *arXiv preprint arXiv:1301.3781*, 2013.

- [22] R. Sennrich, O. Firat, K. Cho, A. Birch, B. Haddow, J. Hitschler, M. Junczys-Dowmunt, S. Läubli, A. V. M. Barone, J. Mokry, *et al.*, “Nematus: a toolkit for neural machine translation,” *arXiv preprint arXiv:1703.04357*, 2017.