

Navigation



Machine Learning Mastery

Making Developers Awesome at Machine Learning

Click to Take the FREE Crash-Course

Search... Q

14 Different Types of Learning in Machine Learning

by Jason Brownlee on November 11, 2019 in Start Machine Learning



Last Updated on November 11, 2019

Machine learning is a large field of study that overlaps with and inherits ideas from many related fields such as artificial intelligence.

The focus of the field is learning, that is, acquiring skills or knowledge from experience. Most commonly, this means synthesizing useful concepts from historical data.


As such, there are many different types of learning that you may encounter as a practitioner in the field of machine learning: from whole fields of study to specific techniques.

In this post, you will discover a gentle introduction to the different types of learning that you may encounter in the field of machine learning.

After reading this post, you will know:

- Fields of study, such as supervised, unsupervised, and reinforcement learning.
- Hybrid types of learning, such as semi-supervised and self-supervised learning.
- Broad techniques, such as active, online, and transfer learning.

Let's get started.



Types of Learning

Given that the focus of the field of machine learning is "*learning*," there are many types that you may encounter as a practitioner.

Some types of learning describe whole subfields of study comprised of many different types of algorithms such as "supervised learning." Others describe powerful techniques that you can use on your projects, such as "transfer learning."

There are perhaps 14 types of learning that you must be familiar with as a machine learning practitioner; they are:

Learning Problems

- 1. Supervised Learning
- 2. Unsupervised Learning
- 3. Reinforcement Learning

Hybrid Learning Problems

- 4. Semi-Supervised Learning
- 5. Self-Supervised Learning
- 6. Multi-Instance Learning

Statistical Inference

- 7. Inductive Learning
- 8. Deductive Inference
- 9. Transductive Learning

Learning Techniques

- 10. Multi-Task Learning
- 11. Active Learning
- 12. Online Learning
- 13. Transfer Learning
- 14. Ensemble Learning

In the following sections, we will take a closer look at e

Did I miss an important type of learning?

Let me know in the comments below.

Learning Problems

First, we will take a closer look at three main types of learning problems in machine learning: supervised, unsupervised, and reinforcement learning.

1. Supervised Learning


Supervised learning describes a class of problem that involves using a model to learn a mapping between input examples and the target variable.

Applications in which the training data comprises examples of the input vectors along with their corresponding target vectors are known as supervised learning problems.

Page 3, Pattern Recognition and Machine Learning, 2006.

Models are fit on training data comprised of inputs and outputs and used to make predictions on test sets where only the inputs are provided and the outputs from the model are compared to the withheld target variables and used to estimate the skill of the model.

Learning is a search through the space of possible hypotheses for one that will perform well, even on new examples beyond the training set. To measure the accuracy of a hypothesis we give it a test set of examples that are distinct find Your Start in Machine Learning



— Page 695, Artificial Intelligence: A Modern Approach, 3rd edition, 2015.

There are two main types of supervised learning problems: they are classification that involves predicting a class label and regression that involves predicting a numerical value.

- Classification: Supervised learning problem that involves predicting a class label.
- Regression: Supervised learning problem that involves predicting a numerical label.

Both classification and regression problems may have one or more input variables and input variables may be any data type, such as numerical or categorical.


An example of a classification problem would be the MNIST handwritten digits dataset where the inputs are images of handwritten digits (pixel data) and the output

(numbers 0 to 9).

An example of a regression problem would be the Bos variables that describe a neighborhood and the output

Some machine learning algorithms are described as "designed for supervised machine learning problems. Fixed vector machines, and many more.

Our goal is to find a useful approximation f(x) trelationship between the inputs and outputs



— Page 28, The Elements of Statistical Learning: Data Mining, Inference, and Prediction, 2nd edition, 2016.

Algorithms are referred to as "supervised" because they learn by making predictions given examples of input data, and the models are supervised and corrected via an algorithm to better predict the expected target outputs in the training dataset.

The term supervised learning originates from the view of the target y being provided by an instructor or teacher who shows the machine learning system what to do.

— Page 105, Deep Learning, 2016.

Some algorithms may be specifically designed for classification (such as logistic regression) or regression (such as linear regression) and some may be used for both types of problems with minor modifications (such as artificial neural networks).

2. Unsupervised Learning

Unsupervised learning describes a class of problems that involves using a model to describe or extract relationships in data.

Compared to supervised learning, unsupervised learning operates upon only the input data without outputs or target variables. As such, unsupervised learning does not have a teacher correcting the model, as in the case of supervised learning.

56


In unsupervised learning, there is no instructor or teacher, and the algorithm must learn to make sense of the data without this guide.

— Page 105, Deep Learning, 2016.

There are many types of unsupervised learning, althousencountered by a practitioner: they are clustering that estimation that involves summarizing the distribution of

- Clustering: Unsupervised learning problem that
- Density Estimation: Unsupervised learning prob data.

An example of a clustering algorithm is k-Means wher data. An example of a density estimation algorithm is groups of closely related data samples to estimate the



The most common unsupervised learning task is clustering: detecting potentially useful clusters of input examples. For example, a taxi agent might gradually develop a concept of "good traffic days" and "bad traffic days" without ever being given labeled examples of each by a teacher.

— Pages 694-695, Artificial Intelligence: A Modern Approach, 3rd edition, 2015.

Clustering and density estimation may be performed to learn about the patterns in the data.

Additional unsupervised methods may also be used, such as visualization that involves graphing or plotting data in different ways and projection methods that involves reducing the dimensionality of the data.

- Visualization: Unsupervised learning problem that involves creating plots of data.
- Projection: Unsupervised learning problem that involves creating lower-dimensional representations
 of data.

An example of a visualization technique would be a scatter plot matrix that creates one scatter plot of each pair of variables in the dataset. An example of a projection method would be Principal Component Analysis that involves summarizing a dataset in terms of eigenvalues and eigenvectors, with linear dependencies removed.



The goal in such unsupervised learning problems may be to discover groups of similar examples within the data, where it is called clustering, or to determine the distribution of data within the input space, known as density estimation, or to project the data from a high-dimensional space down to two or three dimensions for the purpose of visualization.


— Page 3, Pattern Recognition and Machine Learning, 2006.

3. Reinforcement Learning

Reinforcement learning describes a class of problems where an agent operates in an environment and must *learn* to operate using feedback.

- Reinforcement learning is learning what to do maximize a numerical reward signal. The learn must discover which actions yield the most rev
- Page 1, Reinforcement Learning: An Introduction, 2

The use of an environment means that there is no fixe an agent is required to achieve, actions they may perf goal.



Some machine learning algorithms do not just

reinforcement learning algorithms interact with an environment, so there is a feedback loop between the learning system and its experiences.

- Page 105, Deep Learning, 2016.

It is similar to supervised learning in that the model has some response from which to learn, although the feedback may be delayed and statistically noisy, making it challenging for the agent or model to connect cause and effect.

An example of a reinforcement problem is playing a game where the agent has the goal of getting a high score and can make moves in the game and received feedback in terms of punishments or rewards.

In many complex domains, reinforcement learning is the only feasible way to train a program to perform at high levels. For example, in game playing, it is very hard for a human to provide accurate and consistent evaluations of large numbers of positions, which would be needed to train an evaluation function directly from examples. Instead, the program can be told when it has won or lost, and it can use this information to learn an evaluation function that gives reasonably accurate estimates of the probability of winning from any given position.

- Page 831, Artificial Intelligence: A Modern Approac

Impressive recent results include the use of reinforcement in Google's AlphaGo in out-performing the world's top Go player.

Some popular examples of reinforcement learning algorithms include Q-learning, temporal-difference learning, and deep reinforcement learning.

Hybrid Learning Problems

The lines between unsupervised and supervised learning is blurry, and there are many hybrid approaches that draw from each field of study.

In this section, we will take a closer look at some of the more common hybrid fields of study: semi-

supervised, self-supervised, and multi-instance learnir

4. Semi-Supervised Learning

Semi-supervised learning is supervised learning wher examples and a large number of unlabeled examples.

The goal of a semi-supervised learning model is to mathe labelled data like in supervised learning.

In semi-supervised learning we are given a few of a large collection of unlabeled examples. Extruths that we hope for.



— Page 695, Artificial Intelligence: A Modern Approach, 3rd edition, 2015.

Making effective use of unlabelled data may require the use of or inspiration from unsupervised methods such as clustering and density estimation. Once groups or patterns are discovered, supervised methods or ideas from supervised learning may be used to label the unlabeled examples or apply labels to unlabeled representations later used for prediction.

Unsupervised learning can provide useful cues for how to group examples in representation space. Examples that cluster tightly in the input space should be mapped to similar representations.

— Page 243, Deep Learning, 2016.

It is common for many real-world supervised learning problems to be examples of semi-supervised learning problems given the expense or computational cost for labeling examples. For example, classifying photographs requires a dataset of photographs that have already been labeled by human operators.

Many problems from the fields of computer vision (image data), natural language processing (text data), and automatic speech recognition (audio data) fall into this category and cannot be easily addressed using standard supervised learning methods.

... in many practical applications labeled data is very scarce but unlabeled data is plentiful. "Semisupervised" learning attempts to improve the accuracy of supervised learning by exploiting information in unlabeled data. This sounds like magic, but it can work!

— Page 467, Data Mining: Practical Machine Learning Tools and Techniques, 4th edition, 2016.


5. Self-Supervised Learning

Self-supervised learning refers to an unsupervised learning problem in order to apply supervised learning

Supervised learning algorithms are used to solve an a or representation that can be used in the solution of the

The self-supervised learning framework requirements pretext learning task such as predicting context can be computed without supervision.

Revisiting Self-Supervised Visual Representation L



START MY EMAIL COURSE

A common example of self-supervised learning is computer vision where a corpus of unlabeled images is available and can be used to train a supervised model, such as making images grayscale and having a model predict a color representation (colorization) or removing blocks of the image and have a model predict the missing parts (inpainting).

In discriminative self-supervised learning, which is the main focus of this work, a model is trained on an auxiliary or 'pretext' task for which ground-truth is available for free. In most cases, the pretext task involves predicting some hidden portion of the data (for example, predicting color for gray-scale images

Scaling and Benchmarking Self-Supervised Visual Representation Learning, 2019.

A general example of self-supervised learning algorithms are autoencoders. These are a type of neural network that is used to create a compact or compressed representation of an input sample. They achieve this via a model that has an encoder and a decoder element separated by a bottleneck that represents the internal compact representation of the input.

An autoencoder is a neural network that is trained to attempt to copy its input to its output.

Internally, it has a hidden layer h that describe

Your Start in Machine Learning

- Page 502, Deep Learning, 2016.

These autoencoder models are trained by providing the input to the model as both input and the target output, requiring that the model reproduce the input by first encoding it to a compressed representation then decoding it back to the original. Once trained, the decoder is discarded and the encoder is used as needed to create compact representations of input.


Although autoencoders are trained using a supervised learning method, they solve an unsupervised learning problem, namely, they are a type of projection method for reducing the dimensionality of input data.

Traditionally, autoencoders were used for dime

- Page 502, Deep Learning, 2016.

Another example of self-supervised learning is general generative models that are most commonly used for confundable examples from the target domain.

GAN models are trained indirectly via a separate discr from the domain as real or fake (generated), the resulencourage it to generate more realistic photos on the



The generator network directly produces samples [...]. Its adversary, the discriminator network, attempts to distinguish between samples drawn from the training data and samples drawn from the generator. The discriminator emits a probability value given by $d(x; \theta(d))$, indicating the probability that x is a real training example rather than a fake sample drawn from the model.

— Page 699, Deep Learning, 2016.

6. Multi-Instance Learning

Multi-instance learning is a supervised learning problem where individual examples are unlabeled; instead, bags or groups of samples are labeled.

In multi-instance learning, an entire collection of examples is labeled as containing or not containing an example of a class, but the individual members of the collection are not labeled.

— Page 106, Deep Learning, 2016.

Instances are in "bags" rather than sets because a given instance may be present one or more times, e.g. duplicates.

Modeling involves using knowledge that one or some of the instances in a bag are associated with a target label, and to predict the label for new bags in the future given their composition of multiple unlabeled examples.

In supervised multi-instance learning, a class label is associated with each bag, and the goal of learning is to determine how the class can be inferred from the instances that make up the bag.

— Page 156, Data Mining: Practical Machine Learning Tools and Techniques, 4th edition, 2016.

Simple methods, such as assigning class labels to individual instances and using standard supervised learning algorithms, often work as a good first step.


Statistical Inference

Inference refers to reaching an outcome or decision.

In machine learning, fitting a model and making a pred

There are different paradigms for inference that may k machine learning algorithms work or how some learning

Some examples of approaches to learning are inductive inference.



7. Inductive Learning

Inductive learning involves using evidence to determine the outcome.

Inductive reasoning refers to using specific cases to determine general outcomes, e.g. specific to general.

Most machine learning models learn using a type of inductive inference or inductive reasoning where general rules (the model) are learned from specific historical examples (the data).

... the problem of induction, which is the problem of how to draw general conclusions about the future from specific observations from the past.

Page 77, Machine Learning: A Probabilistic Perspective, 2012.

Fitting a machine learning model is a process of induction. The model is a generalization of the specific examples in the training dataset.

A model or hypothesis is made about the problem using the training data, and it is believed to hold over new unseen data later when the model is used.



Lacking any further information, our assumption is that the best hypothesis regarding unseen instances is the hypothesis that best fits the observed training data. This is the fundamental assumption of inductive learning ...

— Page 23, Machine Learning, 1997.

8. Deductive Inference

Deduction or deductive inference refers to using general rules to determine specific outcomes.


We can better understand induction by contrasting it with deduction.

Deduction is the reverse of induction. If induction is go going from the general to the specific.

... the simple observation that induction is just

Page 291, Machine Learning, 1997.

Deduction is a top-down type of reasoning that seeks conclusion, whereas induction is a bottom-up type of routcome.



In the context of machine learning, once we use induction or deduction or deductive inference.

9. Transductive Learning

Transduction or transductive learning is used in the field of statistical learning theory to refer to predicting specific examples given specific examples from a domain.

It is different from induction that involves learning general rules from specific examples, e.g. specific to specific.

66

Induction, deriving the function from the given data. Deduction, deriving the values of the given function for points of interest. Transduction, deriving the values of the unknown function for points of interest from the given data.

— Page 169, The Nature of Statistical Learning Theory, 1995.

Unlike induction, no generalization is required; instead, specific examples are used directly. This may, in fact, be a simpler problem than induction to solve.



The model of estimating the value of a function at a given point of interest describes a new concept of inference: moving from the particular to the particular. We call this type of inference transductive inference. Note that this concept of inference appears when one would like to get the best result from a restricted amount of information.

— Page 169, The Nature of Statistical Learning Theory, 1995.

A classical example of a transductive algorithm is the k-Nearest Neighbors algorithm that does not model the training data, but instead uses it directly each time a prediction is required.

For more on the topic of transduction, see the tutorial:

Gentle Introduction to Transduction in Machine Le


Contrasting Induction, Deduction, and

We can contrast these three types of inference in the


For example:

- Induction: Learning a general model from specifi
- Deduction: Using a model to make predictions.
- Transduction: Using specific examples to make

The image below summarizes these three different ap



START MY EMAIL COURSE



There are many techniques that are described as types of learning.

In this section, we will take a closer look at some of the more common methods.

This includes multi-task, active, online, transfer, and ensemble learning.

10. Multi-Task Learning

Multi-task learning is a type of supervised learning that involves fitting a model on one dataset that addresses multiple related problems.

It involves devising a model that can be trained on multiple related tasks in such a way that the performance of the model is improved by training across the tasks as compared to being trained on any single task.

Multi-task learning is a way to improve generalization by pooling the examples (which can be seen as soft constraints imposed on the parameters) arising out of several tasks.

— Page 244, Deep Learning, 2016.

Multi-task learning can be a useful approach to problem-solving when there is an abundance of input data labeled for one task that can be shared with another task with much less labeled data.



... we may want to learn multiple related models at the same time, which is known as multi-task learning. This will allow us to "borrow statistical strength" from tasks with lots of data and to share it with tasks with little data.

Page 231, Machine Learning: A Probabilistic Perspective, 2012.


For example, it is common for a multi-task learning problem to involve the same input patterns that may be used for multiple different outputs or supervised learning problems. In this setup, each output may be

predicted by a different part of the model, allowing the the same inputs.

In the same way that additional training example model towards values that generalize well, who of the model is more constrained towards good yielding better generalization.

— Page 244, Deep Learning, 2016.

A popular example of multi-task learning is where the representation of words in text that is then shared acrosupervised learning tasks.



11. Active Learning

Active learning is a technique where the model is able to query a human user operator during the learning process in order to resolve ambiguity during the learning process.



Active learning: The learner adaptively or interactively collects training examples, typically by querying an oracle to request labels for new points.

— Page 7, Foundations of Machine Learning, 2nd edition, 2018.

Active learning is a type of supervised learning and seeks to achieve the same or better performance of so-called "passive" supervised learning, although by being more efficient about what data is collected or used by the model.



The key idea behind active learning is that a machine learning algorithm can achieve greater accuracy with fewer training labels if it is allowed to choose the data from which it learns. An active learner may pose queries, usually in the form of unlabeled data instances to be labeled by an oracle (e.g., a human annotator).

Your Start in Machine Learning

Active Learning Literature Survey, 2009.

It is not unreasonable to view active learning as an approach to solving semi-supervised learning problems, or an alternative paradigm for the same types of problems.

... we see that active learning and semi-supervised learning attack the same problem from opposite directions. While semi-supervised methods exploit what the learner thinks it knows about the unlabeled data, active methods attempt to explore the unknown aspects. It is therefore natural to think about combining the two


Active Learning Literature Survey, 2009.

Active learning is a useful approach when there is not collect or label.

The active learning process allows the sampling of the number of samples and maximizes the effectiveness of

Active learning is often used in applications whe computational biology applications.

Page 7, Foundations of Machine Learning, 2nd edi



12. Online Learning

Online learning involves using the data available and updating the model directly before a prediction is required or after the last observation was made.

Online learning is appropriate for those problems where observations are provided over time and where the probability distribution of observations is expected to also change over time. Therefore, the model is expected to change just as frequently in order to capture and harness those changes.

Traditionally machine learning is performed offline, which means we have a batch of data, and we optimize an equation [...] However, if we have streaming data, we need to perform online learning, so we can update our estimates as each new data point arrives rather than waiting until "the end" (which may never occur).

— Page 261, Machine Learning: A Probabilistic Perspective, 2012.

This approach is also used by algorithms where there may be more observations than can reasonably fit into memory, therefore, learning is performed incrementally over observations, such as a stream of data.



Online learning is helpful when the data may be changing rapidly over time. It is also useful for applications that involve a large collection of data that is constantly growing, even if changes are gradual.

— Page 753, Artificial Intelligence: A Modern Approach, 3rd edition, 2015.

Generally, online learning seeks to minimize "regret," which is how well the model performed compared to how well it might have performed if all the available information was available as a batch.

In the theoretical machine learning community, the objective used in online learning is the regret, which is the averaged loss incurred relative to the best we could have gotten in hindsight using a single fixed parameter value

— Page 262, Machine Learning: A Probabilistic Persp

One example of online learning is so-called stochastic neural network.

The fact that stochastic gradient descent minir online learning case, where examples or minit

- Page 281, Deep Learning, 2016.

Your Start in Machine Learning

You can master applied Machine Learning without math or fancy degrees.


Find out how in this free and practical course.

Email Address

START MY EMAIL COURSE

13. Transfer Learning

Transfer learning is a type of learning where a model is first trained on one task, then some or all of the model is used as the starting point for a related task.



— Page 536, Deep Learning, 2016.

It is a useful approach on problems where there is a task related to the main task of interest and the related task has a large amount of data.

It is different from multi-task learning as the tasks are learned sequentially in transfer learning, whereas multi-task learning seeks good performance on all considered tasks by a single model at the same time in parallel.

... pretrain a deep convolutional net with 8 layer 1000 ImageNet object categories) and then in

of the first net. All the layers of the second network (with the upper layers initialized randomly) are then jointly trained to perform a different set of tasks (another subset of the 1000 ImageNet object categories), with fewer training examples than for the first set of tasks.

— Page 325, Deep Learning, 2016.


An example is image classification, where a predictive model, such as an artificial neural network, can be trained on a large corpus of general images, and the weights of the model can be used as a starting point when training on a smaller more specific dataset, such as dogs and cats. The features already learned by the model on the broader task, such as extracting lines and patterns, will be helpful on the new related task.

If there is significantly more data in the first set learn representations that are useful to quickly from P2. Many visual categories share low-lev of geometric changes, changes in lighting, etc.

— Page 536, Deep Learning, 2016.

As noted, transfer learning is particularly useful with m model can be used as a starting point for continued tra

For more on the topic of transfer learning, see the tutc



A Gentle Introduction to Transfer Learning for Deep Learning

14. Ensemble Learning

Ensemble learning is an approach where two or more modes are fit on the same data and the predictions from each model are combined.

The field of ensemble learning provides many ways of combining the ensemble members' predictions, including uniform weighting and weights chosen on a validation set.

— Page 472, Deep Learning, 2016.

The objective of ensemble learning is to achieve better performance with the ensemble of models as compared to any individual model. This involves both deciding how to create models used in the ensemble and how to best combine the predictions from the ensemble members.

Ensemble learning can be broken down into two tasks: developing a population of base learners from the training data, and then combining them to form the composite predictor.

— Page 605, The Elements of Statistical Learning: Data Mining, Inference, and Prediction, 2nd edition, 2016.

Ensemble learning is a useful approach for improving the predictive skill on a problem domain and to reduce the variance of stochastic learning algorithms, such as artificial neural networks.

Some examples of popular ensemble learning algorithms include: weighted average, stacked generalization (stacking), and bootstrap aggregation (bagging).

Bagging, boosting, and stacking have been developed over the last couple of decades, and their performance is often astonishingly good. Machine learning researchers have struggled to understand why.

Page 480, Data Mining: Practical Machine Learning

For more on the topic of ensemble learning, see the tu

Ensemble Learning Methods for Deep Learning N

Further Reading

This section provides more resources on the topic if you

Books

- Pattern Recognition and Machine Learning, 2006.
- Deep Learning, 2016.
- Reinforcement Learning: An Introduction, 2nd edition, 2018.
- Data Mining: Practical Machine Learning Tools and Techniques, 4th edition, 2016.
- The Elements of Statistical Learning: Data Mining, Inference, and Prediction, 2nd edition, 2016.
- Machine Learning: A Probabilistic Perspective, 2012.
- Machine Learning, 1997.
- The Nature of Statistical Learning Theory, 1995.
- Foundations of Machine Learning, 2nd edition, 2018.
- Artificial Intelligence: A Modern Approach, 3rd edition, 2015.

Papers

- Revisiting Self-Supervised Visual Representation Learning, 2019.
- Active Learning Literature Survey, 2009.

Tutorials

- Supervised and Unsupervised Machine Learning Algorithms
- Why Do Machine Learning Algorithms Work on No
- How Machine Learning Algorithms Work

Your Start in Machine Learning



You can master applied Machine Learning without math or fancy degrees.

Find out how in this free and practical course.

X

Email Address

START MY EMAIL COURSE


- Gentle Introduction to Transduction in Machine Learning
- A Gentle Introduction to Transfer Learning for Deep Learning
- Ensemble Learning Methods for Deep Learning Neural Networks

Videos

• Yann LeCun @EPFL - "Self-supervised learning: could machines learn like humans?" 2018

Articles

- · Supervised learning, Wikipedia.
- · Unsupervised learning, Wikipedia.
- · Reinforcement learning, Wikipedia.
- Semi-supervised learning, Wikipedia.
- Multi-task learning, Wikipedia.
- Multiple instance learning, Wikipedia.
- Inductive reasoning, Wikipedia.
- Deductive reasoning, Wikipedia.
- Transduction (machine learning), Wikipedia.
- Active learning (machine learning), Wikipedia.
- Online machine learning, Wikipedia.
- Transfer learning, Wikipedia.
- · Ensemble learning, Wikipedia.



Summary


In this post, you discovered a gentle introduction to the different types of learning that you may encounter in the field of machine learning.

Specifically, you learned:

- Fields of study, such as supervised, unsupervised, and reinforcement learning.
- Hybrid types of learning, such as semi-supervised and self-supervised learning.
- Broad techniques, such as active, online, and transfer learning.

Do you have any questions?

Ask your questions in the comments below and I will do my best to answer.





About Jason Brownlee


Jason Brownlee, PhD is a machine learning specialist who teaches developers how to get results with modern machine learning methods via hands-on tutorials.

View all posts by Jason Brownlee →

< A Gentle Introduction to Maximum a Posteriori (MAP) for Machine Learning

How to Save a NumPy Array to File for Machine Learning >

14 Responses to 14 Different Types of Learning in Machine Learning



More practical texts on reinforcement learning would be a good thing. The material in this space is either too specific on the theory or too much repetition on pre-existing open ai gym environments.



Jason Brownlee November 12, 2019 at 6:38 am #

REPLY 👆

Thanks.

The tech doesn't look useful for anything except games, e.g. the gym, and robotics. That's probably why there are no useful examples.



Avram November 12, 2019 at 9:34 am #

I don't agree with you. You can use RL in travel salesman problem, job scheduling, vehicle routing problems etc. that has not discovered yet. So, I can see the topic will be promising in lots of industrial areas in the future.

Jason Brownlee November 12, 2019 at 2:02 pm #

You can, but classical combinatorial optimization methods do these problems better and faster. E.g. you would not use it "at work", at least from what I can see.



Avram November 11, 2019 at 7:19 pm #



I think,in the near future, this topic and supervised and unsupervised models will be gathered to form strong AI.Knowing it may be well for anybody who is interested in AI.



Jason Brownlee November 12, 2019 at 6:36

Thanks for sharing.



marco November 12, 2019 at 6:53 pm #

Hello Jason, question about GAN.

Is possibile to implement a GAN only with KERAS? Is

Do you have an easy example to better undestand and try GAN?

What are possible fields of application of GAN?

Thanks,

Marco

Your Start in Machine Learning



You can master applied Machine Learning without math or fancy degrees.

Find out how in this free and practical course.

Email Address

START MY EMAIL COURSE



Jason Brownlee November 13, 2019 at 5:38 am #



Yes, you can implement GANs with Keras.

I have many examples, start here:

https://machinelearningmastery.com/start-here/#gans



Savan Vachhani November 13, 2019 at 12:53 am #



Hi Jason,

I am loving your website and all the work you have done for a beginner. A quick non-technical question though – why there isn't much stuff that uses Google's Colab? Any particular reason?

Thanks




Jason Brownlee November 13, 2019 at 5:47 am #

REPLY 🦴

Thanks!

I try to stay agnostic from platforms like google/ms/amazon. Run the code wherever you like.



SUBMIT COMMENT



Welcome! I'm Jason Brownlee PhD and I help developers get results with machine learning. Read More

Picked for you:



Your First Deep Learning Project in Python with Keras Step-By-Step



Your First Machine Learning Project in Python Step-By-Step



How to Develop LSTM Models for Time Series Fore



Why Machine Learning Does Not Have to Be So Ha



Machine Learning for Programmers

Your Start in Machine Learning

You can master applied Machine Learning without math or fancy degrees.

Find out how in this free and practical course.

X

Email Address

START MY EMAIL COURSE

Loving the Tutorials?

The EBook Catalog is where I keep the *Really Good* stuff.

SEE WHAT'S INSIDE

© 2019 Machine Learning Mastery Pty. Ltd. All Rights Reserved.

Address: PO Box 206, Vermont Victoria 3133, Australia. | ACN: 626 223 336.

RSS | Twitter | Facebook | LinkedIn

Privacy | Disclaimer | Terms | Contact | Sitemap | Search