

Second Assignment: Dataflow analysis

Carmine De Rosa
Manuel Gherardi
Arild Kuti

Contents

1	Very Busy Expressions	2
2	Dominator Analysis	5
3	Constant Propagation	8

1 Very Busy Expressions

An expression is defined as a *very busy expression* at a point p if any path starting from p uses the expression without redefining any of its operands. To identify them, we proceed backward, starting from the *Exit* basic block of the Control Flow Graph (CFG), applying the transfer function and using the intersection ($\cap$) as the meet operator.

Parameter	Definition
Domain	Sets of expressions
Direction	Backward: $in[b] = f_b(out[b])$, $out[b] = \wedge in[succ(b)]$
Transfer Function	$in[b] = Gen_b \cup (out[b] \setminus Kill_b)$
Meet Operation ($\wedge$)	Intersection ($\cap$)
Boundary Condition	$in[Exit] = \emptyset$
Initial Interior Points	$in[B] = U$ (Universal set)

Table 1: Very Busy Expressions parameters

Algorithm 1 Very Busy Expressions Algorithm

```

1:  $in[Exit] \leftarrow \emptyset$ 
2: for each basic block  $B \neq Exit$  do
3:    $in[B] \leftarrow U$ 
4: end for

5:  $changes \leftarrow true$ 
6: while  $changes$  do
7:    $changes \leftarrow false$ 
8:   for each basic block  $B \neq Exit$  do
9:      $out[B] \leftarrow \bigcap_{a \in succ(B)} in[a]$ 
10:     $in_{new} \leftarrow Gen_B \cup (out[B] \setminus Kill_B)$ 
11:    if  $in[B] \neq in_{new}$  then
12:       $in[B] \leftarrow in_{new}$ 
13:       $changes \leftarrow true$ 
14:    end if
15:   end for
16: end while

```




Figure 1: Very busy expression example CFG

Basic Block	Iteration 1		Iteration 2	
	IN[B]	OUT[B]	IN[B]	OUT[B]
BB1 (Entry)	$\{b - a\}$	$\{b - a\}$	$\{b - a\}$	$\{b - a\}$
BB2	$\{b - a\}$	$\{b - a\}$	$\{b - a\}$	$\{b - a\}$
BB3	$\{b - a, a - b\}$	$\{a - b\}$	$\{b - a, a - b\}$	$\{a - b\}$
BB4	$\{a - b\}$	$\emptyset$	$\{a - b\}$	$\emptyset$
BB5	$\{b - a\}$	$\emptyset$	$\{b - a\}$	$\emptyset$
BB6	$\emptyset$	$\{a - b\}$	$\emptyset$	$\{a - b\}$
BB7	$\{a - b\}$	$\emptyset$	$\{a - b\}$	$\emptyset$
BB8 (Exit)	$\emptyset$	$\emptyset$	$\emptyset$	$\emptyset$

Table 2: Iteration table for example CFG (we iterate on BBs in decreasing order)

2 Dominator Analysis

Dominator analysis is essential for building the Static Single Assignment (SSA) form and for finding natural loops in the Control Flow Graph (CFG). A node d dominates a node n if each path from the entry node to n passes through d .

Parameter	Dominator Analysis
Domain	Sets of Basic Blocks
Direction	Forward: $out[b] = f_b(in[b])$, $in[b] = \bigwedge out[pred[b]]$
Transfer Function	$out[b] = \{b\} \cup in[b]$
Meet Operation ($\wedge$)	Intersection ($\cap$)
Boundary Condition	$out[Entry] = \{Entry\}$
Initial Interior Points	$out[B] = U$ (Universal set)

Table 3: Dominator Analysis as a Dataflow problem

Algorithm 2 Dominator Analysis Algorithm

```

1:  $OUT[Entry] \leftarrow \{Entry\}$ 
2: for each basic block  $B \neq Entry$  do
3:    $OUT[B] \leftarrow U$ 
4: end for

5:  $changes \leftarrow \text{true}$ 
6: while  $changes$  do
7:    $changes \leftarrow \text{false}$ 
8:   for each basic block  $B \neq Entry$  do
9:      $IN[B] \leftarrow \bigcap_{p \in pred(B)} OUT[p]$ 
10:     $OUT_{new} \leftarrow \{B\} \cup IN[B]$ 
11:    if  $OUT[B] \neq OUT_{new}$  then
12:       $OUT[B] \leftarrow OUT_{new}$ 
13:       $changes \leftarrow \text{true}$ 
14:    end if
15:   end for
16: end while

```




Figure 2: Dominator analysis example CFG

Block	Iteration 1		Iteration 2	
	IN[B]	OUT[B]	IN[B]	OUT[B]
A (Entry)	$\emptyset$	$\{A\}$	$\emptyset$	$\{A\}$
B	$\{A\}$	$\{A, B\}$	$\{A\}$	$\{A, B\}$
C	$\{A\}$	$\{A, C\}$	$\{A\}$	$\{A, C\}$
D	$\{A, C\}$	$\{A, C, D\}$	$\{A, C\}$	$\{A, C, D\}$
E	$\{A, C\}$	$\{A, C, E\}$	$\{A, C\}$	$\{A, C, E\}$
F	$\{A, C\}$	$\{A, C, F\}$	$\{A, C\}$	$\{A, C, F\}$
G	$\{A\}$	$\{A, G\}$	$\{A\}$	$\{A, G\}$

Table 4: Iteration table for Dominator Analysis on the example CFG.

3 Constant Propagation

Constant Propagation is a global dataflow analysis designed to discover variables that are guaranteed to hold a single constant value at specific program points across all possible execution paths. By tracking pairs of $\langle \text{variable}, \text{constant} \rangle$, this analysis enables the compiler to substitute variable uses with their actual values and statically fold binary expressions whose operands are known constants, thereby optimizing execution efficiency.

Parameter	Definition
Domain	Sets of pairs $\langle \text{variable}, \text{value} \rangle$
Direction	Forward
	$in[B] = \wedge(out[pred(B)])$
	$out[B] = f_B(in(B))$
Transfer Function	$f_B(x) = Gen_B \cup (x \setminus Kill_B)$
Meet Operation ($\wedge$)	Intersection ($\cap$)
Boundary Condition	$in[entry] = \emptyset, out[entry] = \emptyset$
Initial Interior Points	$in[B] = U, out[B] = \emptyset$

Table 5: Constant Propagation parameters

Algorithm 3 Constant Propagation

```
1:  $in[Entry] \leftarrow \emptyset$ 
2:  $out[Entry] \leftarrow \emptyset$ 

3: for each basic block  $B \neq Entry$  do
4:    $in[B] \leftarrow U$ 
5:    $out[B] \leftarrow \emptyset$ 
6: end for

7:  $changes \leftarrow \text{true}$ 
8: while  $changes$  do
9:    $changes \leftarrow \text{false}$ 
10:  for each basic block  $B \neq Entry$  do
11:    // Meet operation: combine constants from all predecessors
12:     $in[B] \leftarrow \bigcap_{p \in pred(B)} out[p]$ 

13:    // Transfer function: apply constant folding
14:     $out_{new} \leftarrow f_B(in[B])$ 

15:    if  $out[B] \neq out_{new}$  then
16:       $out[B] \leftarrow out_{new}$ 
17:       $changes \leftarrow \text{true}$ 
18:    end if
19:  end for
20: end while
```




Figure 3: Constant Propagation example CFG

Basic Block	Iteration 1		Iteration 2	
	IN[B]	OUT[B]	IN[B]	OUT[B]
BB1 (Entry)	$\emptyset$	$\emptyset$	$\emptyset$	$\emptyset$
BB2	$\emptyset$	$\langle k, 2 \rangle$	$\emptyset$	$\langle k, 2 \rangle$
BB3	$\langle k, 2 \rangle$	$\langle k, 2 \rangle$	$\langle k, 2 \rangle$	$\langle k, 2 \rangle$
BB4	$\langle k, 2 \rangle$	$\langle k, 2 \rangle, \langle a, 4 \rangle$	$\langle k, 2 \rangle$	$\langle k, 2 \rangle, \langle a, 4 \rangle$
BB5	$\langle k, 2 \rangle, \langle a, 4 \rangle$	$\langle k, 2 \rangle, \langle a, 4 \rangle, \langle x, 5 \rangle$	$\langle k, 2 \rangle, \langle a, 4 \rangle$	$\langle k, 2 \rangle, \langle a, 4 \rangle, \langle x, 5 \rangle$
BB6	$\langle k, 2 \rangle$	$\langle k, 2 \rangle, \langle a, 4 \rangle$	$\langle k, 2 \rangle$	$\langle k, 2 \rangle, \langle a, 4 \rangle$
BB7	$\langle k, 2 \rangle, \langle a, 4 \rangle$	$\langle k, 2 \rangle, \langle a, 4 \rangle, \langle x, 8 \rangle$	$\langle k, 2 \rangle, \langle a, 4 \rangle$	$\langle k, 2 \rangle, \langle a, 4 \rangle, \langle x, 8 \rangle$
BB8	$\langle k, 2 \rangle, \langle a, 4 \rangle$	$\langle k, 4 \rangle, \langle a, 4 \rangle$	$\langle k, 2 \rangle, \langle a, 4 \rangle$	$\langle k, 4 \rangle, \langle a, 4 \rangle$
BB9	$\langle k, 4 \rangle, \langle a, 4 \rangle$	$\langle k, 4 \rangle, \langle a, 4 \rangle$	$\langle a, 4 \rangle$	$\langle a, 4 \rangle$
BB10	$\langle k, 4 \rangle, \langle a, 4 \rangle$	$\langle k, 4 \rangle, \langle a, 4 \rangle, \langle b, 2 \rangle$	$\langle a, 4 \rangle$	$\langle a, 4 \rangle, \langle b, 2 \rangle$
BB11	$\langle k, 4 \rangle, \langle a, 4 \rangle, \langle b, 2 \rangle$	$\langle k, 4 \rangle, \langle a, 4 \rangle, \langle b, 2 \rangle, \langle x, 8 \rangle, \langle y, 8 \rangle$	$\langle a, 4 \rangle, \langle b, 2 \rangle$	$\langle a, 4 \rangle, \langle b, 2 \rangle$
BB12	$\langle k, 4 \rangle, \langle a, 4 \rangle, \langle b, 2 \rangle, \langle x, 8 \rangle, \langle y, 8 \rangle$	$\langle k, 4 \rangle, \langle a, 4 \rangle, \langle b, 2 \rangle, \langle x, 8 \rangle, \langle y, 8 \rangle$	$\langle a, 4 \rangle, \langle b, 2 \rangle$	$\langle a, 4 \rangle, \langle b, 2 \rangle, \langle y, 8 \rangle$
BB13	$\langle k, 4 \rangle, \langle a, 4 \rangle, \langle b, 2 \rangle, \langle x, 8 \rangle, \langle y, 8 \rangle$	$\langle k, 5 \rangle, \langle a, 4 \rangle, \langle b, 2 \rangle, \langle x, 8 \rangle, \langle y, 8 \rangle$	$\langle a, 4 \rangle, \langle b, 2 \rangle, \langle y, 8 \rangle$	$\langle a, 4 \rangle, \langle b, 2 \rangle, \langle y, 8 \rangle$
BB14	$\langle k, 4 \rangle, \langle a, 4 \rangle$	$\langle k, 4 \rangle, \langle a, 4 \rangle$	$\langle a, 4 \rangle$	$\langle a, 4 \rangle$
BB15 (Exit)	$\langle k, 4 \rangle, \langle a, 4 \rangle$	$\langle k, 4 \rangle, \langle a, 4 \rangle$	$\langle a, 4 \rangle$	$\langle a, 4 \rangle$

Table 6: Constant Propagation Algorithm Execution Table

The third iteration is equal to the second one so we omitted it.